Form 3160-5 (June 2015)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

OCD Artesia

FORM APPROVED OMB NO. 1004-0137 Expires: January 31, 2018

Lease Serial No. NMNM07260

SUNDRY NOTICES AND REPORTS ON WELLS	
Do not use this form for proposals to drill or to re-enter an	
abandoned well. Use form 3160-3 (APD) for such proposals	١.

6. If Indian, Allottee or Tribe Name

						_			
SUBMIT IN TRIPLICATE - Other instructions on page 2					7. If Unit or CA/Agre 8910085010	eement, N	ame and/or No.		
 Type of Well Oil Well ☐ Gas Well ☐ Oth 		8. Well Name and No. INDIAN HILLS UNIT 24							
Name of Operator OXY USA WTP LIMITED PTN		9. API Well No. 30-015-31266-00-S1							
3a. Address		10. Field and Pool or Exploratory Area INDIAN BASIN-UPPER PENN ASSOC							
HOUSTON, TX 77210 Ph: 432-685-5717					INDIAN BASIN	-UPPE	R PENN ASSOC		
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)					11. County or Parish, State				
Sec 28 T21S R24E NWNE 68			EDDY COUNT	Y, NM					
12. CHECK THE AF	PPROPRIATE BOX(ES)	TO INDICA	ΓE NATURE OI	F NOTICE,	REPORT, OR OT	HER D	ATA		
TYPE OF SUBMISSION	TYPE OF ACTION								
Notice of Intent	☐ Acidize	☐ Dee	☐ Deepen		on (Start/Resume)	o w	ater Shut-Off		
_	☐ Alter Casing	☐ Hyd	raulic Fracturing 🔲 Reclam		ation	■ Well Integrity			
☐ Subsequent Report	Casing Repair	□ New	Construction	□ Recomp	lete	□ Other			
☐ Final Abandonment Notice	☐ Change Plans	☑ Plug	and Abandon	□ Tempora	arily Abandon				
13. Describe Proposed or Completed Ope	☐ Convert to Injection	Plug		□ Water D	-				
determined that the site is ready for fi TD-8700' PBTD-8645' Perfs 13-3/8" 54.5# csg @ 1200' w/ 9-5/8" 40-43.5# csg @ 8698', 1. RIH & set CIBP @ 7960' w. 2. M&P 35sx cmt @-7415-694 3. M&P 35sx cmt @ 5470-53' 4. M&P 45sx cmt @ 2590-236 5. M&P 25sx cmt @ 1250-113	Accepted to Accepted to OC-Surf-Circ (wc & bu	NOV 1 9 2019 DISTRICT/-ARTESIAO.C.D. SEE ATTACHED FOR							
6. M&P 170sx cmt @ 850' to surface 10# MLF between plugs-Above ground steel tanks will be utilized CONDITIONS OF APPROVAL							ROVAL		
14. I hereby certify that the foregoing is true and correct. Electronic Submission #489798 verified by the BLM Well Information System For OXY USA WTP LIMITED PTNRSHIP, sent to the Carlsbad Committed to AFMSS for processing by DEBORAH MCKINNEY on 10/25/2019 (20DLM0074SE)									
Name(Printed/Typed) DAVID STEWART			Title SR. REGULATORY ADVISOR						
Signature (Electronic S	Date 10/24/20)19							
THIS SPACE FOR FEDERAL OR STATE OFFICE USE									
Approved By James a. Como			Title S	£T			11-2-19 Date		
Conditions of approval. If any, are attached. Approval of this notice does not warrant or vertify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon. Office Office Office									
Fitle 18 U.S.C. Section 1001 and Title 43 States any false, fictitious or fraudulent s	U.S.C. Section 1212, make it a statements or representations as	crime for any pe	rson knowingly and thin its jurisdiction.	willfully to ma	ke to any department or	r agency (of the United		

OXY USA WTP LP - Current Indian Hills Unit #24 API No. 30-015-31266

SA	806
61	2416
Ye 50	2536
BS	5418
Sand	7094
w(7234
up	7946

PB-8645' /

TD-8700' -

17-1/2" hole @ 1200' 13-3/8" csg @ 1200' w/ 950sx-TOC-Surf-Circ -12-1/4" hole @ 8700' 9-5/8" csg @ 8698' w/ 2380sx-TOC-Surf-Circ -DVT @ 7065' Perfs @ 8010-8242'

OXY USA WTP LP - Proposed Indian Hills Unit #24 API No. 30-015-31266

170sx @ 850'-Surface

25sx @ 1250-1135' WOC-Tag

45sx @ 2590-2365' WOC-Tag

35sx @ 5470-5315' WOC-Tag

7284- 705 35sx @ 7115-6940' WOC-Tag

CIBP @ 7960' w/ 40sx to 7780'

TD-8700'

17-1/2" hole @ 1200' 13-3/8" csg @ 1200' w/ 950sx-TOC-Surf-Circ

12-1/4" hole @ 8700' 9-5/8" csg @ 8698' w/ 2380sx-TOC-Surf-Circ DVT @ 7065'

Perfs @ 8010-8242'

PB-8645'

BUREAU OF LAND MANAGEMENT Carlsbad Field Office 620 East Greene Street Carlsbad, New Mexico 88220 575-234-5972

Permanent Abandonment of Federal Wells Conditions of Approval

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

1. Plugging operations shall commence within <u>ninety (90)</u> days from the approval date of this Notice of Intent to Abandon.

If you are unable to plug the well by the 90th day provide this office, prior to the 90th day, with the reason for not meeting the deadline and a date when we can expect the well to be plugged. Failure to do so will result in enforcement action.

The rig used for the plugging procedure cannot be released and moved off without the prior approval of the authorized officer. Failure to do so may result in enforcement action.

- 2. <u>Notification:</u> Contact the appropriate BLM office at least 24 hours prior to the commencing of any plugging operations. For wells in Chaves and Roosevelt County, call 575-627-0272; Eddy County, call 575-361-2822; Lea County, call 575-393-3612.
- Blowout Preventers: A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The BOP must be installed and maintained as per API and manufacturer recommendations. The minimum BOP requirement is a 2M system for a well not deeper than 9,090 feet; a 3M system for a well not deeper than 13,636 feet; and a 5M system for a well not deeper than 22,727 feet.
- 4. Mud Requirement: Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at the rate of 25 sacks (50 pounds each) of gel per 100 barrels of brine water. Minimum nine (9) pounds per gallon.
- 5 <u>Cement Requirement</u>: Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. Any plug that requires a tag will have a minimum WOC time of 4 hours.

In heu of a cement plug across perforations in a cased hole (not for any other plugs), a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 25 sacks of cement. If a bailer is used to cap this plug, 35 feet of cement shall be sufficient. Before pumping or bailing cement on top of CIBP, tag will be required to verify depth. Based on depth, a tag of the cement may be deemed necessary.

Unless otherwise specified in the approved procedure, the cement plug shall consist of either Neat Class "C", for up to 7,500 feet of depth or Neat Class "H", for deeper than 7,500 feet plugs.

- 6. Dry Hole Marker: All casing shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). The BLM is to be notified a minimum of 4 hours prior to the wellhead being cut off to verify that cement is to surface in the casing and all annuluses. Wellhead cut off shall commence within ten (10) calendar days of the well being plugged. If the cut off cannot be done by the 10th day, the BLM is to be contacted with justification to receive an extension for completing the cut off.

 The well bore shall then be capped with a 4-inch pipe, 10-feet in length, 4 feet above ground and embedded in cement, unless otherwise noted in COA (requirements will be attached). The following information shall be permanently inscribed on the dry hole marker: well name and number, name of the operator, lease serial number, surveyed location (quarter-quarter section, section, township and range or other authorized survey designation acceptable to the authorized officer such as metes and bounds).
- 7. <u>Subsequent Plugging Reporting</u>: Within 30 days after plugging work is completed, file one original and three copies of the Subsequent Report of Abandonment, Form 3160-5 to BLM. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. <u>Show date well was plugged</u>.
- 8. <u>Trash:</u> All trash, junk and other waste material shall be contained in trash cages or bins to prevent scattering and will be removed and deposited in an approved sanitary landfill. Burial on site is not permitted.

Following the submission and approval of the Subsequent Report of Abandonment, surface restoration will be required. See attached reclamation objectives.