

Submit 1 Copy To Appropriate District Office

District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-103
Revised July 18, 2013

WELL API NO. 30-015-35539
5. Indicate Type of Lease STATE [ ] FEE [x]
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name DOUBLE DALE FEE COM
8. Well Number #001
9. OGRID Number 16696
10. Pool name or Wildcat MALAGA ATOKA (GAS)
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3298' GL

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)
1. Type of Well: Oil Well [ ] Gas Well [x] Other
2. Name of Operator OXY USA INC.
3. Address of Operator PO BOX 4294, HOUSTON, TX 77210
4. Well Location Unit Letter I : 1600 feet from the SOUTH line and 660 feet from the EAST line
Section 6 Township 24S Range 29E NMPM County EDDY

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:
PERFORM REMEDIAL WORK [ ] PLUG AND ABANDON [ ]
TEMPORARILY ABANDON [ ] CHANGE PLANS [ ]
PULL OR ALTER CASING [ ] MULTIPLE COMPL [ ]
DOWNHOLE COMMINGLE [ ]
CLOSED-LOOP SYSTEM [ ]
OTHER: [ ]
SUBSEQUENT REPORT OF:
REMEDIAL WORK [ ] ALTERING CASING [ ]
COMMENCE DRILLING OPNS. [ ] P AND A [x]
CASING/CEMENT JOB [ ]
OTHER: [ ]

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

12/26/19 MIRU, Notified NMOCD. PU unset pkr and scan out with tubing.
12/27/19 Casing and tubing on a slight vacuum. Circ to kill well with 117bbls FW. Function tested BOP. Pumped 6bbls brine down casing, 3bbls brine down tubing.
12/28/19 POOH with 2-3/8" tubing. Pumped 18bbls FW down casing, pressured up to 500 psi, held.
12/30/19 RIH with CCL and 3.75" gauge ring, tagged CIBP at 12000'. Circ 170bbls gel brine.
12/31/19 Spot 20sx class h cement on top of CIBP @ 12000'. WOC ~4 hrs. RIH and tag @ 11738'. POOH to 10182', pump 45sx class h cement (1.18 yield). POOH. WOC +4hrs.
1/2/20 RIH and tag @ 9782'. EOT at 8010'. perf guns at 8330', shot 6 holes, establish circulation.
1/3/20 RIH and set pkr at 8016', pump spacer and 12 bbls brine between cement, pumped 211bbls (900sx). POOH to 7042, circ 20bbls cement to pit. POOH.
1/6/20 RIH and tag @ 7188'. Ran CBL.
1/7/20 Contacted Gilbert Cordero with the NMOCD and reviewed CBL, agreed to do balanced plugs.
1/8/20 RIH EOT @ 6725'. Pump 55sx Class C (1.32 yld). WOC ~4hrs. Tag @ 6032'. EOT @ 4695' pump 35sx Class C (1.32yld). WOC +4hrs.
1/9/20 EOT @ 2785. Pump 55sx Class C (1.32yld). WOC ~4hrs. Tag @ 2115'. EOT @ 1660, Pump 35sx Class C (1.32yld) WOC +4hrs.
1/10/20 RIH and tag @ 1172'. EOT @ 430', pump 30sx Class C (1.32yld). Cement to surface. RDMO.

Approved for plugging of well bore only.
Liability under bond is retained pending receipt of C-103. (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms: www.enr.nm.gov/nmoecd.

Spud Date: [ ]

Rig Release Date: [ ]

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Leslie T. Reeves TITLE REGULATORY ADVISOR DATE 1/16/20

Type or print name LESLIE REEVES E-mail address: LESLIE\_REEVES@OXY.COM PHONE: 713-497-2492

For State Use Only

APPROVED BY: [Signature] TITLE Staff TITLE DATE 1/28/20

Conditions of Approval (if any):