

RECEIVED

Submit 1 Copy To Appropriate District Office

FEB 21 2020

State of New Mexico  
Energy, Minerals and Natural ResourcesForm C-103  
Revised July 18, 2013

District I - (575) 393-6161  
1625 N. French Dr., Hobbs, NM 88240  
District II - (575) 765-3333  
811 S. First St., Artesia, NM 88210  
District III - (505) 334-6178  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV - (505) 476-3460  
1220 S. St. Francis Dr., Santa Fe, NM 87505

ENRDO-OCDA-ARTESIA

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

WELL API NO.  
30-015-20459

5. Indicate Type of Lease  
STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

MERLAND A COM

8. Well Number #001

9. OGRID Number  
192463

10. Pool name or Wildcat  
CARLSBAD; STRAWN (GAS)

### SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☐ Gas Well ☒ Other

2. Name of Operator  
OXY USA WTP LP

3. Address of Operator  
PO BOX 4294, HOUSTON, TX 77210

4. Well Location

Unit Letter O : 660 feet from the SOUTH line and 1400 feet from the EAST line  
Section 19 Township 22S Range 27E NMPM County EDDY

11. Elevation (Show whether DR, RKB, RT, GR, etc.)

### 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

#### NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐  
DOWNHOLE COMMINGLE ☐  
CLOSED-LOOP SYSTEM ☐  
OTHER: ☐

#### SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ P AND A ☐  
CASING/CEMENT JOB ☐  
OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

TD-11,750' PBTD-11,188'  
Perfs-10,329' - 10,375'; CIBP @ 11230' w/ 4sx cmt to 11188';  
Closed-Off Perfs 11,318' - 11,654'

13-3/8" 48# csg @ 353' w/ 380sx, 15-1/2" hole, TOC-Surf-Circ  
9-5/8" 36# & 40# csg @ 5299' w/ 2150sx, DV-Tool @ 1556', 12-1/4" hole, TOC-Surf-Circ.  
5-1/2" 17# & 20# csg @ 11,749' w/ 1000sx, 8-3/4" hole, TOC--7470'

1. POOH with tubing. RIH & set CIBP @ 10279', M&P 25 sx class h cmt to 10088' WOC-Tag
  2. M&P 25sx class h cmt from 9590' to 9399' WOC-Tag
  3. M&P 75sx class h cmt from 8811' to 8233' WOC-Tag
  4. Perf at 6902', sqz 270sx class c cmt from 6970' to 6270' WOC-Tag
  5. Perf at 5899', sqz 115sx class c cmt from 5349' to 5188' WOC-Tag
  6. Perf at 2395', sqz 375sx class c cmt from 2445' to 1506' WOC-Tag
  7. Perf at 346', sqz 235sx class c cmt from 595' to Surface
- 10# MLF between plugs - Above ground steel tanks will be utilized

\*\*\* SEE ATTACHED COA'S-*Revised*  
MUST BE PLUGGED BY  
2/24/21

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

TITLE REGULATORY ADVISOR

DATE 2/20/20

Type or print name LESLIE REEVES

E-mail address: LESLIE\_REEVES@OXY.COM PHONE: 713-497-2492

For State Use Only


APPROVED BY:

TITLE Staff mgr

DATE 2/24/20

Conditions of Approval (if any):

OXY USA WTP LP - Current  
Merland A Com #001  
API No. 30-015-20459



Spud 06/25/1971

15-1/2" hole @ 354'  
13-3/8" 48# csg @ 353'  
w/ 380 sx-TOC-Surf-Circ.

12-1/4" hole @ 5300'  
9-5/8" 36# & 40# csg @ 5299'  
w/ 2150 sx-TOC-Surf-Circ.  
DV Tool@1556'

8-3/4" hole @ 11750'  
5-1/2" 17# & 20# csg @ 11749'  
w/ 1000 sx-TOC-7470'

2-3/8" tbg @ 10242'

PBTD - 11188'

Perfs 10329' - 10375'  
CIBP @ 11230 w/ 4sx cmt to 11188'  
Closed Off perfs - 11318' - 11654'

TD - 11750' TVD

Perf at 545', sqz 235sx class c cmt from 595' to Surface

Perf at 2395', sqz 375sx class c cmt from 2445' to 1506' WOC-Tag

Perf at 5299', sqz 115sx class c cmt from 5349' to 5188' WOC-Tag


Perf at 6902', sqz 270sx class c cmt from 6970' to 6270' WOC-Tag

M&P 75sx class h cmt from 8811' to 8233' WOC-Tag

M&P 25sx class h cmt from 9590' to 9399' WOC-Tag

RIH and set CIBP @ 10279' - M&P 25sx class h cmt to 10088' WOC-Tag

PBTD - 11188'



Spud 06/25/1971

15-1/2" hole @ 354'  
 13-3/8" 48# csg @ 353'  
 w/ 380 sx-TOC-Surf-Circ.

12-1/4" hole @ 5300'  
 9-5/8" 36# & 40# csg @ 5299'  
 w/ 2150 sx-TOC-Surf-Circ.  
 DV Tool@1556'

8-3/4" hole @ 11750'  
 5-1/2" 17# & 20# csg @ 11749'  
 w/ 1000 sx-TOC-7470'

Perfs 10329' - 10375'  
 CIBP @ 11230 w/ 4sx cmt to 11188'  
 Closed Off perfs - 11318' - 11654'

TD - 11750' TVD

## **CONDITIONS FOR PLUGGING AND ABANDONMENT**

### **OCD - Southern District**

The following is a guide or checklist in preparation of a plugging program, this is not all inclusive and care must be exercised in establishing special plugging programs in unique and unusual cases, Notify NMOCD District Office II at (575)-748-1283 at least 24 hours before beginning work. After MIRU rig will remain on well until it is plugged to surface. OCD is to be notified before rig down. Company representative will be on location during plugging procedures.

1. A notice of intent to plug and abandon a wellbore is required to be approved before plugging operations are conducted. A cement evaluation tool is required in order to ensure isolation of producing formations, protection of water and correlative rights. A cement bond log or other accepted cement evaluation tool is to be provided to the division for evaluation if one has not been previously run or if the well did not have cement circulated to surface during the original casing cementing job or subsequent cementing jobs. Insure all bradenheads have been exposed, identified and valves are operational prior to rig up.
2. Closed loop system is to be used for entire plugging operation. Upon completion, contents of steel pits are to be hauled to a permitted disposal location.
3. Trucking companies being used to haul oilfield waste fluids to a disposal – commercial or private – shall have an approved NMOCD C-133 permit. A copy of this permit shall be available in each truck used to haul waste products. It is the responsibility of the operator as well as the contractor, to verify that this permit is in place prior to performing work. Drivers shall be able to produce a copy upon request of an NMOCD Field inspector.
4. Filing a subsequent C-103 will serve as notification that the well has been plugged.
5. A final C-103 shall be filed (and a site inspection by NMOCD Inspector to determine if the location is satisfactorily cleaned, all equipment, electric poles and trash has been removed to Meet NMOCD standards) before bonding can be released.
6. If work has not begun within 1 Year of the approval of this procedure, an extension request must be file stating the reason the well has not been plugged.
7. Squeeze pressures are not to exceed 500 psi, unless approval is given by NMOCD.
8. Produced water will not be used during any part of the plugging operation.
9. Mud laden fluids must be placed between all cement plugs mixed at 25 sacks per 100 bbls of water.
10. All cement plugs will be a minimum of 100' in length or a minimum of 25 sacks of cement, whichever is greater. 50' of calculated cement excess required for inside casing plugs and 100% calculated cement excess required on outside casing plugs.
11. Class 'C' cement will be used above 7500 feet.
12. Class 'H' cement will be used below 7500 feet.
13. A cement plug is required to be set 50' above and 50' below, casing stubs, DV tools, attempted casing cut offs, cement tops outside casing, salt sections and anywhere the casing is perforated, these plugs require a 4 hour WOC and then will be tagged
14. All Casing Shoes Will Be Perforated 50' below shoe depth and Attempted to be Squeezed, cement needs to be 50' above and 50' Below Casing Shoe inside the Production Casing.

16. When setting the top out cement plug in production, intermediate and surface casing, wellbores should remain full at least 30 minutes after plugs are set.
17. A CIBP is to be set within 100' of production perforations, capped with 100' of cement, WOC 4 hours and tag.
18. A CIBP with 35' of cement may be used in lieu of the 100' plug if set with a bailer. This plug will be placed within 100' of the top perforation, (WOC 4 hrs and tag).
19. No more than 3000' is allowed between cement plugs in cased hole and 2000' in open hole.
20. Some of the Formations to be isolated with cement plugs are: These plugs to be set to isolate formation tops
  - A) Fusselman
  - B) Devonian
  - C) Morrow
  - D) Wolfcamp
  - E) Bone Springs
  - F) Delaware
  - G) Any salt sections
  - H) Abo
  - I) Glorieta
  - J) Yates.
  - K) Potash--- (In the R-111-P Area (Potash Mine Area), a solid cement plug must be set across the salt section. Fluid used to mix the cement shall be saturated with the salts that are common to the section penetrated and in suitable proportions, not more than 3% calcium chloride (by weight of cement) will be considered the desired mixture whenever possible, WOC 4 hours and tag, this plug will be 50' below the bottom and 50' above the top of the Formation.
21. If cement does not exist behind casing strings at recommended formation depths, the casing can be cut and pulled with plugs set at recommended depths. If casing is not pulled, perforations will be shot and cement squeezed behind casing, WOC and tagged. These plugs will be set 50' below formation bottom to 50' above formation top inside the casing

#### **DRY HOLE MARKER REQUIREMENTS**

The operator shall mark the exact location of the plugged and abandoned well with a steel marker not less than four inches in diameter, 3' below ground level with a plate of at least ¼" welded to the top of the casing and the dry hole marker welded on the plate with the following information welded on the dry hole marker:

1. Operator name 2. Lease and Well Number 3. API Number 4. Unit Letter 5. Quarter Section (feet from the North, South, East or West) 6. Section, Township and Range 7. Plugging Date  
 B. County (SPECIAL CASES)-----AGRICULTURE OR PRARIE CHICKEN BREEDING AREAS

In these areas, a below ground marker is required with all pertinent information mentioned above on a plate, set 3' below ground level, a picture of the plate will be supplied to NMOCD for record, the exact location of the marker (longitude and latitude by GPS) will be provided to NMOCD (We typically require a current survey to verify the GPS)

#### **SITE REMEDIATION DUE WITHIN ONE YEAR OF WELL PLUGGING COMPLETION**