

Submit 1 Copy To Appropriate District Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

RECEIVED

FEB 26 2020

State of New Mexico
Energy, Minerals and Natural Resources
OIL CONSERVATION DIVISION
St. Francis Dr.
Santa Fe, NM 87505

Form C-103
Revised July 18, 2013

WELL API NO.
30-015-45367

5. Indicate Type of Lease
STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

Berry SWD

8. Well Number 1

9. OGRID Number 371643

10. Pool name or Wildcat
SWD: Devonian-Silurian

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☐ Gas Well ☐ Other SWD

2. Name of Operator
Solaris Water Midstream, LLC

3. Address of Operator
907 Tradewinds Blvd, Suite B, Midland, TX 79706

4. Well Location

Unit Letter D : 690 feet from the North line and 220 feet from the West line
Section 20 Township 24S Range 29E NMPM Eddy County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
2954' GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐
CLOSED-LOOP SYSTEM ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐
OTHER: TD, RR, Tbg & Acid ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

1/24/2020: Drilled 6-1/2" hole to TD 15,650'. OH 14,640' - 15,650'
1/30/2020: Release Rig
1/31/2020: Run 5-1/2" 20 ppf HCP 110 tbg to 9782'.
Run 5" 18 ppf P-110 tbg to 14,609'.
Run 4-1/2" Nickel Alloy tbg to 14,623'.
Halliburton Nickel Alloy 925 Pkr @ 14,613'.
2/7/2020: Acidize with: 81,000 gal 15% NEFE acid.
Avg Rate 15 bpm, Max Rate 20.5 bpm
Avg PSI 275 psi, Max PSI 2850 psi.

Spud Date:

12/17/2019

Rig Release Date:

1/30/2020

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Bonnie Atwater TITLE Reg Tech DATE 2/21/2020

Type or print name Bonnie Atwater E-mail address: bonnie.atwater@solarismidstream.com PHONE: 432-203-9020

For State Use Only

APPROVED BY: [Signature] TITLE Staff DATE 2/27/20

Conditions of Approval (if any):

KS 2-27-20