District I 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico

(

Energy, Minerals and Natural Resources Department Submit Original

MCF/D

Oil Conservation Division

to Appropriate

1220 South St. Francis DEMNRI Santa Fe, NM 87505

Date: 10/31/2018	GAS CAPTURE PLA	N			
☑ Original☐ Amended - Reason for Amendment:	Operator & OGRID N	o.: <u>XTO Pe</u>	rmian Operati	ing, LLC [260737]	<u> </u>
This Gas Capture Plan outlines actions to b new completion (new drill, recomplete to ne		reduce we	ll/production	facility flaring/ver	nting fo
Note: Form C-129 must be submitted and approve	d prior to exceeding 60 days all	lowed by Rule	e (Subsection A	of 19.15.18.12 NMA	<i>C)</i> .
Well(s)/Production Facility – Name of fac	ility				
The well(s) that will be located at the produc	ction facility are shown in the	he table bel	ow.		
Well Name API W	ell Location Footages	Expected	Flared or	Comments	

Big Eddy Unit DI5 BS2- 1E 339H	,	G-27-20S-31E	1950'FNL & 1873'FEL	2500 MCF/D	Sold	CTB Connected

Gathering System and Pipeline Notification

Well(s) will be connected to a production facility after flowback operations are complete, if gas transporter system is in place. The gas produced from production facility is dedicated to DCP Midstream and will be connected to DCP Midstream low/high pressure gathering system located in Eddy County, New Mexico. It will require 0' of pipeline to connect the facility to low/high pressure gathering system. XTO Permian Operating, LLC. provides (periodically) to DCP Midstream a drilling, completion and estimated first production date for wells that are scheduled to be drilled in the foreseeable future. In addition, XTO Permian Operating, LLC. and DCP Midstream have periodic conference calls to discuss changes to drilling and completion schedules. Gas from these wells will be processed at DCP Midstream Processing Plant located in Sec. 19_, Twn. 19S, Rng. 32E, Eddy County, New Mexico. The actual flow of the gas will be based on compression operating parameters and gathering system pressures.

Flowback Strategy

After the fracture treatment/completion operations, well(s) will be produced to temporary production tanks and gas will be flared or vented. During flowback, the fluids and sand content will be monitored. When the produced fluids contain minimal sand, the wells will be turned to production facilities. Gas sales should start as soon as the wells start flowing through the production facilities, unless there are operational issues on DCP Midstream system at that time. Based on current information, it is XTO Permian Operating, LLC's belief the system can take this gas upon completion of the well(s).

Safety requirements during cleanout operations from the use of underbalanced air cleanout systems may necessitate that sand and non-pipeline quality gas be vented and/or flared rather than sold on a temporary basis.

Alternatives to Reduce Flaring

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.

- Power Generation On lease
 - Only a portion of gas is consumed operating the generator, remainder of gas will be flared
- Compressed Natural Gas On lease
 - o Gas flared would be minimal, but might be uneconomical to operate when gas volume declines
- NGL Removal On lease
 - Plants are expensive, residue gas is still flared, and uneconomical to operate when gas volume declines