

Submit 3 Copies To Appropriate District  
Office  
District I  
1625 N. French Dr., Hobbs, NM 88240  
District II  
811 South First, Artesia, NM 88210  
District III  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV  
1220 S. St. Francis Dr., Santa Fe, NM  
87505

State of New Mexico  
Energy, Minerals and Natural Resources  
OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

Form C-103  
Revised May 27, 2004

WELL API NO.  
30-015-24824

5. Indicate Type of Lease

STATE ☐ FEE ☒

6. State Oil & Gas Lease No.  
LC-050572 UNIT

7. Lease Name or Unit Agreement  
Name: Big Eddy 100

8. Well No. 100

9. OGRID Number: 161968

10. Pool name or Wildcat  
NW Fenton Delaware

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil Well ☐ Gas Well ☐ Other SWD

2. Name of Operator  
Mesquite SWD, Inc.

3. Address of Operator  
P.O. Box 1479 Carlsbad, NM 88220

4. Well Location

Unit Letter L : 2291 feet from the FSL line and 483 feet from the FWL line

Section 8 Township 21-S Range 28E NMPM County Eddy

10. Elevation (Show whether DR, RKB, RT, GR, etc.)

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☒ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☒ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

April 26: MI pulling unit, bled down well. TOH. PU work string bit and scrapper cleaned out to 3550' SDFD

April 27: TOH PU packer set at 3100' treated bottom perf. with 1500 gal. acid. TOH PU plug and packer set plug at 3100' packer at 2820' treated with 1500 gal of acid. Pressure down to 480#.

May: ran 30 minute chart, held, notify Jerry Guye- OCD. Put back into production.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Clay Wilson TITLE V.P. DATE 5-22-2006

Type or print name Clay L. Wilson Telephone No. 505-885-3996

(This space for State use)

APPROVED BY Gerry Guye TITLE Deputy Field Inspector DATE MAY 26 2006  
Conditions of approval, if any: District II - Artesia

