District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Form C-144 June 1, 2004

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 For drilling and production facilities, submit to appropriate NMOCD District Office.

For downstream facilities, submit to Santa Fe office

Pit or Below-Grade Tank Registration or Closure
Is pit or below-grade tank covered by a "general plan"? Yes \(\subseteq No \subseteq \)

Type of action: Registration of a pit or below-grade tank 🔲 Closure of a pit or below-grade tank 🐹		
Operator: Kaiser Francis Oil Co Telephone: 432-563-2992 e-mail address: DAVIDR & KFOC. NET		
Address: 11722 W Hwy 80 E Odessa Tx 79765		
Facility or well name: Mesa 11 Grande #2 API #: 30 -015 - 33720 U/L or Qtr/Qtr L Sec 11 T 225 R 26E		
Address: 11727 W Hwy 80 E Odessa Tx 79765 Facility or well name: Mesa Grande #2 API #: 30-015-33720 U/L or Qtt/Qtr L Sec T 225 R 26E County: Eddy Latitude 32° 14' 48.8" Longitude 103° 30' 34.7" NAD: 1927 1983		
Surface Owner: Federal State Private M Indian		
Pit	Below-grade tank	
Type: Drilling X Production Disposal	Volume:bbl Type of fluid:	
Workover ☐ Emergency ☐	Construction material:	
Lined 🔀 Unlined 🗌	Double-walled, with leak detection? Yes If not, explain why not.	
Liner type: Synthetic M Thickness 12 mil Clay		
Pit Volume 42,000 bbl		
	Less than 50 feet	(20 points)
Depth to ground water (vertical distance from bottom of pit to seasonal	50 feet or more, but less than 100 feet	(10 points) /D
high water elevation of ground water.)	100 feet or more	(0 points)
	Yes	(20 points)
Wellhead protection area: (Less than 200 feet from a private domestic	No.	(0 points)
water source, or less than 1000 feet from all other water sources.)	No	(o points)
Distance to surface water: (horizontal distance to all wetlands, playas,	Less than 200 feet	(20 points)
irrigation canals, ditches, and perennial and ephemeral watercourses.)	200 feet or more, but less than 1000 feet	(10 points)
Apox1500' to Hackberry Draw	1000 feet or more	(0 points)
THE PLANT OF THE PARTY OF THE P	Ranking Score (Total Points)	10
If this is a nit closure. (1) Attach a diagram of the facility chawing the nit	e relationship to other equipment and tanks (2) In	
If this is a pit closure: (1) Attach a diagram of the facility showing the pit's relationship to other equipment and tanks. (2) Indicate disposal location: (check the onsite box if		
your are burying in place) onsite 🖾 offsite 🗀 If offsite, name of facility		
remediation start date and end date. (4) Groundwater encountered: No Tyes, show depth below ground surface ft. and attach sample results.		
(5) Attach soil sample results and a diagram of sample locations and excavations.		
Additional Comments:		
	·	
I haraby cartify that the information above is true and complete to the base		
hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that the above-described pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines [3], a general permit [1], or an (attached) alternative OCD-approved plan [1].		
	^	
Date: 6-10-06		
Printed Name/Title Shelly J. Tucker representative Signature Shelly Jucker		
Your certification and NMOCD approval of this application/closure does not relieve the operator of liability should the contents of the pit or tank contaminate ground water or otherwise endanger public health or the environment. Nor does it relieve the operator of its responsibility for compliance with any other federal, state, or local laws and/or regulations.		
	bundany	
Approval: Gerry Guye	18 my ony	D. ILIN 9 & 2006
Printed Name/Title Pointly Field Inspector	Signature /	5. ILIN 97 M / ILIN /

District II - Artesia

CLOSURE PLAN Drilling Pit

MESA GRANDE 11-2 11-22S-26E Unit L

- 1. Dig an appropriate sized trench next to the outer wall of pit.
- 2. Line with 12mil pit liner.
- 3. Remove drill cuttings and primary liner from pit and place in lined trench.
- 4. Inspect ground for any liner breaches.
- 5. Remove any necessary contaminant and place in lined trench.
- 6. Take soil samples if necessary and contact OCD regarding such samples.
- 7. Cover top of trench with 20mil plastic.
- 8. Place three feet of top soil on trench and old pit area so that area will be at the grade of surrounding area.

Signed

Sherry Sucker Shelly J. Tucker

Valley Energy Services Rep: Kaiser Francis Oil Co