State of New Mexico Energy, Minerals and Natural Resources Department

Form C-103 Revised 1-1-89

DISTRICT I	OIL CONSERVATION	N DIVISION	r.::2:	
P.O. Box 1980, Hobbs, NM 88240	2040 Pacheco St.		WELL API NO.	
DISTRICT II	Santa Fe, NM 8	78970	30-015-32845	
P.O. Drawer DD, Artesia, NM 88210	245	0,777/2	sIndicate Type of Lea	
DISTRICT III	\(\sigma^3\)		₀State Oil & Gas Lea	
1000 Rio Brazos Rd., Aztec, NM 87410	//	" 3003 E	E-5073	SC 110.
DISTRICT II P.O. Drawer DD, Artesia, NM 88210 DISTRICT III 1000 Rio Brazos Rd., Aztec, NM 87410 OIL CONSERVATION DIVISION 2040 Pacheco St. Santa Fe, NM 87595 9 70 77 SINDER STATE FEE S				
(DO NOT USE THIS FORM FOR PROPO DIFFERENT RESERVO	DEPLYG BACK TO A	₁Lease Name or Uni	t Agreement Name	
DIFFERENT RESERVO	DIR. USE "APPLICATION ROR PER 1) FOR SUCH PROPOSALS.)	MOT. L	Winchester 36	•
Type of Well:		700/		
OIL GAS WELL WELL	OTHER OTHER	3542527270	<u> </u>	
2Name of Operator			sWell No.	
Mewbourne Oil Company 14744			1	
3Address of Operator PO Box 5270, Hobbs, New Mexico			Pool name or Wildcat Winchester Morrow	
PO Box 5270, Hobbs, New Mexico Well Location				III UVV
1/ 4000	eet From The South	Line and1980	Feet From The	West Line
Section 36	Township 19S	Range 28E	NMPM	Eddy County
	10Elevation (Show whether DF,			
3293' GL				
Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data				
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:				
PERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WORK		ALTERING CASING
TEMPORARILY ABANDON	CHANGE PLANS	COMMENCE DRILLING OF	PNS.	PLUG AND ANBANDONMENT
PULL OR ALTER CASING		CASING TEST AND CEME		
OTHER:		OTHER:		
	Closely state all porting at distance and distance		timotod data of starti-	any proceed
¹² Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.				
07/01/03Mi & spud 17 1/2" hole. TD'ed 17 1/2" hole @ 311'. Ran 311' 13 3/8" H-40 ST/C csg. Cemented w/ 200 sks BJ Lite 'C' w/ additives. Mixed @ 12.5 #/g w/ 1.97cf/sk yd. Tailed w/ 200 sks 'C' w/ 2% CaCl2. Mixed @ 14.8 #/g w/ 1.34 cf/sk yd.				
Circl 25 sks to pit. WOC 18 hrs. Tested BOP to 1000 psi. Drill out w/ 12 1/4" bit.				
07/07/03TD'ed 12 1/4" hole @ 2595'. Ran 2595' 8 5/8" J-55 ST/C csg. Cemented w/ 925 sks BJ Lite 'C' w/ additives. Mixed @				
07/07/031D'ed 12 1/4" hole @ 2595". Ran 2595"8 5/8" J-55 S1/C csg. Cemented W/ 925 sks BJ Lite 'C' W/ additives, Mixed @ 12.5 #/g w/ 1.96 cf/sk yd. Tailed w/ 200 sks 'C' w/ 2% CaCl2. Mixed @ 14.8 #/g w/ 1.34 cf/sk yd. Circl 98 sks to pit.				
WOC 18 hrs. Tested BOP & Equipment to 2500 psi. Drill out w/ 7 7/8" bit.				
I hereby certify that the information above is true and complete to the best of my knowledge and belief.				
~ A al		rLE District Manager		DATE 07-31-03
SIGNATURE	TI	ILE DISTRICT MAILAGE		DATE 07-31-03
TYPE OR PRINT NAME N.M. Young				TELEPHONE NO. 505-393-5905
(This space for State Use)				A110 A
·				AUG 0 7 2003
APPROVED BY				DATE
CONDITIONS OF APPROVAL, IF AN FOR RE	CORDS ONLY			

The second section of the second section is a second section of the second section of the second section is a second section of the second section of the second section is a second section of the section of the second section of the section of the second section of the section o