Foam 3160-5 (April 2004)

FORM APPROVED OM B No. 1004-0137 Expires: March 31, 2007

			OF LAND MANA				88210	5. Lease Serial No).		
SUNDRY NOTICES AND REPORTS ON WELLSED SO TO THE PART OF THE PART O								6. If Indian, Allottee or Tribe Name			
SUBMIT IN TRIPLICATE- Other instructions on reverse side &									7. If Unit or CA/Agreement, Name and/or No.		
1. Type of Well Of Well ☐ Oil Well ☑ Gas Well ☐ Other								8. Well Name and No.			
2. Name of Operator Nadel and Gussman Perm					LC		 ,	•		Federal Com #1	
								9. API Well No.			
3a. Address 601 N. Marienfeld, Suite 508 Midland, TX 79701				3b. Pho	one No. (include are (432) 682-			30-015-347		- Cuntomatory Area	
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)					(432) 082-		10. Field and Pool, or Exploratory Area Draw, Morrow, North				
UL H Sec. 8-T25S-R27E 1460' FNL & 1310' FEL								1 1. County or Parish, State Eddy County, NM			
12. CHECK APPROPRIATE BOX(ES) TO					ATÉ NATURE	OTICE, RE					
TYPE OF SU	BMISSION				ТҮРЕ	OF A	CTION	-			
	MEMORY .		Acidize		Deepen			Start/Resume)		Water Shut-Off	
□ Notice of I	Intent	154	Alter Casing		Fracture Treat		Reclamation	,		Well Integrity	
Subsequent	Subsequent Report		Casing Repair		New Construction		Recomplete			Other	
☐ Final Abandonment Notice			Č		Plug and Abandon Plug Back		Temporarily		_		
- I mai Abandonment Notice		_	Convert to Injection		Trug Buck		Water Dispo	sal	_		
•	s been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has ad that the site is ready for final inspection.) Day 18 Depth 6,406' Footage 0'. Continue lay down 8" collars and BHA. Rig up casing crew and run 6406' of 9 5/8"casing as follows: 6406'-4300': 9 5/8"/40#/P110/LTC and 4300'-0': 9 5/8"/40#/N80/LTC. Casing set at 6405', FC at 6310'. Rig up Schlumberger and cement with 1483 sx 50/50 poz c and 200 sx class "C". Displace with 480 bbls and bump plug. Did not circulate. At report time, nipple down BOP's and WOC. Will check cement depth and proceed as necessary after WOC. WOC for 24 hours.										
8/07/06	approved dum	19 Depth 6,406' Footage 0'. RIH with plumb bob on tally tape and tag cement at 95'. Onsite BLM representative (Jerry Blakely) oved dumping redi mix to top out. Dump 4 yards of redi mix and top out cement. Set slips and cut off pipe, install B section and test 500 psi. Install and test BOP's, and test choke manifold, valves, etc. Slip and change drilling line.									
08/08/06	Tag cement at	6310'. D	rill cement from 6310	'-6372',	test casing to 150	0 psi, c	irill out ceme	ent and begin dri		PTED FOR RECO	
	rtify that the fore ntedITyped) Joel M		rue and correct		Title Dr	illing	Manager	PE	G.	ARY GOURLEY PLEUM ENGINEER	
Signature	Val	M	and a		Date	7-/	1-06				
		THIS	SPACE FOR	FEDE	RAL OR ST	ATE	OFFICE	USE			
					Titl	Δ		Dat			
certify that the ap	pplicant holds lega	l or equital	Approval of this notice ble title to those rights i		warrant or		Ac	cepted for re-		- NMOCD	
which would enti	tle the applicant to	conduct o	perations thereon.								

Title 18 U.S.C. Section 1001 and Tide 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.