Submit 3 Copies To Appropriate District Office District I State of New Mexico Energy, Minerals and Natural Resources	Form C-103 May 27, 2004
1625 N. French Dr., Hobbs, NM 88240	WELL API NO. 30-015-31973
District II 1301 W. Grand Ave., Artesia, NM 88210 OIL CONSERVATION DIVISION	5. Indicate Type of Lease
District III 1220 South St. Francis Dr.	STATE X FEE
District IV Santa Fe, NIA 84309	6. State Oil & Gas Lease No.
District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505	LS 4146
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR READ BACK TO ADDIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (EORM G-10) FOR SUCH	7. Lease Name or Unit Agreement Name POKER LAKE UNIT
PROPOSALS.) 1. Type of Well: Oil Well Gas Well Other April	8. Well Number 186
2. Name of Operator	9. OGRID Number 001801
BEPCO, L.P. 3. Address of Operator P. O. BOX 2760	10. Pool name or Wildcat
MIDLAND, TX 79706-2760	NASH DRAW-DEL/BS/AVALON SAND
4. Well Location	
Unit Letter K: 1750 feet from the South line and 165	feet from the West line
Section 32 Township 23S Range 30E	NMPM CountyEddy
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3270' GL	
Pit or Below-grade Tank Application or Closure	大百0 00000000000000000000000000000000000
Pit type Depth to Groundwater Distance from nearest fresh water well Distance fresh water well Distance from nearest fresh water well Distance fresh water well	ance from nearest surface water
	nstruction Material
12. Check Appropriate Box to Indicate Nature of Notice,	Report or Other Data
NOTICE OF INTENTION TO: SUB	SEQUENT REPORT OF:
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORLD	
TEMPORARILY ABANDON	LLING OPNS.□ P AND A □
PULL OR ALTER CASING	JOB
OTHER:DRILLING OPERATIONS X OTHER:	П
13. Describe proposed or completed operations. (Clearly state all pertinent details, and	give pertinent dates, including estimated date
of starting any proposed work). SEE RULE 1103. For Multiple Completions: Att	tach wellbore diagram of proposed completion
or recompletion.	
Spudded well 8/18/06. Drilled 12-1/4" hole to 518'. Ran 12 jts 8-5/8", 32#, K-55 LTC casi water spacer ahead of 150 sx Thixotropic cmt (wt 14.2, yld 1.60) followed by 100 sx 65/35	
1/8 pps D130 (wt 12.8, yld 1.88) lead and 250 sx Class C + 2% CaCl2 (wt 14.8, yld 1.35)	tail. Topped out with 270 sx Class C + 2%
CaCl2 (wt 14.8, yld 1.35). Circ 20 sx to surface. WOC 23 1/2 hrs. Tested csg to 1000 psi, 1	
36 jts 5-1/2", 17# amd 148 jts 15.50#, J-55, LTC csg. Cemented with 900 sx Litecrete + 2 + 0.03 gps M45 + 0.4 gps D801 (wt 10.2, yld 2.40) lead and 275 sx Litecrete + 2 pps D53	
M45 + 0.04 D801 (wt 10.5, yld 2.07) tail. TOC by temperture survey 2840'. Rig released o	
I hereby certify that the information above is true and complete to the best of my knowledge grade tank has been/will be constructed or closed according to NMOCD guidelines , a general permit	e and belief. I further certify that any pit or below-
SIGNATURE MOST WITH A TITLE Administrative Assista	
Type or print name Annette Childers E-mail address:machilders@ For State Use Only	basspet.com Telephone No. (432)683-2277
FOR RECORDS ONLY	SEP 1 5 2006
APPROVED BY:TITLE	DATE
Conditions of Approval (if any):	

PRECISION PRESSURE DATA, INC.

TEMPERATURE SURVEY REPORT

Company _	BASS ENTERPRISES		Lease	POKER LAKE UNIT	Well#	186	
Field			County	EDDY	State	NEW MEXICO	
Gurvey Date	9/7/06		Time	19:51	Company Rep.	TERRY BARRON	
Top of Cemi Total Depth		ent	2840				
			7600				
	Zero @ Plug Down @			GL			
			3	9/6/06 @ 10:00			
		Casing Size		5 1/2			
		Hole Size		7 7/8			
		Sacks of Cer	ment				
		Ran By		C. HOMER			
		Calculated By	y	D. WEST			

TEMPERATURE SURVEY REPORT

