Form 3160-5 (April 2004)

## UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED OMB NO. 1004-0137 Expires March 31, 2007

5. Lease Serial No.

NM~969107

abandoned well. Use Form 3160-3 (APD) for such proposals.  SUBMIT IN TRIPLICATE - Other instructions on reverse side					/Agreement, Name and/or No.	
SUBMIT IN TRIPLICATE - Other instructions on reverse side				East Millman Pool Unit		
1. Type of Well  X Oil Well Gas Well Other  2. Name of Operator Stephens & Johnson Operating Co.				8910169240 8. Well Name ar Tract 6 Well 9. API Well No.	1 No. 9	
3a. Address	3b. Phone No. (include area code)		30-015-3488			
P.O. Box 2249 Wichita Falls TX 76307-2249		(940) 723-2166		10. Field and Pool, or Exploratory Area		
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)				Millman (Yates-SR-QN-GB-SA)		
Sec 13, T19S, R28E					East	
2143 FNL, 2106 FEL			11. County or I			
				Eddy	NM	
12. CHECK APPROPRIATE	BOX(ES) TO INC	DICATE NATURE OF	NOTICE, REP	ORT, OR OTH	ER DATA	
TYPE OF SUBMISSION		TY				
Notice of Intent  X Subsequent Report	Acidize Alter Casing Casing Repair	Deepen Fracture Treat New Construction	Production Reclamation		Water Shut-Off Well Integrity  X Other Drill	
Final Abandonment Notice	Change Plans Convert to Injectic	Plug and Abandon  Plug Back		ily Abandon	and Complete	
3. Describe Proposed or Completed Operation (clearly If the proposal is to deepen directionally or recomp Attach the Bond under which the work will be per following completion of the involved operations. I testing has been completed. Final Abandonment by determined that the final site is ready for final inspect	lete horizontally, give so formed or provide the left the operation results in Notices shall be filed on	ubsurface locations and mea Bond No. on file with BLM a multiple completion or a	asured and true ve MBIA. Required streets recompletion in a	rtical depths of all subsequent reports new interval, a Fo	pertinent markers and zones. shall be filed within 30 days rm 3160-4 shall be filed once	
SEE ATTA	CHED					

14. I hereby certify that the foregoing is true and correct Name (Printed/Typed)	Title				
Name (Printed/Typed) William M. Kincajd	Petroleum Engineer				
Will M. Kucan	Date 10-5-06				
THIS SPACE FOR FEDERAL OR STATE OFFICE USE					
Approved by	Title	Date			
Conditions of approval, if any, are attached. Approval of this notice does not warrant certify that the applicant holds legal or equitable title to those rights in the subject le which would entitle the applicant to conduct operations thereon.	or Office				

Title 18 U.S.C. Section 1001, and Title 43 U.S.C. Section 1212, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

EAST MILLMAN 6-9 FORM 3160-5 EDDY COUNTY, NM

- Spudded 12 1/4" hole 6:00 pm 8-14-06. Drilled to 346' KB and ran 8 jts 8 5/8" 24#/ft surface csg and cemented w/200 sx of cement. Cement circulated to surface (circulate 5 sx to pit). WOC 18 hrs. Pressure test BOP and 8 5/8" surface casing to 1,000 psig for 30 minutes. Held OK.
- 2. Drilled 7 7/8" hole to 2715' KB. Ran 67 jts 5 1/2", 15.50#/ft csg, set @ 2703' KB. Cemented w/725 sx of cement. Plug down @ 8:00 am 8-20-06. TOC @ 330' KB (CBL).
- 3. Test 5 1/2" production casing to 1,500 psig for 30 minutes. Held OK. Perforated Grayburg formation 1 SPF at the following intervals: 2401'-2413', 2427'-2440', 2465'-2480' KB.
- 4. On 9-6-06 acidized perforations w/3,000 gals 15% NEFE.
- 5. On 9-7-06 sand fraced perforations w/103,500 gals 10 lb brine water, 20,000 lbs of BJ LiteProp 125, and 5,000 lbs Super LC 16/30 sand.