Submit 3 Copies To Appropriate District Office		New Mexico	Form C-103
District I	Energy, Minerals and Natural Resources		May 27, 2004 WELL API NO.
1625 N. French Dr., Hobbs, NM 88240 District II			30-015-35557
1301 W. Grand Ave., Artesia, NM 8840		ATION DIVISION	5. Indicate Type of Lease
District III 1000 Rio Brazos Rd., Aztec, NM 87449		St. Francis Dr.	STATE FEE
District IV	Santa Fe	e, NM 87505	6. State Oil & Gas Lease No.
1220 S. St. Francis Dr., Santa Fe, NM 87505			
SUNDRY NOTICES AND REPORTS ON WELLS			7. Lease Name or Unit Agreement Name
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH			Colt State
PROPOSALS.)			8. Well Number 001
	Well 🛛 Other	OCT 0 1 2007	
2. Name of Operator OGX Resource	e II C		9. OGRID Number 217955
3. Address of Operator	os, LLC	OCD-ARTESIA	10. Pool name or Wildcat
-	idland, TX 79702		Salt Draw; Morrow West (Gas)
4. Well Location			
Unit LetterE_:1980feet from the _North line and _660feet from theWestline			
Section 5 Township 25S Range 28E NMPM Eddy County			
11	1. Elevation (Show wh	ether DR, RKB, RT, GR, etc	
3029' GR  Pit or Below-grade Tank Application  or Closure			
		rest fresh water well Di	stance from nearest surface water
Pit Liner Thickness: mil	Below-Grade Tank: Vol		Construction Material
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data			
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:			
· · · · · · · · · · · · · · · · · · ·	LUG AND ABANDON		
	HANGE PLANS		RILLING OPNS. P AND A
PULL OR ALTER CASING M	ULTIPLE COMPL	☐ CASING/CEMEN	NT JOB ⊠
OTHER:		OTHER:	
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion			
or recompletion.			
or recompletion.			
1 <sup>st</sup> intermediate Casing:			
0.01.0007 PWY 10.710177 77.77		0.010	
			resh water, 356 bbl mud flush, and 10 bbl fresh
water spacer. Lead cement: 660 sx 50/50 POZ Premium Plus cmt. + 8% Bentonite + 5% Salt + 5 lbm/sk Gilsonite + 0.25 lbm/sk Poly-E-Flake. Yield = 2.49, slurry wt. = 11.8. Tail cement: 200 sx Premium Plus "C" cmt. + 2% CaCl. Yield =			
1.35, slurry wt. = 14.8. Bump plug – held OK. Circulated 178 sks to reserve pit. Test BOP to 5000 psi for 30 minutes.			
WOC 20 hrs. total. Reduce hole size to 8 ½" and resume drilling.			
		•	
I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines $\square$ , a general permit $\square$ or an (attached) alternative OCD-approved plan $\square$ .			
SIGNATURE Ungela Lig	hther—	FITLE_Consultant	DATE9-26-2007
Type or print name Angela Lightner	E-mail address:	angela@rkford.com Telep	hone No. 432-682-0440
For State Use Only	SODDE ONI V	_	
APPROVED BY:	CORDS ONLY	TITI F	DATE 9CT 1 0 2007

Conditions of Approval (if any):