DISITIO I 1625 N. French Dr., Hobbs, NM 88240 District II
1301 W. Grand Avenue, Artesia, NM 88210
District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr , Santa Fe, NM 87505

State of New Mexico **Energy Minerals and Natural Resources**

June 1, 2004 For drilling and production facilities, submit to appropriate NMOCD District Office.

For downstream facilities, submit to Santa Fe

Form C-144

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

office

Pit or Below-Grade Tank Registration or Closure OCT 0 9 2007		
is pit or below-grade tank covered by a general plan ? res No.		
Operator: Southwestern Energy Production Co. Telephone: (281) 618-4887 e-mail address: martha_howard@swn.com		
2350 N Sam Houston Parkway Rost Suite 300 Houston Toyos 77037		
Facility or well name. Karlshad Corral 2 #7H API #: 30-015-34936 U/L or Qtr/Qtr K Sec 2 T 25S R 29E		
County Eddy Latitude	32°09'31.45" Longitude 103°57	"24.59" NAD: 1927 ☑ 1983 ☐ 1
Surface Owner: Federal State Private Indian		
<u>Pit</u>	Below-grade tank	
Type: Drilling 🗷 Production 🗌 Disposal 🗍	Volumebbl Type of fluid	
Workover Emergency	Construction material:	
Lined L Unlined	Double-walled, with leak detection? Yes If not, explain why not.	
Liner type: Synthetic Thickness 12 mil Clay	ynthetic ☑ Thickness 12 mil Clay □	
Pit Volume 13000 bbl		
Depth to ground water (vertical distance from bottom of pit to seasonal high water elevation of ground water.)	Less than 50 feet	(20 points)
	50 feet or more, but less than 100 feet	(10 points) 0
ingli water elevation of ground water.)	100 feet or more ✓	(0 points)
Wallhard and a day of the way 200 feet from a minute democratic	Yes	(20 points)
Wellhead protection area: (Less than 200 feet from a private domestic water source, or less than 1000 feet from all other water sources.)	No ✓	(0 points) 0
water source, or less than 1000 feet from an outer water sources.	1 d 200 S4	(22)
Distance to surface water: (horizontal distance to all wetlands, playas,	Less than 200 feet	(20 points) 0
irrigation canals, ditches, and perennial and ephemeral watercourses.)	200 feet or more, but less than 1000 feet	(10 points)
	1000 feet or more ✓	(0 points)
	Ranking Score (Total Points)	0
If this is a pit closure: (1) Attach a diagram of the facility showing the pit's relationship to other equipment and tanks. (2) Indicate disposal location: (check the onsite box if		
your are burying in place) onsite 🗷 offsite 🗌 If offsite, name of facility N/A (3). Attach a general description of remedial action taken including		
remediation start date and end date. (4) Groundwater encountered: No 🗹 Yes 🗌 If yes, show depth below ground surfaceft, and attach sample results.		
(5) Attach soil sample results and a diagram of sample locations and excavations.		
Additional Comments: Southwestern Energy: Production Co. Plans To Scep Bury Reserve		
Pit-lines: Contents PER NMOCA PLUK 50 AIT CLOSURE.		
DIG TREACH APPLOX 30'X 120'X 20'DC		mil Plastic -
PACE Pit lines & Contents in TREACH, CAP of 20 mil Plashe		
COURT WI APPROX. 3' NAMUE SOILS RESURD ATEA WT Specified Seed MIX tyre		
Contour Area by Gangles (outra)		
William The Colox Conflet		
I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that the above-described pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines [3], a general permit [3], or an (attached) alternative OCD-approved plan [3].		
Date: 8/15/2007		
Printed Name/Title Martha Howard / Regulatory Analyst Signature Signature		
Your certification and NMOCD approval of this application/closure does not relieve the operator of liability should the contents of the pit or tank contaminate ground water or otherwise endanger public health or the environment. Nor does it relieve the operator of its responsibility for compliance with any other federal, state, or local laws and/or regulations.		
Approval:		,
Printed Name/Title	Signature Mila Lanco	1 Date: 10/9/07
	_ signature / / / Signature	Date: 10/9/0-

NOTIFY OCD 24 HOURS PRIOR to beginning closure and 24 HOURS PRIOR to obtaining samples. Samples are to be obtained from pit area and analyses submitted to OCD prior to back-filling.

If burial trench is to be constructed in pit area, samples are to be obtained and analyses submitted to OCD PRIOR to lining trench.