

Submit 3 Copies To Appropriate District Office
 District I
 1625 N. French Dr., Hobbs, NM 87240
 District II
 1301 W Grand Ave., Artesia, NM 88210
 District III
 1000 Rio Brazos Rd., Aztec, NM 87410
 District IV
 1220 S St Francis Dr., Santa Fe, NM 87505

State of New Mexico
 Energy, Minerals and Natural Resources

Form C-103
 May 27, 2004

OIL CONSERVATION DIVISION
 1220 South St. Francis Dr.
 Santa Fe, NM 87505



SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-015-23587
1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/>		5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
2. Name of Operator POGO PRODUCING COMPANY		6. State Oil & Gas Lease No. L - 6442
3. Address of Operator P.O. Box 10340, Midland, TX 79702-7340		7. Lease Name or Unit Agreement Name: POKER LAKE "32 STATE"
4. Well Location Unit Letter <u>B</u> : <u>660</u> feet from the <u>NORTH</u> line and <u>1980</u> feet from the <u>EAST</u> line Section <u>32</u> Township <u>23 S</u> Range <u>31 E</u> NMPM <u>EDDY</u> County <u>NM</u>		8. Well Number 1
11. Elevation (Show whether DR, RKB, RT, GR, etc.)		9. OGRID Number 017891
Pit or Below-grade Tank Application <input type="checkbox"/> or Closure <input type="checkbox"/> Pit type _____ Depth to Groundwater _____ Distance from nearest fresh water well _____ Distance from nearest surface water _____ Pit Liner Thickness: _____ mil Below-Grade Tank: Volume _____ bbls; Construction Material _____		10. Pool name or Wildcat West Sanddunes Delaware

12. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

- PERFORM REMEDIAL WORK PLUG AND ABANDON
 TEMPORARILY ABANDON CHANGE PLANS
 PULL OR ALTER CASING MULTIPLE COMPLETION
 OTHER:

SUBSEQUENT REPORT OF:

- REMEDIAL WORK ALTERING CASING
 COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT
 CASING TEST AND CEMENT JOB
 OTHER:

Approved for plugging of well bore only.
 Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under forms. www.emnrd.state.us/ocd

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give dates of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach or recompletion.

10-22-07 Notify NMOCDC Phil Hawkins. 10-23-07 to 11-2-07 Drill out CIBP @7,650 to CICR @7,910'. RIH & tag 5" liner @12,271'. 11-6-07 Set CIBP @12,200'. Dumpbail 9 sx. cmt. 12,200'-12,163'. Set CIBP @10,800' w/9 sx. cmt. Dumpbail 10,800'-10,763' on 11-7-07. Set CIBP @7,800' w/9 sx. cmt. Dumpbailed 7,800'-7,763'. 11-7-07 Set CIBP @7,650'. 11-9-07 Calculate 10# MLF 7,650'-surf. Spot 30 sx. cmt. 7,650'-7,527'. Spot 100 sx. cmt. 4,445'-3,933'. 11-12-07 RIH to 4,445' w/tag. Mix & spot 100 sx. cmt. w/2% CaCl @4,445'. WOC & tag TOC @3,097'. Spot 135 sx. cmt. 4,097'-3,406'. 11-13-07 Tag TOC @3,406'. Perf. 7 5/8" csg. @3,406'. 11-14-07 Perf. 720 sx. cmt. w/2% CaCl under pkr. @2,885' thru perfs. @3,406' w/cmt. circulated to surf. out 7 5/8" X 10 3/4" csg. Displace TOC to 3,100'. 11-15-07 Tag TOC @3,088'. (continued on back)

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCDC guidelines , a general permit or an (attached) alternative OCD-approved plan

SIGNATURE Randall M. Minear TITLE P & A SUPERVISOR DATE 11-26-07
 E-mail address: _____

Type or print name RANDALL MINEAR

Telephone No. (432) 530-0907

For State Use Only

APPROVED BY Phil Hawkins TITLE Compliance Officer DATE 12/7/07
 Conditions of Approval, if any: _____

11-16-07 Spot 200 sx. cmt. w/2% CaCl - 3,088'-2,064'.

11-19-07 Tag TOC @2,051'. Spot 200 sx. w/2% CaCl - 2,051'-1,027'.
P.U.H. to spot 110 sx. cmt. w/2% CaCl. - 1,027'-464'. W.O.C.
& tag T.O.C. @480'. 15 sx. cmt. - 60' - surface.
Remove Wellhead and anchors. Install P & A Marker. Backfill collar.