

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S St Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
May 27, 2004



OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

JAN 25 2008

OCD ARTESIA

WELL API NO. 30-015-10199
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name ATOKA SAN ANDRES UNIT
8. Well Number 118
9. OGRID Number 6137
10. Pool name or Wildcat SAN ANDRES

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS)	
1. Type of Well: Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other <u>INJECTION WELL</u>	
2. Name of Operator DEVON ENERGY PRODUCTION COMPANY, LP	
3. Address of Operator 20 North Broadway, Ste 1500, Oklahoma City, OK 73102 405-552-4615	
4. Well Location Unit Letter <u>K</u> : <u>1650'</u> feet from the <u>SOUTH</u> line and <u>2310'</u> feet from the <u>WEST</u> line Section <u>10</u> Township <u>18S</u> Range <u>26E</u> NMPM County <u>EDDY</u>	
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3349' KB; 3338' GL	
Pit or Below-grade Tank Application <input type="checkbox"/> or Closure <input type="checkbox"/>	
Pit type _____ Depth to Groundwater _____ Distance from nearest fresh water well _____ Distance from nearest surface water _____	
Pit Liner Thickness: _____ mil Below-Grade Tank: Volume _____ bbls; Construction Material _____	

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

1. MIRU. POOH w/ 2-3/8" tubing & packer from 1,458'.
2. TIH w/CIBP & set @ 1,470'. Dump 35' cement on top. (San Andres perms from 1,513' to 1,748')
3. Spot 25 Sx plug (362') in 4-1/2" production casing @ 1,170'. WOC & TAG. (Calc. PBD @ 808') (7" casing shoe @ 1,114').
4. Circulate 25 Sx (362') surface plug.
5. Cut wellhead off, set dry hole marker, clean location.

**Notify OCD 24 hrs. prior
To any work done.**

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines ☐, a general permit ☐ or an (attached) alternative OCD-approved plan ☐.

SIGNATURE Ronnie Slack TITLE Engineering Technician DATE 1/23/08

Type or print name Ronnie Slack E-mail address: Ronnie.Slack@dmn.com Telephone No. 405-552-4615

For State Use Only

APPROVED BY: [Signature] TITLE Comptroller DATE 1/25/08

Conditions of Approval (if any):

DEVON ENERGY PRODUCTION COMPANY LP

Well Name: ATOKA SAN ANDRES UNIT #118		Field: ATOKA	
Location: 1650' FSL & 2310' FWL; SEC 10-18S-26E		County: EDDY	State: NM
Elevation: 3349' KB; 3338' GL		Spud Date: 12/26/63	Compl Date: 3/1/64
API#: 30-015-10199	Prepared by: Ronnie Slack	Date: 1/23/08	Rev:

PROPOSED PLUG & ABANDONMENT

Proposed PA

1. Circulate 25 Sx (362') plug to surface
2. Cut wellhead off, set dry hole marker, clean location

10 ppg mud

Proposed PA

1. Spot 25 Sx cement @ 1,170'.
2. WOC & TAG. (Calc. PBD @ 808')

9-5/8" Hole

7", 20#, J55, STC, @ 1,114'

Cmt'd w/1000 Sx to surface

10 ppg mud

Proposed PA

Circulate wellbore w/10 ppg mud

Proposed PA

1. Set CIBP @ 1,470' w/35' cement on top. PBD @ 1,435'

SAN ANDRES

1,513' - 1,748'

6-1/4" Hole

4-1/2", 9.5#, J55, STC, @ 1,844'

Cmt'd w/300 Sx to surface

1,804' PBTD

1,850' TD

DEVON ENERGY PRODUCTION COMPANY LP

Well Name: ATOKA SAN ANDRES UNIT #118		Field: ATOKA	
Location: 1650' FSL & 2310' FWL; SEC 10-18S-26E		County: EDDY	State: NM
Elevation: 3349' KB; 3338' GL		Spud Date: 12/26/63	Compl Date: 3/1/64
API#: 30-015-10199	Prepared by: Ronnie Slack	Date: 1/23/08	Rev:

CURRENT WELLBORE SCHEMAT

9-5/8" Hole
7", 20#, J55, STC, @ 1,114'
 Cmt'd w/1000 Sx to surface

2-3/8", 4.7#, J55, IPC Tubing

Baker AD-1 Packer @ 1,458' (3/16/02)

SAN ANDRES
 1,513' - 1,748'

6-1/4" Hole
4-1/2", 9.5#, J55, STC, @ 1,844'
 Cmt'd w/300 Sx to surface

1,804' PBD

1,850' TD

