

Submit 3 Copies To Appropriate District  
Office  
District I  
1625 N. French Dr., Hobbs, NM 88240  
District II  
1301 W Grand Ave., Artesia, NM 88210  
District III  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV  
1220 S. St. Francis Dr., Santa Fe, NM  
87505

State of New Mexico  
Energy, Minerals and Natural Resources

Form C-103  
May 27, 2004



SOIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

JAN 31 2008

OCD-ARTESIA

<b>SUNDRY NOTICES AND REPORTS ON WELLS</b> (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. <b>30-015-00226</b>
1. Type of Well: Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other <u>INJECTION WELL</u>		5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
2. Name of Operator <b>DEVON ENERGY PRODUCTION COMPANY, LP</b>		6. State Oil & Gas Lease No.
3. Address of Operator <b>20 North Broadway, Ste 1500, Oklahoma City, OK 73102 405-552-4615</b>		7. Lease Name or Unit Agreement Name <b>ATOKA SAN ANDRES UNIT</b>
4. Well Location Unit Letter <u>D</u> : <u>330'</u> feet from the <u>NORTH</u> line and <u>990'</u> feet from the <u>WEST</u> line Section <u>23</u> Township <u>18S</u> Range <u>26E</u> NMPM County <u>EDDY</u>		8. Well Number <b>156</b>
11. Elevation (Show whether DR, RKB, RT, GR, etc.) <b>3326' GL</b>		9. OGRID Number <b>6137</b>
Pit or Below-grade Tank Application <input type="checkbox"/> or Closure <input type="checkbox"/>		
Pit type _____ Depth to Groundwater _____ Distance from nearest fresh water well _____ Distance from nearest surface water _____		
Pit Liner Thickness: _____ mil Below-Grade Tank: Volume _____ bbls; Construction Material _____		

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ P AND A ☐  
CASING/CEMENT JOB ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

1. MIRU. TIH to CIBP @ 1,277'. Circulate wellbore w/10 ppg mud.
2. Spot 25 Sx plug (240') on existing CIBP @ 1,277'. WOC & TAG. (Calc. PBD @ 1,037') (8-5/8" casing shoe @ 1,240').
3. Perforate 5-1/2" casing @ 100'. Pump 30 Sx cement for surface plug on 5-1/2" casing X 5-1/2" casing annulus.
4. Cut wellhead off, set dry hole marker, clean location.

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines ☐, a general permit ☐ or an (attached) alternative OCD-approved plan ☐.

SIGNATURE Ronnie Slack TITLE Engineering Technician DATE 1/29/08

Type or print name Ronnie Slack E-mail address: Ronnie.Slack@dvN.com Telephone No. 405-552-4615  
**For State Use Only**

APPROVED BY: Gerry Guye TITLE Compliance Officer DATE FEB 12 2008  
Conditions of Approval (if any):

**DEVON ENERGY PRODUCTION COMPANY LP**

Well Name: ATOKA SAN ANDRES UNIT #156		Field: ATOKA	
Location: 330' FNL & 990' FWL; SEC 23-T18S-R26E		County: EDDY	State: NM
Elevation: 3326' GL		Spud Date: 6/20/58	Compl Date: 10/5/58
API#: 30-015-00226	Prepared by: Ronnie Slack	Date: 1/29/08	Rev:

**PROPOSED PLUG & ABANDONMENT**

**Proposed PA**

1. Perforate 5-1/2" casing @ 100'.
2. Pump 30 Sx cement for surface plug inside & out on 5-1/2" casing.
3. Cut wellhead off, set dry hole marker, clean location.

10# Mud

TOC @ 960' (temp survey)

**Proposed PA:**

1. Circulate wellbore w/10 ppg mud.

**Proposed PA:**

1. Spot 25 Sx (240') plug on CIBP @ 1,277'
2. WOC & Tag. (Calc. PBD @ 1,037')

*San Andres 1540'*

11" Hole

8-5/8", 24#, J55, @ 1,240'

Cmt'd w/450 Sx, topped out w/35 sx to surface

**SAN ANDRES**

1,382' - 1,396'

1,544' - 1,566'

1,607' - 1,622

1,672' - 1,683'

1,745' - 1,775' (perfs sqzd w/150 sx)

7-7/8" Hole

5-1/2", 14#, J55, @ 1,795'

Cmt'd w/150 Sx. (TOC @ 960' Temp survey)

CIBP @ 1,277' (3/18/82)

1,695' PBD  
Cement retainer @ 1,710'

1,795' TD

**DEVON ENERGY PRODUCTION COMPANY LP**

Well Name: ATOKA SAN ANDRES UNIT #156		Field: ATOKA	
Location: 330' FNL & 990' FWL; SEC 23-T18S-R26E		County: EDDY	State: NM
Elevation: 3326' GL		Spud Date: 6/20/58	Compl Date: 10/5/58
API#: 30-015-00226	Prepared by: Ronnie Slack	Date: 1/29/08	Rev:

**CURRENT WELLBORE SCHEMAT**

TOC @ 960' (temp survey)

11" Hole  
8-5/8", 24#, J55, @ 1,240' ✓  
 Cmt'd w/450 Sx, topped out w/35 sx to surface

SAN ANDRES  
 1,382' - 1,396'

1,544' - 1,566'

1,607' - 1,622

1,672' - 1,683'

1,745' - 1,775' (perfs sqzd w/150 sx)

7-7/8" Hole  
5-1/2", 14#, J55, @ 1,795' ✓  
 Cmt'd w/150 Sx. (TOC @ 960' Temp survey)

CIBP @ 1,277' (3/18/82)

1,695' PBDT ✓  
 Cement retainer @ 1,710'

1,795' TD

