

Submit 3 Copies To Appropriate District
Office
District I
1625 N French Dr., Hobbs, NM 88240
District II
1301 W Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
May 27, 2004

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

FEB 28 2008

OCD-ARTESIA



SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☐ Gas Well ☐ Other INJECTION WELL

2. Name of Operator
DEVON ENERGY PRODUCTION COMPANY, LP

3. Address of Operator
20 North Broadway, Ste 1500, Oklahoma City, OK 73102 405-552-4615

4. Well Location
Unit Letter D : 330' feet from the NORTH line and 990' feet from the WEST line
Section 23 Township 18S Range 26E NMPM County EDDY

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3326' GL

Pit or Below-grade Tank Application ☐ or Closure ☐

Pit type _____ Depth to Groundwater _____ Distance from nearest fresh water well _____ Distance from nearest surface water _____

Pit Liner Thickness: _____ mil Below-Grade Tank: Volume _____ bbls; Construction Material _____

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☒
CASING/CEMENT JOB ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

1. 2/20/08—MIRU for P&A. Tag CIBP @ 1,277'. Circulated wellbore w/10 ppg mud.
2. Spot 25 Sx cement on CIBP @ 1,277'. Tagged TOC @ 1,021'. (8-5/8" casing shoe @ 1,240').
3. Perforated 5-1/2" casing @ 100'. Pump 30 Sx cement for surface plug on 5-1/2" casing X 5-1/2" casing annulus.
4. 2/21/08—Wellbore plugged out.
5. 2/25/08—Wellhead cut off & dry hole marker set. Plugged & Abandoned.

Approved for plugging of well bore only.
Liability under bond is retained pending receipt
of C-103 (Subsequent Report of Well Plugging)
which may be found at OCD Web Page under
Forms, www.cmnrd.state.nm.us/oed.

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines ☐, a general permit ☐ or an (attached) alternative OCD-approved plan ☐.

SIGNATURE Ronnie Slack TITLE Engineering Technician DATE 2/25/08

Type or print name Ronnie Slack E-mail address: Ronnie.Slack@dv.n.com Telephone No. 405-552-4615
For State Use Only

APPROVED BY: [Signature] TITLE Compliance Officer DATE 2/28/08
Conditions of Approval (if any):

DEVON ENERGY PRODUCTION COMPANY LP

Well Name: ATOKA SAN ANDRES UNIT #156		Field: ATOKA	
Location: 330' FNL & 990' FWL; SEC 23-T18S-R26E		County: EDDY	State: NM
Elevation: 3326' GL		Spud Date: 6/20/58	Compl Date: 10/5/58
API#: 30-015-00226	Prepared by: Ronnie Slack	Date: 2/25/08	Rev:

PLUGGED & ABANDONED
2/25/08

1. Perf 5-1/2" casing @ 100'
2. Circulated 30 sx cement to surface
3. Wellbore plugged out. (2/21/08)
4. Wellhead cut off. Dry hole marker set. (2/25/08)

10# Mud

Circulated wellbore w/10 ppg mud. (2/21/08)

TOC @ 960' (temp survey)

Tagged TOC @ 1,021'. (2/21/08)

11" Hole

8-5/8", 24#, J55, @ 1,240'

Cmt'd w/450 Sx, topped out w/35 sx to surface

Spot 25 Sx cement on CIBP @ 1,277' (2/21/08)

MIRU for PA. Tag CIBP @ 1277' (2/20/08)

CIBP @ 1,277' (3/18/82)

SAN ANDRES

1,382' - 1,396'

1,544' - 1,566'

1,607' - 1,622

1,672' - 1,683'

1,745' - 1,775' (perfs sqzd w/150 sx)

7-7/8" Hole

5-1/2", 14#, J55, @ 1,795'

Cmt'd w/150 Sx (TOC @ 960' Temp survey)

1,695' PBD
Cement retainer @ 1,710'

1,795' TD