1625 N Fresh Pr., Hobb, N. 88320 DIL CONSERVATION DIVISION 1220 South St. Francis Dr. Santa Fe, NM 87410 S	Submit 3 Copies To Appropriate District Office <u>District I</u>	State of New Energy, Minerals and		Form C-103 May 27, 2004	
1220 South St. Francis Dr. STATE FEE		OIL CONSERVATION DIVISION			
Santa Fr., NM 8 7505	District III				
SUNDRY NOTICES AND REPORTS ON WELLS ON ONT SET HIS PORM OF ROPOSALS TO DAIL OR TO DEEP ROPOSALS OR SUCH PROPOSALS OR S	District IV 1220 S. St. Francis Dr., Santa Fe, NM			6. State Oil & Gas Lease No.	
PROPOSALS) 19 19 19 19 19 19 19 1	SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A			Pinnacle State	
2. Name of Operator RKI Exploration and Production, LLC. OCD_ARTESIA 9. OCRID Number 20.289 3. Address of Operator 3817 NW Expressway, Suite 950, Oklahoma City, OK. 73112 10. Pool name or Wildcat Herradurra Bend (Delaware) 4. Well Location Unit Letter E 2470 feet from the Morth line and 820 feet from the West line Section 36 Township 228 Range 28E NMPM Eddy County County Eddy County Eddy County Eddy County Eddy Eddy	PROPOSALS)			1	
3. Address of Operator 3817 NW Expressway, Suite 950, Oklahoma City, OK. 73112 4. Well Location Unit Letter E	2. Name of Operator				
4. Well Location Unit Letter E : 2470 feet from the North line and 820 feet from the West line Section 36 Township 228 Range 28E NMPM Eddy County 11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3,128 GR Ple Or Below-grade Tank Application or Closure Distance from nearest from Application or Closure Ple Or Below-grade Tank Application or Closure Distance from nearest from Nature Distance from nearest from nearest surface water Ple Or Below-grade Tank Application or Closure Distance from nearest from nearest surface water Distance from nearest surface water Deepth to Groundwater Deepth to Groundwater Distance from nearest from nearest surface water Deepth to Groundwater Deepth to Groundwater Distance from nearest surface water Deepth to Groundwater Deepth to Groundwater Deepth to Groundwater Deepth Capital Work ALTERING CASING COMMENCE DRILLING OPINS PAND A CASING/CEMENT JOB DITHER: CBL and Completion COMMENCE DRILLING OPINS DITHER: CBL and Completion diagram of proposed completion or recompletion. Commenced completion operations on 3-14-08. Installed and tested 3,000# BOPE. Drilled out DV tool @ 3,405*. Cleaned out well to 6,605* (float collar depth). Pressure tested casing to 2,000 psi. for 25 minutes. Pressure tested good. Ran cement bond/gamma ray/casing collar log. Perforated the Bone Springs from 6,467* -6,489* (3 SPF, 66 total holes). Acidized with 2,000 gals. of 7-1/2% HCl using 99 ball sealers. Fracture simulated via 5-1/2* casing with 24,500 gals Medalion 3000, 12,546 gals 30# linear gel, 42,000 lbs. 16/30 white sand, and 20,000 bs. 16/30 resin-coated proppant. Cleaned out to 6,605*. Installed sector rol pumping equipment. Placed well on production. United the proposed of the pr		ition and Production, LLC.			
Unit Letter E : 2470 feet from the North line and 820 feet from the West line Section 36 Township 22S Range 28E NMPM Eddy County II. Elevation (Show whether DR, RKB, RT, GR, etc.)				Herradurra Bend (Delaware)	
Section 36 Township 22S Range 28E NMPM Eddy County 11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3,128 GR 12. Check Application or Cleaver					
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3,128' GR					
Pit type	11. Elevation (Show whether DR, RKB, RT, GR, etc.)				
Pit Liner Thickness: mil Below-Grade Tank: Volume bbls; Construction Material					
NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK	,				
NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING REMEDIAL WORK ALTERING CASING COMMENCE DRILLING OPNS P AND A PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMENT JOB P AND A OTHER: 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. Commenced completion operations on 3-14-08. Installed and tested 3,000# BOPE. Drilled out DV tool @ 3,405". Cleaned out well to 6,605" (float collar depth). Pressure tested casing to 2,000 psi. for 25 minutes. Pressure tested good. Ran cement bond/gamma ray/casing collar log. Perforated the Bone Springs from 6,467" - 6,489" (3 SPF, 66 total holes). Acidized with 2,000 gals. of 7-1/2% HCl using 99 ball sealers. Fracture stimulated via 5-1/2" casing with 24,500 gals Medalion 3000, 12,546 gals 30# linear gel, 42,000 lbs. 16/30 white sand, and 20,000 lbs. 16/30 resin-coated proppant. Cleaned out to 6,605". Installed sucker rod pumping equipment. Placed well on production. Work completed on 3-26-08. I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be conducted or closed according to NMOCD guidelines a general permit or an (attached) alternative OCD-approved plan SIGNATURE					
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING ALTERING CASING PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMENT JOB OTHER: CBL and Completion SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. Commenced completion operations on 3-14-08. Installed and tested 3,000# BOPE. Drilled out DV tool @ 3,405°. Cleaned out well to 6,605° (float collar depth). Pressure tested casing to 2,000 psi. for 25 minutes. Pressure tested good. Ran cement bond/gamma ray/casing collar log. Perforated the Bone Springs from 6,467° -6,489° (3 SPF, 66 total holes). Acidized with 2,000 gals of 7-1/27% HCl using 99 ball sealers. Fracture stimulated via 5-1/2" casing with 24,500 gals Medalion 3000, 12,546 gals 30# linear gel, 42,000 lbs. 16/30 white sand, and 20,000 lbs. 16/30 resin-coated proppant. Cleaned out to 6,605°. Installed sucker rod pumping equipment. Placed well on production. Work completed on 3-26-08. Thereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be confructed or doyal according to NMOCD guidelines a general permit or an (attached) alternative OCD-approved plan SIGNATURE TITLE PRODUCTION SUPERINTENDENT DATE Type or print name Gene Simer E-mail address: gsimen@rkixp.com Telephone No. 505-885-1313 For State Use Only APPROVED BY: TITLE DATE					
TEMPORARILY ABANDON					
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. Commenced completion operations on 3-14-08. Installed and tested 3,000# BOPE. Drilled out DV tool @ 3,405'. Cleaned out well to 6,605' (float collar depth). Pressure tested casing to 2,000 psi. for 25 minutes. Pressure tested good. Ran cement bond/gamma ray/casing collar log. Perforated the Bone Springs from 6,467' - 6,489' (3 SPF, 66 total holes). Acidized with 2,000 gals. of 7-1/2% HCl using 99 ball sealers. Fracture stimulated via 5-1/2" casing with 24,500 gals Medalion 3000, 12,546 gals 30# linear gel, 42,000 lbs. 16/30 white sand, and 20,000 lbs. 16/30 resin-coated proppant. Cleaned out to 6,605'. Installed sucker rod pumping equipment. Placed well on production. Work completed on 3-26-08. Thereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or belowgrade tank has been/will be confructed or closed according to NMOCD guidelines □, a general permit □ or an (attached) alternative OCD-approved plan □. SIGNATURE TITLE PRODUCTION SUPERINTENDENT DATE Type or print name Gene Simer E-mail address: gsimer@rkixp.com Telephone No. 505-885-1313 For State Use Only APPROVED BY: TITLE DATE					
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. Commenced completion operations on 3-14-08. Installed and tested 3,000# BOPE. Drilled out DV tool @ 3,405′. Cleaned out well to 6,605′ (float collar depth). Pressure tested casing to 2,000 psi. for 25 minutes. Pressure tested good. Ran cement bond/gamma ray/casing collar log. Perforated the Bone Springs from 6,467′ - 6,489′ (3 SPF, 66 total holes). Acidized with 2,000 gals. of 7-1/2% HCl using 99 ball sealers. Fracture stimulated via 5-1/2″ casing with 24,500 gals Medalion 3000, 12,546 gals 30# linear gel, 42,000 lbs. 16/30 white sand, and 20,000 lbs. 16/30 resin-coated proppant. Cleaned out to 6,605′. Installed sucker rod pumping equipment. Placed well on production. Work completed on 3-26-08. I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be conducted or closed according to NMOCD guidelines □, a general permit □ or an (attached) alternative OCD-approved plan □. SIGNATURE	PULL OR ALTER CASING	MULTIPLE COMPL	CASING/CEMEN	T JOB	
of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. Commenced completion operations on 3-14-08. Installed and tested 3,000# BOPE. Drilled out DV tool @ 3,405°. Cleaned out well to 6,605° (float collar depth). Pressure tested casing to 2,000 psi. for 25 minutes. Pressure tested good. Ran cement bond/gamma ray/casing collar log. Perforated the Bone Springs from 6,467° - 6,489° (3 SPF, 66 total holes). Acidized with 2,000 gals. of 7-1/2% HCl using 99 ball sealers. Fracture stimulated via 5-1/2" casing with 24,500 gals Medalion 3000, 12,546 gals 30# linear gel, 42,000 lbs. 16/30 white sand, and 20,000 lbs. 16/30 resin-coated proppant. Cleaned out to 6,605°. Installed sucker rod pumping equipment. Placed well on production. Work completed on 3-26-08. I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be capacucted or closed according to NMOCD guidelines \(\), a general permit \(\) or an (attached) alternative OCD-approved plan \(\). SIGNATURE TITLE PRODUCTION SUPERINTENDENT DATE Type or print name Gene Simer E-mail address: gsimen@rkixp.com Telephone No. 505-885-1313 For State Use Only APPROVED BY: TITLE DATE					
well to 6,605' (float collar depth). Pressure tested casing to 2,000 psi. for 25 minutes. Pressure tested good. Ran cement bond/gamma ray/casing collar log. Perforated the Bone Springs from 6,467' - 6,489' (3 SPF, 66 total holes). Acidized with 2,000 gals. of 7-1/2% HCl using 99 ball sealers. Fracture stimulated via 5-1/2" casing with 24,500 gals Medalion 3000, 12,546 gals 30# linear gel, 42,000 lbs. 16/30 white sand, and 20,000 lbs. 16/30 resin-coated proppant. Cleaned out to 6,605'. Installed sucker rod pumping equipment. Placed well on production. Work completed on 3-26-08. Thereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be condructed or closed according to NMOCD guidelines [], a general permit [] or an (attached) alternative OCD-approved plan []. SIGNATURE	of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion				
Acidized with 2,000 gals. of 7-1/2% HCl using 99 ball sealers. Fracture stimulated via 5-1/2" casing with 24,500 gals Medalion 3000, 12,546 gals 30# linear gel, 42,000 lbs. 16/30 white sand, and 20,000 lbs. 16/30 resin-coated proppant. Cleaned out to 6,605. Installed sucker rod pumping equipment. Placed well on production. Work completed on 3-26-08. I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be confurcted or closed according to NMOCD guidelines, a general permit or an (attached) alternative OCD-approved plan SIGNATURE					
grade tank has been/will be constructed or closed according to NMOCD guidelines , a general permit or an (attached) alternative OCD-approved plan SIGNATURE TITLE PRODUCTION SUPERINTENDENT DATE Type or print name Gene Simer E-mail address: gsimer@rkixp.com Telephone No. 505-885-1313 For State Use Only APPROVED BY: TITLE DATE	Acidized with 2,000 gals. of 7-1/2% HCl using 99 ball sealers. Fracture stimulated via 5-1/2" casing with 24,500 gals Medalion 3000, 12,546 gals 30# linear gel, 42,000 lbs. 16/30 white sand, and 20,000 lbs. 16/30 resin-coated proppant. Cleaned out to 6,605'. Installed sucker rod pumping equipment. Placed well on production.				
grade tank has been/will be constructed or closed according to NMOCD guidelines , a general permit or an (attached) alternative OCD-approved plan SIGNATURE TITLE PRODUCTION SUPERINTENDENT DATE Type or print name Gene Simer E-mail address: gsimer@rkixp.com Telephone No. 505-885-1313 For State Use Only APPROVED BY: TITLE DATE	,				
grade tank has been/will be constructed or closed according to NMOCD guidelines , a general permit or an (attached) alternative OCD-approved plan SIGNATURE TITLE PRODUCTION SUPERINTENDENT DATE Type or print name Gene Simer E-mail address: gsimer@rkixp.com Telephone No. 505-885-1313 For State Use Only APPROVED BY: TITLE DATE					
grade tank has been/will be constructed or closed according to NMOCD guidelines , a general permit or an (attached) alternative OCD-approved plan SIGNATURE TITLE PRODUCTION SUPERINTENDENT DATE Type or print name Gene Simer E-mail address: gsimer@rkixp.com Telephone No. 505-885-1313 For State Use Only APPROVED BY: TITLE DATE					
grade tank has been/will be constructed or closed according to NMOCD guidelines , a general permit or an (attached) alternative OCD-approved plan SIGNATURE TITLE PRODUCTION SUPERINTENDENT DATE Type or print name Gene Simer E-mail address: gsimer@rkixp.com Telephone No. 505-885-1313 For State Use Only APPROVED BY: TITLE DATE	•				
Type or print name Gene Simer E-mail address: gsimer@rkixp.com Telephone No. 505-885-1313 For State Use Only APPROVED BY: DATE	I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines \square , a general permit \square or an (attached) alternative OCD-approved plan \square .				
APPROVED BY: DATE	SIGNATURE Stane	inico titi	E PRODUCTION SU	PERINTENDENT DATE	
		mer E-mail addre	ss: <u>gsimer@rkixp.co</u>	m Telephone No. <u>505-885-1313</u>	
		TITI	.E	DATE	