

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

OCD-ARTESIA

MAY 19 2008

FORM APPROVED
Budget Bureau No 1004-0135
Expires March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

OCD-ARTESIA

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT-" for such proposals

SUBMIT IN TRIPLICATE



1 Type of Well
Oil Well ☐ Gas Well ☐ ☒ Other

2 Name of Operator

ExxonMobil Corporation

3 Address and Telephone No

Po Box 4358 Houston, Tx 77210-4358

4 Location of Well (Footage, Sec, T, R, M, or Survey Description)

1557' FNL & 660' FWL

Sec 4, T 21S, R 27E

8 Well Name and No

Yates C Federal # 22

9 API Well No

30-015-24501

10 Field and Pool, or Exploratory Area

Avalon, Delaware

11 County or Parish, State

Eddy, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

Notice of Intent

☒ Subsequent Report

Final Abandonment Notice

TYPE OF ACTION

☒ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form)


13 Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work)*

4-11-08 Tagged cement on top of existing CIBP at 3132'. Mix and pump 35 sks of salt water clay with 70 bbl of 10# brine water from 3107'. Mix and pump 100 sks of class C neat cement from 3107'. WOC plug. Tag plug at 2223'. Perforated csg at 720'. Set pkr at 25'. Mix and pump 205 sks Class C neat cement under pkr down csg out through perforations at 720' back up annulus to surface

4-14-08 Mechanically cut 5 1/2" csg from inside at 3' below surface. Rih and tag plug at 30'. Circulate cement inside of 5 1/2" csg from 30' to surface.

Accepted for record
NMOCD

Approved for plugging of well bore only.
Liability under bond is retained pending receipt
of C-103 (Subsequent Report of Well Plugging)
which may be found at OCD Web Page under
Forms. www.blm.state.nm.us/oed.



14 I hereby certify that the foregoing is true and correct

Signed *[Signature]*

Title Supervisor

Date 04/23/08

(This space for Federal or State office use)

Approved by
Conditions of approval, if any

Title

Date

Title 18 U S C Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side