Form 3160-5 (August 2007)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

OCD-ARTESIA

FORM APPROVED OMB No 1004-0137 Expires July 31, 2010

				5 Lease Serial No		
SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.				See attached 6 If Indian, Allottee o	or Tribe Name	
SUBMIT IN TRIPLICATE - Other instructions on page 2.			7 If Unit of CA/Agree	ement, Name and/or No.		
1. Type of Well ☑ Oil Well ☐ Gas V	Vell Other	UN 2 4 2008		8 Well Name and No See attached		
2 Name of Operator Marbob Energy Corporation		ACDARTESIA	1	9 API Well No. See attached 3	015-36164	
3a Address P O Box 227, Artesia, NM 88211-0227		3b Phone No. (include area co 575-748-3303		10. Field and Pool or E See attached	Exploratory Area	
				11 Country or Parish, See attached	State	
12 CHEC	K THE APPROPRIATE BO	OX(ES) TO INDICATE NATUR	E OF NOTIC	E, REPORT OR OTHI	ER DATA	
TYPE OF SUBMISSION		TY	ON			
Notice of Intent	Acidize Alter Casing Casing Repair	Deepen Fracture Treat New Construction	Recla	nction (Start/Resume) mation	Water Shut-Off Well Integrity ✓ Other Replacement Page	
Subsequent Report Final Abandonment Notice	Change Plans Convert to Injection	Plug and Abandon Plug Back		orarily Abandon Disposal		
13 Describe Proposed or Completed Opthe proposal is to deepen directions. Attach the Bond under which the wideling completion of the involvesting has been completed. Final addetermined that the site is ready for Marbob Energy respectfully requests of cement does not circulate on surface 1" pipe will be fundable.	ally or recomplete horizontal york will be performed or produced operations. If the operation handonment Notices must be final inspection of the following approval for the following the supproval for the following the followin	ly, give subsurface locations and ovide the Bond No. on file with B on results in a multiple completion be filed only after all requirement statement to be added to the	measured and BLM/BIA. Report or recomplets, including to be cement pro-	d true vertical depths of equired subsequent repetion in a new interval, reclamation, have been ogram on the attacha	f all pertinent markers and zones orts must be filed within 30 days a Form 3160-4 must be filed once completed and the operator has	

14 I hereby certify that the foregoing is true and correct Name (Printed/Typed)		
Nancy T Agnew Tutl	e Land Department	
Signature Dancy T. Ocnew Dat	e 06/16/2008	APPROVED
THIS SPACE FOR FEDERA	L OR STATE OFFIC	USE
Approved by	Title	JUN 2 1 ZODS
Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.	Office :	WESLEY W. INGRAM PETROLEUM ENGINEER

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction

Attachment for Marbob Sundry dated 6/16/08

Well Name and #	API#	Lease #	Location	Field and Pool
Loco Federal #6	30-015-36164	NMNM 106231	1800' FNL & 2310' FEL, Sec 21, T17S - R30E, Eddy County, NM	Loco Hills; Glorieta-Yeso
Birdie Federal #10	30.015 36371	NMNM 074936	1650' FNL & 530' FEL, Section 17, T17S - R30E, Eddy County, NM	Loco Hills; Glorieta-Yeso
Thunder Road Federal #8	30-015-36280	NMLC0029342E	1675' FNL & 2310' FEL, Sec 20, T17S - R30E, Eddy County, NM	Loco Hills; Glorieta-Yeso
Randy Federal #6	30-015-36361	NMLC 29020E	1750' FNL & 2310' FEL, Sec 22, T17S -R30E, Eddy County, NM	Loco Hills; Glorieta-Yeso
Randy Federal #7	30-015-36264	NMLC 29020E	1800' FNL & 990' FEL, Sec 22, T17S - R30, Eddy County, NM	Loco Hills; Glorieta-Yeso

1

1 Ju

Loco Federal #6 API 30-015-36164 June 21, 2008 Conditions of Approval

For the surface casing: If cement does not circulate to the surface, the appropriate BLM office shall be notified and a tag with 1" will be performed at four positions 90 degrees apart to verify cement depth. BLM Petroleum Engineer Technician to witness tags. If depth is greater than 100' or water is standing in the annulus, remedial cementing will be done. If no water and TOC tag is less than 100', when 100% excess cement of the annulus volume was run on the primary job, ready-mix can be used to bring cement to surface.

WWI 062108