

Submit 3 Copies To Appropriate District Office
 District I
 1625 N French Dr., Hobbs, NM 88240
 District II
 1301 W Grand Ave., Artesia, NM 88210
 District III
 1000 Rio Brazos Rd., Aztec, NM 87410
 District IV
 1220 S St Francis Dr., Santa Fe, NM 87505

State of New Mexico
 Energy, Minerals and Natural Resources

Form C-103
 May 27, 2004

OIL CONSERVATION DIVISION
 1220 South St. Francis Dr.
 Santa Fe, NM 87505



WELL API NO.	30-005-60890
5. Indicate Type of Lease	STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.	
7. Lease Name or Unit Agreement Name	Bell Estate
8. Well Number	1
9. OGRID Number	255333
10. Pool name or Wildcat	Undesignated Pecos Slope Abo

SUNDRY NOTICES AND REPORTS ON WELLS
 (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well Gas Well Other **JUL 10 2008**

2. Name of Operator
 Lime Rock Resources A, L.P. **OCD-ARTESIA**

3. Address of Operator
 Heritage Plaza, 1111 Bagby St. Suite 4600, Houston, TX 77002

4. Well Location
 Unit Letter J : 1,980 feet from the South line and 1,980 feet from the East line
 Section 17 Township 5S Range 24E NMPM Chaves County

11. Elevation (Show whether DR, RKB, RT, GR, etc)
 4,096' GR

Pit or Below-grade Tank Application or Closure

Pit type _____ Depth to Groundwater _____ Distance from nearest fresh water well _____ Distance from nearest surface water _____

Pit Liner Thickness: _____ mil Below-Grade Tank: Volume _____ bbls; Construction Material _____

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

- PERFORM REMEDIAL WORK PLUG AND ABANDON
 TEMPORARILY ABANDON CHANGE PLANS
 PULL OR ALTER CASING MULTIPLE COMPL

OTHER:

SUBSEQUENT REPORT OF:

- REMEDIAL WORK ALTERING CASING
 COMMENCE DRILLING OPNS. P AND A
 CASING/CEMENT JOB

OTHER:

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

6/25/2008

SAFETY MEETING - MOVE IN EQUIPMENT - NU BOP - POOH WITH TUBING - 111 JOINTS OF 2-3/8" TUBING - SDFD

6/26/2008

SAFETY MEETING - RIH NO TAG - POOH - RIH WITH CIBP SET @ 3535' - POOH - RIH AND CIRCULATE PLUGGING MUD - SPOT 25 SACKS ON TO OF CIBP - POOH - RIH AND PERF @ 1754' - RIH WITH PACKER - PUMP 100 SACKS - LOST CIRCULATION - POOH - SDFD.

6/27/2008

SAFETY MEETING - RIH AND TAG @1253' - RIH AND PERF @925' - RIH WITH TUBING - SPOT 25 SACKS - POOH - WOC - RIH AND TAG @ 745' - TURNED WELL OVER TO LANDOWNER TO CONVERT WELL TO WATER WELL - SDFD.

WELL P&A'D.

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines , a general permit or an (attached) alternative OCD-approved plan .

SIGNATURE C. J. Miller TITLE: Vice President - Operations DATE: 10 July 2008

Type or print name: C. Tim Miller E-mail address: tmiller@limerockresources.com Telephone No.: (713) 292-9514


For State Use Only

APPROVED BY: **Accepted for record** TITLE _____
 Conditions of Approval (if any): **NMOCD**

Approved for plugging of well bore only.
 Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms, www.cmnr.state.nm.us/oed.

DATE 7/15/08

FINAL ABANDONMENT WELLBORE TURNED OVER TO LANDOWNER FOR WATER WELL



13-3/8", 48#, K-55, ST&C Casing @ 875'
Perforated at 925' and spotted 25 sx plug from 925' to 7455' (tagged top of plug)

8-5/8", 24#, K-55, ST&C Casing @ 1,704'
Perforated at 1,754' and spotted 100 sx plug from 1,754' to 1,253' (tagged top of plug)

Cast Iron Bridge Plug @ 3,535' w/ 25 sxs cement on top of plug

Abo Perfs 3,585-97', 3,721-25', & 3,733-35' (12 - 0.42" DIA holes)
Note: Squeezed perfs 3,585-97' and re-perforated.

CIBP @ 3,850' w/ 30' cement on top of plug
Abo Perfs ABANDONED: 3,885-90'; 3,894'; 3,898';
 3,902-07' & 3,911-13' (16 - 0.42" DIA holes)

4-1/2", 10.5#, J-55, ST&C, Casing @ 4,015'

TD @ 4,300'

PBTD @ 3,820'

**Lime Rock Resources
 Bell Estate 1
 Sec 17J-5S-24E
 Chaves County, NM**