

Submit 3 Copies To Appropriate District  
Office  
District I  
1625 N French Dr , Hobbs, NM 88240  
District II  
1301 W Grand Ave , Artesia, NM 88210  
District III  
1000 Rio Brazos Rd , Aztec, NM 87410  
District IV  
1220 S. St Francis Dr , Santa Fe, NM  
87505

State of New Mexico  
Energy, Minerals and Natural Resources

Form C-103  
May 27, 2004

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

WELL API NO. 30-015-36383
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name RDX "16"
8. Well Number 2
9. OGRID Number 246289
10. Pool name or Wildcat Brushy Draw - Delaware East

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH  
PROPOSALS )  
1. Type of Well: Oil Well ☒ Gas Well ☐ Other

2. Name of Operator  
RKI Exploration and Production, LLC.

3. Address of Operator  
3817 NW Expressway, Suite 950, Oklahoma City, OK. 73112

4. Well Location  
Unit Letter \_\_\_\_\_ : 2190' feet from the South line and 1875' feet from the West line  
Section 16 Township 26S Range 30E NMPM Eddy County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)  
3,047' GR

Pit or Below-grade Tank Application ☐ or Closure ☐  
Pit type \_\_\_\_\_ Depth to Groundwater \_\_\_\_\_ Distance from nearest fresh water well \_\_\_\_\_ Distance from nearest surface water \_\_\_\_\_  
Pit Liner Thickness: \_\_\_\_\_ mil Below-Grade Tank: Volume \_\_\_\_\_ bbls; Construction Material \_\_\_\_\_

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ P AND A ☐  
CASING/CEMENT JOB ☐

OTHER: ☐

OTHER: Spud and set surface and Intermediate casing. ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

RIG UP, SPUD IN @ 20 00 HRS 7-6-08

DRILLED 17-1/2" HOLE TO 477'. RAN 13-3/8", 68#, J-55, ST&C, CASING. LANDED CASING WITH SHOE @ 472', FLOAT COLLAR @ 430'. CEMENT W/ 20 BBL FW GEL SPACER, LEAD: 166 SX "C" W/ ADDS, YD 2.26, H2O 12 74, DENSITY 12 5 TAIL: 200 SX CLASS "C" W/ ADDS YD 1.34, H2O 6 29, DENSITY 14 8, PLUG DOWN @ 13 15 HRS, BUMP PLUG W/ 500 PSI OVER, 650 #, MAINTAINED FULL RETURNS, 88 SXS TO SURFACE. WELD ON 13 3/8" HEAD, TEST TO 800 PSI-OK INSTALLED AND TESTED BOPE TO 1000 PSI DRILLED OUT SHOE 28 25 HOURS AFTER CEMENT IN PLACE.

DRILLED 12-1/4" HOLE TO 3495'. RAN 8-5/8", 32#, J-55, ST&C CASING SHOE@ 3493' FLOAT COLLAR@3452' CIRCULATE CEMENT W/ SCHLUMBERGER, 20 BBL SPACER 920 SKS. 35' 65 POZ "C" + 5% D44 + 6% D20 + 2PPS D42 + 0.125 PPS D130, 12 6 DENSITY 2 05 YIELD TAIL 200 SKS. "C" + 1% S1 + 0 125PPS D130 14.8 DENSITY 1.33 YIELD DISPLACE W/ FRESH WATER, BUMP PLUG W/ 1378 PSI FLOAT HELD. CIRCULATED 123 SKS CEMENT TO SURFACE. WAIT ON CEMENT CUT OFF 13 5/8" HEAD, WELD ON 11" 3M X 8 5/8" SOW HEAD AND TEST @ 1000 PSI NIPPLE UP BOPE TEST BOPS ANNULAR @ 1500 PSI. DRILL CEMENT AND FLOAT COLLAR TEST CASING @1000 PSI AND FINISH DRILLING CEMENT DRILLED OUT SHOE 24 5 HOURS AFTER CEMENT IN PLACE

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines ☐, a general permit ☐ or an (attached) alternative OCD-approved plan ☐.

SIGNATURE Gene Simer TITLE SUPERINTENDENT DATE 7/30/08

Type or print name GENE SIMER E-mail address: gsimer@rkixp.com Telephone No. 505-885-1313

For State Use Only

APPROVED BY: \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_

Conditions of Approval (if any):

Accepted for record - NMOCD