



UNITED STATES DEPARTMENT OF THE INTERIOR

FORM A	PPROVED
OMB No.	1004-0135
Expires Janu	ary 31, 200

	BUREAU OF LAND MANAGEMENT		OCD-ARTE	3. / 3.	6	
SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.			NM 29279 6. If Indian, Allouee or Tribe Name			
SUBMITINAR	PLICATE - Other instructions o	n revers	e side	7. If Uni	it or CA/Agreement, Name and/or No.	
 Type of Well Gas Well 	Other	SEF	15 2008	8. Well	Name and No.	
2. Name of Operator		OCI	D-ARTESIA		arbold # 5	
REMITT RESOURCES, THE:		9. API Well No. 30-015-24,778				
			10. Field and Pool, or Exploratory Area Empire Y SR			
4. Location of Well (Footage, Sec., T., R., M., or Survey Description) Unit o 350S 1650E S34 T17S R27E NMPM				11. County or Parish, State Eddy NM		
12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA						
TYPE OF SUBMISSION		Т	YPE OF ACTION			
Notice of Intent Subsequent Report	☐ Casing Repair ☐ New C	n re Treat Construction	Production (Stan. Reclamation Recomplete	(Resume)	Water Shut-Off Well Integrity Other	
Final Abandonment Notice	Change Plans Plug at Convert to Injection Plug B	nd Abandon lack	Temporarily AbaWater Disposal	indon		
following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.) Plan to Plug and Abandon by Filling with Ready Mix Concrete. Will have Vacumn Truck on standby in case there is waterAPPROVED present at surface. Cement was circulated when Well was drilled. Will notify Date and Time						
ACCEPTED FOR RECORD					JAMES A. AMOS SUPERVISOR-EPS	
SEP 16 2008			SEE A	ATTACHED FOR		
Gerry Guye, Deputy Field Inspector NMOCD-District ILARTESIA CONDITIONS OF APPROVA						
14. I hereby certify that the foregoing is true and correct Name (Printed/Typed) Daliton Bell Pres. Title				·		
Signature	As Sec	Date	9-3-08			
THIS SPACE FOR FEDERAL OR STATE OFFICE USE AND THE STATE OF THE STATE						
Approved by			Title		Date	
Conditions of approval, if any, are attached. Approval of this notice does not warrant or						
which would entitle the applicant to c	conduct operations thereon.	jour rease	Office			

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

BUREAU OF LAND MANAGEMENT Carlsbad Field Office 620 East Greene Street Carlsbad, New Mexico 88220 575-234-5972

Permanent Abandonment of Federal Wells Conditions of Approval

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

1. Plugging operations shall commence within <u>ninety (90)</u> days from the approval date of this Notice of Intent to Abandon.

If you are unable to plug the well by the 90th day provide this office, prior to the 90th day, with the reason for not meeting the deadline and a date when we can expect the well to be plugged. Failure to do so will result in enforcement action.

- 2. <u>Notification:</u> Contact the appropriate BLM office at least 24 hours prior to the commencing of any plugging operations. For wells in Chaves and Roosevelt County, call 575-627-0272; Eddy County, call 575-361-2822; Lea County, call 575-393-3612.
- 3. <u>Blowout Preventers</u>: A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The minimum BOP requirement is a 2M system for a well not deeper than 9,090 feet; a 3M system for a well not deeper than 13,636 feet; and a 5M system for a well not deeper than 22,727 feet.
- 4. <u>Mud Requirement:</u> Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at the rate of 25 sacks (50 pounds each) of gel per 100 barrels of water. Minimum nine (9) pounds per gallon.
- 5. <u>Cement Requirement</u>: Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. In lieu of a cement plug in a cased hole, a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 25 sacks of cement. If a bailer is used to cap this plug, 35 feet of cement shall be sufficient.

Unless otherwise specified in the approved procedure, the cement plug shall consist of either Neat Class "C", for up to 7,500 feet of depth or Neat Class "H", for deeper than 7,500 feet plugs.

- 6. <u>Dry Hole Marker</u>: All casing shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). The well bore shall then be capped with a 4-inch pipe, 10-feet in length, 4 feet above ground and embedded in cement. The following information shall be permanently inscribed on the dry hole marker: well name and number, name of the operator, lease serial number, surveyed location (quarter-quarter section, section, township and range or other authorized survey designation acceptable to the authorized officer such as metes and bounds).
- 7. <u>Subsequent Plugging Reporting:</u> Within 30 days after plugging work is completed, file one original and five copies of the Subsequent Report of Abandonment, Form 3160-5 to BLM. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. **Show date well was plugged.**
- 8. <u>Trash:</u> All trash, junk and other waste material shall be contained in trash cages or bins to prevent scattering and will be removed and deposited in an approved sanitary landfill. Burial on site is not permitted.

Following the submission and approval of the Subsequent Report of Abandonment, surface restoration conditions of approval will be developed and furnished to you.