

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
May 27, 2004

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-015-3650026037
5. Indicate Type of Lease STATE FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Quick Draw 10 G
8. Well Number 1
9. OGRID Number 14744
10. Pool name or Wildcat Cemetery Yeso

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH
PROPOSALS)

1. Type of Well: Oil Well ☒ Gas Well Other

2. Name of Operator
Mewbourne Oil Company

3. Address of Operator
PO Box 5270 Hobbs, NM 88240

4. Well Location

Unit Letter G : 2310 feet from the N line and 1650 feet from the E line
Section 10 Township 20S Range 25E NMPM Eddy County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3400' GL

Pit or Below-grade Tank Application ☐ or Closure ☐

Pit type _____ Depth to Groundwater _____ Distance from nearest fresh water well _____ Distance from nearest surface water _____

Pit Liner Thickness: _____ mil Below-Grade Tank: Volume _____ bbls; Construction Material _____

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐

OTHER:

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB X

OTHER:

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

09/05/08...MI & spud 11" hole. Ran 803' 8 5/8" 32# J55 LT&C csg. Cemented with 100 sks Thixad Class H with additives. Mixed @ 14.6 #/g w/ 1.52 yd. Tail with 300 sks Class C with 2% CaCl2. Mixed @ 14.8 #/g w/ 1.34 yd. Plug down @ 4:30 am 09/07/08. Circ 100 sks cement to pit. WOC 18 hrs. At 11:45 pm on 09/07/08, tested BOPE and casing to 1500# for 30 minutes, held OK. Drilled out with 7 7/8" bit.

09/11/08 TD'ed 7 7/8" hole @ 3321'. Ran 3321' 4 1/2" 11.6# J55 LT&C csg. Cemented w/500 sks BJ Lite Class C (35:65:6) with additives. Mixed @ 12.5 /g w/2.04 yd. Tail with 400 sks Class H with additives. Mixed @ 15.1 /g w/1.29 yd. Plug down @ 12:15 pm 09/12/08. Circ 78 sks cement to pit. At 12:15 pm on 09/12/08, tested csg to 1000# for 30 mins, held OK. Set casing slips w/32k.

ACCEPTED FOR RECORD

09/12/08...Released rig at 7:00 pm.

SEP 29 2008

Gerry Guye, Deputy Field Inspector
NMOCD-District II ARTESIA

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines ☐, a general permit ☐ or an (attached) alternative OCD-approved plan ☐.

SIGNATURE Jackie Lathan TITLE Hobbs Regulatory DATE 09/24/08

Type or print name Jackie Lathan
For State Use Only

E-mail address: Telephone No. 575-393-5905

APPROVED BY: TITLE DATE
Conditions of Approval (if any):