

Submit 3 Copies To Appropriate District
Office
District I
125 N French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
June 19, 2008

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO.
30-015-20267

5. Indicate Type of Lease
STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name
Pearman BKP

8. Well Number
1

9. OGRID Number
025575

10. Pool name or Wildcat
Wildcat; Morrow

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH
PROPOSALS.)

1. Type of Well: Oil Well ☐ Gas Well ☒ Other

2. Name of Operator
Yates Petroleum Corporation

3. Address of Operator
105 South Fourth Street, Artesia, NM 88210

4. Well Location

Unit Letter K : 1980 feet from the South line and 1980 feet from the West line
Section 32 Township 19S Range 26E NMPM Eddy County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3299'GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐

OTHER: Re-entry procedures and production casing ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

7/8/08 - Cleaned location and began re-entry procedures.

7/14/08 - Tagged surface plug at 8' and began drilling through plugs.

11/16/08 - 11/20/08 - Drilled cement plugs to 2455' - tagged cement. Tested casing to 1000 psi for 30 min. Continued drilling through plugs down to 9799'.

11/21/08 - Reached TD 7-7/8" hole 9804'. Set 5-1/2" 15.5#, 17# J-55 LT&C casing at 9804'. Float collar at 9759'. Cemented with 650 sx 50/50 Poz + 0.125#/sx D130 + 10% D20 + 0.2% D46 + 5% D44 + 0.2% D13 + 0.2% D65 + 0.2% D167 (yld 2.47, wt 11.9). Tailed in with 900 sx PVL + 1.33% D44 + 0.4% D13 + 0.2% D65 + 0.2% D167 (yld 1.40, wt 13). Cement circulated to surface.

ACCEPTED FOR RECORD

APD Re-instated
Late Filing

DEC 15 2008

Gerry Guye, Deputy Field Inspector
NMOCD-District II ARTESIA

Spud Date:

Re-entry 7/8/08

Rig Release Date:

11/22/08

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Tina Huerta TITLE Regulatory Compliance Supervisor DATE December 8, 2008

Type or print name Tina Huerta E-mail address: tinah@yatespetroleum.com PHONE: 575-748-4168

For State Use Only

APPROVED BY: _____ TITLE _____ DATE _____

Conditions of Approval (if any):