## UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT



FORM APPROVED OMB NO 1004-0135 Expires: July 31, 2010

## 5. Lease Serial No. NMNM100549

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an
abandoned well. Use form 3160-3 (APD) for such proposals

6.	If Indian, Allottee or Tribe Name

abandoned wel	6. If Indian, Allottee or Tribe Name							
SUBMIT IN TRII	7. If Unit or CA/Agreement, Name and/or No.							
Type of Well     Oil Well	8. Well Name and No. BLAST BLA FEDERAL 1							
Name of Operator     YATES PETROLEUM CORPO	9. API Well No. 30-015-36136-00-X1							
3a. Address 105 S 4TH STREET ARTESIA, NM 88210	Phone No. (inc : 505.748.41 : 575.748.458	68	)	10. Field and Pool, or Exploratory WILDCAT MISSISSIPPIAN				
4. Location of Well (Footage, Sec., T	., R., M., or Survey Description)		DEC 102	2008	11. County or Parish, a	nd State		
Sec 17 T26S R27E NWSE 19	80FSL 1650FEL		OCD-ARTESIA		EDDY COUNTY, NM			
12. CHECK APPE	ROPRIATE BOX(ES) TO IN	DICATE NA	TURE OF 1	NOTICE, R	EPORT, OR OTHER	DATA		
TYPE OF SUBMISSION	TYPE OF SUBMISSION				TYPE OF ACTION			
Notice of Intent	□ Acidize	☐ Deepen		□ Produc	tion (Start/Resume)	□ Water Shut-Off		
_	☐ Alter Casing	☐ Fracture		□ Reclam		☐ Well Integrity		
Subsequent Report	☐ Casing Repair	□ New Cor	struction	Recomplete		Other Drilling Operations		
Final Abandonment Notice	_	☐ Change Plans ☐ Plug and Abandon ☐ Temporarily Abandon		rarily Abandon	Drining Operations			
	☐ Convert to Injection	□ Plug Bac	k	□ Water I	Disposal			
testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.)  11/11/08 Resumed drilling at 5:45 PM.  11/12/08 TD 17-1/2" hole and set 13-3/8" 48# H-40 ST&C casing at 399'. Cemented with 165 sx Class "C" + D020 + D046 + D903 + S001 (yld 1.98, wt 12.9). Tailed in with 200 sx Class "C" + D903 + S001 (yld 1.34, wt 14.8). Cement circulated to surface. Tested casing to 600 psi. WOC 30 hrs 25 min. Reduced hole to 12-1/4" and resumed drilling.  11/18/08 TD 12-1/4" hole and set 9-5/8" 36# ST&C casing at 2210'. Cemented with 565 sx Class "C" + 4% D20 + 2% S1 + 0.2% D46 (yld 1.98, wt 12.9). Tailed in with 200 sx Class "C" + 2% S1 (yld 1.34, wt 14.8). Cement circulated to surface. Tested casing to 2000 psi for 30 min. WOC 30 hrs  45 min. Reduced hole to 8-3/4" and resumed drilling.								
					DEC 10 2008			
14. I hereby certify that the foregoing is	s true and correct. Electronic Submission #6523 For YATES PETROLEU nmitted to AFMSS for procession	JM CORPORA	TION, sent t	o the Carist	ad-District II AR	spector FESIA		
Name(Printed/Typed) TINA HUE	Titl	REG C	OMPLIANC	E SUPERVISOR				
Signature (Electronic S	Dat	Date 12/03/2008						
	THIS SPACE FOR I	FEDERAL O	R STATE	OFFICE U	SE			
Approved By JAMES A AMOS	Tit	TitleSUPERVISOR EPS			Date 12/07/20			
Conditions of approval, if any, are attached certify that the applicant holds legal or equivalent would entitle the applicant to conditions.	bject lease Of	Office Carlsbad						
Title 18 U S.C. Section 1001 and Title 43 States any false, fictitious or fraudulent	U.S.C. Section 1212, make it a crin statements or representations as to a	ne for any persor any matter within	knowingly a its jurisdictio	nd willfully to n.	make to any department o	r agency of the United		