

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

FEB -9 2009

Form C-103
May 27, 2004

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO.
30-015-36132

5. Indicate Type of Lease
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

Homer State Com

8. Well Number
002

9. OGRID Number
162683

10. Pool name or Wildcat
Chosa Draw; Morrow

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH
PROPOSALS.)

1. Type of Well: Oil Well ☐ Gas Well ☒ Other ☐

2. Name of Operator
Cimarex Energy Co. of Colorado

3. Address of Operator
PO Box 140907; Irving, TX 75014-0907

4. Well Location

SHL Unit Letter L : 1980 feet from the South line and 1250 feet from the West line
Section 2 Township 25S Range 25E NMPM County Eddy

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3564' GR

Pit or Below-grade Tank Application ☐ or Closure ☐

Pit type _____ Depth to Groundwater _____ Distance from nearest fresh water well _____ Distance from nearest surface water _____

Pit Liner Thickness: _____ Below-Grade Tank: Volume _____ bbls; Construction Material _____

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS ☐ P AND A ☐
CASING/CEMENT JOB ☒
OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

05-23-08 Spudded 17½" hole.

05-24-08 Ran 13¾" 48# H-40 STC casing to 325.' Cemented with 340 sx Premium Plus + 2% CaCl₂ (wt 14.8, yld 1.34). Circulated 55 sx to surface. WOC 44.75 hrs.

05-25-08 Pressure-tested surface casing to 1000 psi for 30 minutes.

05-30-08 In 12¼" hole, ran 9¾" 40# J-55 LTC casing to 2244.' Cemented with Lead 960 sx Interfill C + 0.125# Poly-e-flake (wt 11.9, yld 2.45) and Tail 250 sx Premium Plus + 1% CaCl₂ (wt 14.8, yld 1.34). Circulated 183 sx to surface. WOC 29 hours.

05-31-08 Pressure-tested intermediate casing to 1000 psi for 30 minutes.

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines ☐, a general permit ☐ or an (attached) alternative OCD-approved plan ☐.

SIGNATURE Natalie Krueger TITLE Regulatory Analyst DATE February 5, 2009

Type or print name Natalie Krueger email address: nkrueger@cimarex.com Telephone No. 469-420-2723

For State Use Only

APPROVED BY: Accepted for record DATE _____

Conditions of Approval (if any): NMOCD