Form 3160-5 (April 2004)

UNITED STATES DEPARTMENT OF THE INTERIOR

OCD-AKIESIA FFR 18 2000 Stars FORM APPROVED OMB No 1004-0137 Expires March 31, 2007

	BUREALLOFTAN	ND MANAGEMENT	FEB 18 21	5 Lease Serial No
				LC 069641
SUNDRY NOTICES AND REPORTS ON WELLS				6 If Indian, Allottee or Tribe Name
Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.				
				7 If Unit or CA/Agreement, Name and/or No
SUBMIT IN TRIPLICATE – Other instructions on reverse side				NM 71058 X
Type of Well				West Henshaw Premier'Unit
Oil Well Gas Well Other Name of Operator				8 Well Name and No
·				W Henshaw Premier Ut. Tr. 6 #9 9 API Well No
Nordstrand Engineering Inc. 3a Address 3b Phone No (include area code)				
				30-015-03846
229 D'Amico St. # 2200 713 520 1555			To Field and Pool, of Exploratory Area	
Houston, TX 77019 4 Location of Well (Footage, Sec. F. R. M. or Survey Description)				West Henchery Cusyland
				West Henshaw Grayburg 11 County or Parish, State
Unit Letter Q, 2310 FSL & 660 FEL				
Sec. 3, T-16-S, R-30-E, Eddy Co. 12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE. RI				EDDY COUNTY, NM
	PROPRIATE BOX	(ES) TO INDICATE N.		
TYPE OF SUBMISSION			TYPE OF ACTION	V
	Acidize	Deepen	Production (Start/Re	sume) Water Shut-Off
Notice of Intent	Alter Casing	Fracture Treat	Reclamantion	Well Integrity
Subsequent Report	Casing Repair	New Construction	Recomplete	Other
	Change Plans	Plug and Abandon	Temporarily Abando	on C
Final Abandonment Notice	Convert to Injection		Water Disposal	
Attach the Bond under which the following completion of the involtesting has been completed Final determined that the site is ready for the order of	work will be performed operations. If the of Abandonment Notices final inspection.) If the of Abandonment of the and cement equal to the fish, work paid laiden fluid. So I we packer and page plug @ 1060', sx class C cement.	ed or provide the Bond No operation results in a multiple shall be filed only after all uipment. NU BOP. Packer free. Lay down pot 25 sx on top of C pressured up on csg. POH w/ tbg. Perf. cs at @ 500'. WOC 4 hr	on file with BLM/BIA Recompletion or recompletion requirements, including relick up on tbg. Tbg. tbg. and pakcker. IBP. POH to 2295'. (600 psi.). RIH w/tg. @ 500'. Sqz 70 sx s. Tag plug@ 365'.	true vertical depths of all pertinent markers and zones equired subsequent reports shall be filed within 30 days n in a new interval, a Form 3160-4 shall be filed once claimantion, have been completed, and the operator has parted at well head slips. Spear tbg. RIH w/ CIBP on tbg. and set @ 2850'. Spot 30 sx. class C cement. POH w/ bg. to 1350. Spot 30 sx class C Cement. C. class C cement. WOC 4 hrs. RIH to Perf. csg. @ 60'. Sqz. 40 sx class C lown and clean location. Move off.
Approved as to plugging of the well bore. Liability under bond is retained until Surface rectoration is completed. 14 Thereby certify that the foregoing is true and correct) Name (Printed Typed)				APPROVED FEB 1 6 2009 JAMES A. AMOS SUPERVISOR-EPS
Mike Huffman		Titl	e Feild Superv	risor
-11.7.7/				
Signature //////	le comment de la	Dar	The second secon	· ,
	THIS SPAC	CE FOR FEDERAL	OR STATE OFFIC	E USE
			- Accep	ted for record
Approved by Conditions of approval, if any, are attache the applicant holds legal or equitable title applicant to conduct operations thereon	d Approval of this notice to those rights in the subj	e does not warrant or certify, the lect lease which would entitle ti	Title	VMOCD Date

Title 18 U S C Section 1001 and Title 43 U S C Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction