

MAR 27 2009

Form C-103

June 19, 2008

Submit 3 Copies To Appropriate District Office
District I
 1625 N French Dr, Hobbs, NM 88240
District II
 1301 W Grand Ave, Artesia, NM 88210
District III
 1000 Rio Brazos Rd, Aztec, NM 87410
District IV
 1220 S St Francis Dr, Santa Fe, NM 87505

State of New Mexico
 Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
 1220 South St. Francis Dr.
 Santa Fe, NM 87505

WELL API NO.	30-005-60675
5. Indicate Type of Lease STATE ☐ FEE ☒	
6. State Oil & Gas Lease No.	
7. Lease Name or Unit Agreement Name J G O'BRIEN (11602)	
8. Well Number	001
9. OGRID Number	24581
10. Pool name or Wildcat	ELKINS;FUSSELMAN, SOUTH (21720)

SUNDRY NOTICES AND REPORTS ON WELLS
 (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS)

1. Type of Well: Oil Well ☐ Gas Well ☒ Other

2. Name of Operator

WALTER EXPLORATION INC

3. Address of Operator

6116 N CENTRAL EXP #313, DALLAS TX 75206

4. Well Location

Unit Letter **E (Lot 2)** : **1980** feet from the **N** line and **660** feet from the **W** line
 Section **31** Township **07 S** Range **29 E** NMPM County **CHAVES**

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
GL 4020

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒
 TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
 PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
 DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
 COMMENCE DRILLING OPNS. ☐ P AND A ☐
 CASING/CEMENT JOB ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

See attached before and after wellbore schematic.

Notify NMOCDD office Artesia @ 575-748-1283 24 hours prior to commence plugging operations.

1) Set CIBP @ 6650' above open perms 6708-6716. With wireline cap CIBP with 35' cement.

2) Load hole to 5700' w/ 9.5 lb brine mud.

3) Cut & Pull 5 1/2" casing @ 5700'

4) Place cement stub plug 50' in/50' out stub. **TAG ***

5) Set 25 SX cement plug from ~~4600-4500'~~ top ~~Tub @ 4530'~~ **Abo**

6) Shoe plug- cement plug 50' in/50' out of 9 5/8" casing shoe @ 2792'. **TAG ***

7) Load hole w/ 9.5 lb brine mud.

8) Shoe plug- cement plug 50' in/50' out of 13 3/8" casing shoe @ 411'. **TAG ***

9) 60' cement plug from 60' to surface.

9) Install dry hole marker.

Approval Granted providing work
 is complete by **6/30/09**

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Eddie W Seay TITLE AGENT DATE 03/26/2009

Type or print name Eddie W Seay E-mail address: SEAY04@LEACO.NET PHONE: 575-392-2236

For State Use Only

APPROVED BY: [Signature] TITLE Comptroller DATE 3/30/09

Conditions of Approval (if any):

* **Waltcamp required plug. Top @ 5975' cmt plug. 6025'-5925'**
Abo- required Plug. 5264'-5164' - TAG
Glorietta required Plug - 3056'-2956' - TAG.
Yates required Plug - 784'-684'

WELLBORE SCHEMATIC AND HISTORY

COMPLETION SCHEMATIC		APINUM: 30-005-60675																																					
FORM	DEPTH	OPERATOR: WALTER EXPLORATION INC																																					
Yates 734 Queen 1443 San Andres 1900 Glorieta 3006 Tubb 4638 Abo 5214 Wolfcamp 5975 PENN 6386 Miss Lm Fusselman 6700 PLUG 0-60 13 3/8 @ 425' TOC 0' 50'in/50'out Shoe @ 386' PLUG 2741 50'in/50'out Shoe @ 2741' PLUG 25 sxs 4500-4600 STUB PLUG 50'in/50'out - TAG. CUT & PULL @ 5700' 50'in/50'out Shoe @ 5700' 5 1/2 @ 7052' TOC @ 1928' TD 6872		LEASENAME: J G O'BRIEN WELL NO 1																																					
		<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <td>SURF LOC</td> <td>UL</td> <td>E</td> <td>SEC</td> <td>31</td> <td>TWN</td> <td>07S</td> <td>RNG</td> <td>29E</td> </tr> <tr> <td colspan="5">1980 FNL</td> <td colspan="4">660 FWL</td> </tr> <tr> <td>BH LOC</td> <td>UL</td> <td>E</td> <td>SEC</td> <td>31</td> <td>TWN</td> <td>07S</td> <td>RNG</td> <td>29E</td> </tr> <tr> <td colspan="5">1980 FNL</td> <td colspan="4">660 FWL</td> </tr> </table>		SURF LOC	UL	E	SEC	31	TWN	07S	RNG	29E	1980 FNL					660 FWL				BH LOC	UL	E	SEC	31	TWN	07S	RNG	29E	1980 FNL					660 FWL			
		SURF LOC	UL	E	SEC	31	TWN	07S	RNG	29E																													
		1980 FNL					660 FWL																																
		BH LOC	UL	E	SEC	31	TWN	07S	RNG	29E																													
		1980 FNL					660 FWL																																
		<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <td>TD</td> <td>7060</td> <td>PBD</td> <td>6740</td> <td>KB</td> <td>DF</td> </tr> <tr> <td colspan="3"></td> <td>GL</td> <td>4051</td> <td></td> </tr> </table>		TD	7060	PBD	6740	KB	DF				GL	4051																									
		TD	7060	PBD	6740	KB	DF																																
					GL	4051																																	
		<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <td>POOL</td> <td>PERFS</td> <td>6741-6745</td> </tr> <tr> <td colspan="3">ELKINS; FUSSELMAN, SOUTH</td> </tr> <tr> <td>POOL</td> <td>PERFS</td> <td>Open Hole</td> </tr> <tr> <td>POOL</td> <td>PERFS</td> <td></td> </tr> </table>		POOL	PERFS	6741-6745	ELKINS; FUSSELMAN, SOUTH			POOL	PERFS	Open Hole	POOL	PERFS																									
POOL	PERFS	6741-6745																																					
ELKINS; FUSSELMAN, SOUTH																																							
POOL	PERFS	Open Hole																																					
POOL	PERFS																																						
<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <th>SIZE</th> <th>DEPTH</th> <th>CMT</th> <th>HOLE SIZE</th> <th>TOC</th> </tr> <tr> <td>SURF</td> <td>13 3/8</td> <td>411</td> <td>450 sxs</td> <td>17 1/2</td> </tr> <tr> <td>INT1</td> <td>9 5/8</td> <td>2792</td> <td>1000 sxs</td> <td>12 1/4</td> </tr> <tr> <td>PROD</td> <td>5 1/2</td> <td>6791</td> <td>500 sxs</td> <td>8 3/4</td> </tr> </table>		SIZE	DEPTH	CMT	HOLE SIZE	TOC	SURF	13 3/8	411	450 sxs	17 1/2	INT1	9 5/8	2792	1000 sxs	12 1/4	PROD	5 1/2	6791	500 sxs	8 3/4																		
SIZE	DEPTH	CMT	HOLE SIZE	TOC																																			
SURF	13 3/8	411	450 sxs	17 1/2																																			
INT1	9 5/8	2792	1000 sxs	12 1/4																																			
PROD	5 1/2	6791	500 sxs	8 3/4																																			
PLUG 25 sxs 4500-4600 50'in/50'out Shoe @ 2741' PLUG 5244-5164' - TAG. STUB PLUG 50'in/50'out - TAG. CUT & PULL @ 5700' 50'in/50'out Shoe @ 5700' 5 1/2 @ 7052' TOC @ 1928' TD 6872																																							
CIBP @ 66650 CAP W/ 35' CMNT PERFS 6708-6716 CIBP @ 6735 CAP W/ CMNT TOC @ 6723 PERFS 6741-6745																																							
5 1/2 @ 7052' TOC @ 1928' TD 6872																																							
PREPARED BY: UPDATED 03/24/09																																							

WELLBORE SCHEMATIC AND HISTORY

COMPLETION SCHEMATIC		APINUM 30-005-60675																															
FORM	DEPTH	OPERATOR: WALTER EXPLORATION INC																															
		LEASENAME: J G O'BRIEN																															
		WELL NO. 1																															
		SURF LOC	UL: E SEC: 31 TWN 07S RNG 29E																														
		1980 FNL 660 FWL																															
		BH LOC	UL: E SEC: 31 TWN 07S RNG 29E																														
		1980 FNL 660 FWL																															
		TD 7060 PBD 6740 KB DF	GL 4051																														
		POOL PERFS 6741-6745																															
		ELKINS;FUSSELMAN, SOUTH Open Hole																															
		POOL PERFS																															
POOL PERFS																																	
POOL PERFS																																	
<table border="1"> <thead> <tr> <th colspan="6">CASING RECORD</th> </tr> <tr> <th></th> <th>SIZE</th> <th>DEPTH</th> <th>CMT</th> <th>HOLE SIZE</th> <th>TOC</th> </tr> </thead> <tbody> <tr> <td>SURF</td> <td>13 3/8</td> <td>411</td> <td>450 sxs</td> <td>17 1/2</td> <td>0' CIRC</td> </tr> <tr> <td>INT1</td> <td>9 5/8</td> <td>2792</td> <td>1000 sxs</td> <td>12 1/4</td> <td>0' CIRC</td> </tr> <tr> <td>PROD</td> <td>5 1/2</td> <td>6791</td> <td>500 sxs</td> <td>8 3/4</td> <td>5840</td> </tr> </tbody> </table>				CASING RECORD							SIZE	DEPTH	CMT	HOLE SIZE	TOC	SURF	13 3/8	411	450 sxs	17 1/2	0' CIRC	INT1	9 5/8	2792	1000 sxs	12 1/4	0' CIRC	PROD	5 1/2	6791	500 sxs	8 3/4	5840
CASING RECORD																																	
	SIZE	DEPTH	CMT	HOLE SIZE	TOC																												
SURF	13 3/8	411	450 sxs	17 1/2	0' CIRC																												
INT1	9 5/8	2792	1000 sxs	12 1/4	0' CIRC																												
PROD	5 1/2	6791	500 sxs	8 3/4	5840																												
Yates 734 Queen 1443 San Andres 1900 Glorieta 3006 Tubb 4538 Abo 5214 Wolfcamp 5975 TOC @ 5840 PENN 6386 Miss Lm Fusselman 6700 PKR @ 6681 PERFS 6708-6716 CIBP @ 6735 CAP W/ CMNT TOC @ 6723 PERFS 6741-6745 TD 6872																																	
13 3/8 @ 425' TOC 0'																																	
9 5/8 @ 2800' TOC @ 0'																																	
5 1/2 @ 7052' TOC @ 1928'																																	

PREPARED BY

UPDATED

03/24/09