Form 3160- 5 (August, 2007)

UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**



SUNDRY NOTICES AND REPORTS ON WELLS

ARTESIAExpires July 31, 2010 Lease Serial No

Do r	NDRY NOTICES AN not use this form for pro	posals i	to drill or to re	enter an	2000 6 21 Indian, Allotte	NM-05551 ee, or Tribe Name			
	doned well. Use Form 31				7 If I but on CA A	grammant Nama and/or Na			
	TRIPLICATE - Other li	nstructi	ons on page	2.	1	7 If Unit or CA Agreement Name and/or No Nort Indian Basin Unit			
Type of Well Sas Well Gas Well	Other				8 Well Name and				
] NIBU	#19			
2 Name of Operator Marathon Oil Company					9 API Well No.	#19			
3a. Address			3b Phone No (in	oclude area code)	-				
5555 San Felipe @ Mail Stop #3	712	206 2412	30-015-28385						
Houston, Texas 77056	,	713-296-3412		10 Field and Pool, or Exploratory Area					
4 Location of Well (Footage, Sec., T., R.	, M , or Survey Description)		Lat.	32.48841		Draw / Upper Pen Associated			
UL 990'	1,986'	R 23	-E Long.	104.57055	11 County or Paris				
"O" FSL	rel .				Eddy				
12. CHECK APPROPR	JATE BOX(S) TO INDIC	CATE N	IATURE OF N	OTICE, REPORT, O	R OTHER DATA	4			
TYPE OF SUBMISSION				TYPE OF ACTION		•			
X Notice of Intent	Acidize		Deepen	Production (S	tart/ Resume)	Water Shut-off			
	Altering Casing		Fracture Treat	Reclamation		Well Integrity			
Subsequent Report	Casing Repair		New Construction	Recomplete		Other			
	Change Plans		Plug and abandon	X Temporarily	A boudou				
		_	-						
Final Abandonment Notice	Convert to Injection	Ш	Plug back	Water Disposa	d				
**Marathon Oil Company is r North Indian Basin Unit #19			ent status for th	ne above mentioned wel	ii, Acce	epted for record			
> Wait on permit appproval t	pefore beginning this work	! > POC	OH laying down	2-7/8" tubing.					
> MIRU pulling unit and revers	se unit .	> Loa	d casing with fre	esh water					
> Kill well with fresh water.		> Tes	t casing and CIB	P to 500psi per regulato	ry requirements.				
> Install and test 3000# BOP.			Make sure chart recorder installed before pressure testing begins!						
> POOH w / open ended 2-7/8" tubing.		> Sen	d in pressure cha	art to "Regulatory Compl	iance" dept.				
> Pick up and RIH w/ tubing conveyed 7" CIBP			ll plug well head						
> Set CIBP at 7,674'.		> RE							
NOTE: Fresh water to be used, i	`	_	•	2.0	,	,			
Spud Date: Estimated April 2	to top off the well with fresi				ation during this w	vork will be fresh water.			
			~	Estimated April 2009	D	C IV DDC WDE EIELD			
14 I hereby certify that the foregoing is tru	1007 Well HAS	NOT	prod. In	over lyr.	cc: B	G, JV, RRS, WRF, FIELD			
Name (Printed/Typed)	e and correct								
RICK R. SCHELL	_	1	Title	RECHLATO	RV COMPLIANCE	REPRESENTATIVE			
Signature Wind Co	Date	3/16/2009							
- \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	THIS SPACE	FOR F	EDERAL OR	STATE OFFICE US	SE				
	7 1110 01 710		1	:)			
Approved by /s/ JD	Whitlock Jr		Title 6	PET	Dat	3/28/09			
Conditions of approval, if any are attach certify that the applicant holds legal or e- which would entitle the appli-	equitable title to those rights in	oes not w n the sub erations	varrant or ject lease Office thereon	CFO					
Title 18 USC Section 1001 AND Titl States any false, fictitiousor fraudulent staten				~ -	fully to make any o	department or agency of the United			

Procedure:

- Wait on permit approval before beginning this work.
- MIRU pulling unit and reverse unit.
- Kill well with fresh water.
- Install and test 3000# BOP.
- POOH w/ open ended 2 7/8" tubing.
- Pick up and RIH with tubing conveyed 7" CIBP.
- Set CIBP at 7,674.
- POOH laying down 2 7/8" tubing.
- · Load casing with fresh water.
- Test casing and CIBP to 500 psi for 30 minutes per regulatory requirements. Make sure chart recorder is installed before pressure test.
- Send in pressure test chart to regulatory department.
- Bull plug well head.
- RDMO.





16" Conductor Casing Set @ 40'. Cemented to Surface w/ Redi-Mix

9 5/8", 36#, J-55 set at 1196' Cemented to Surface with 800 sks, Circualted 350 sks

Tubing

7,961' of 2 7/8" L-80, Open Ended

Perforations: 7,724-42', 7,750-7,812'

7", 23 & 26#, K-55 Set at 8,100' Cemented to Surface w-1275 Sacks, Circulated 186 sx

Well Name & Number: North Indian Basin Unit #1			19	9 Lea		: NM-05551				
County or Parish:		Eddy	State / Prov.		New Mexico		Country:	U.S.A.		
Perforations	: (MD)			Τ		(TVD)				
Angle/Perfs		Angle @KOP	and Depth	0				KOP TVD	0	
BHP:	0	ВНТ:	0	Co	mpletion Flu	id:				
FWHP:		FBHP:		Π	FWHT:		FBHT:		Other:	
Date Comple	ted:								RKB:	
Prepared By: Bryson Goere		es	L;		Last R	evision Date:	02/09/09			

BUREAU OF LAND MANAGEMENT Carlsbad Field Office 620 East Greene Street Carlsbad, New Mexico 88220 575-234-5972

Temporary Abandonment of Wells on Federal Lands Conditions of Approval

A temporarily abandoned well is defined as a completion that is not capable of production in paying quantities but which may have value as a service well. Pursuant to 43 CFR 3162.3-4 (c), no well may be temporarily abandoned for more than 30 days without the prior approval of the authorized officer.

Temporary Abandonment (TA) status approval requires a successful mechanical or casing integrity test as follows:

- 1. A Notice of Intent (NOI) Sundry Notice (Form 3160-5) requesting approval to run a mechanical integrity test (MIT) or casing integrity test (CIT).
- 2. A description of the temporary abandonment procedure.
 - a. A bridge plug or packer must be installed as close to 50 feet above any open perforations or open hole as possible. If a cement plug is used, the top of the cement must be verified by tagging.
 - b. The wellbore must be filled with corrosion inhibited fluid and pressure tested to 500 psi. The casing shall be capable of holding this pressure for at least 30 minutes with a 10% allowable leakoff.
 - c. All downhole production/injection equipment (tubing, rods, etc.) shall be removed from the casing if they are not isolated by a packer.
 - d. A bradenhead test must be conducted. If the test indicates a problem exists, a remedial plan and time frame for remediation shall be submitted within ninety (90) days of the test.
 - e. Contact the appropriate BLM office at least 24 hours prior to the scheduled Casing Integrity Test. For wells in Eddy County, 575-361-2822; Lea County 575-393-3612.
- 3. Provides justification why the well should be temporarily abandoned rather than permanently plugged and abandoned and an estimated date that the well will be returned to beneficial use or plugged and abandoned.

Wells that successfully pass the casing integrity test may be approved for Temporary Abandonment (TA) status provided that the operator:

- Submits a subsequent Sundry Notice (Form 3160-5) requesting TA approval.
- 2. Describes the temporary abandonment procedure.
- 3. Attaches a clear copy or the original of the pressure test chart.

If the well does not pass the casing integrity test, then the operator shall within 30 days submit to BLM for approval one of the following:

- A procedure to repair the casing so that a TA approval can be granted.
- 2. A procedure to plug and abandon the well.

Submit Subsequent Report and well bore diagram with all Perforations and CIBP with tops of cement. Well will be approved till 10/28/09 after successful MIT and subsequent report is submitted. Operator must submit plans for recompletion or plans to P&A well by October 28, 2009 NIBU #27.