

Submit 3 Copies To Appropriate District
Office
District I
1625 N French Dr , Hobbs, NM 88240
District II
1301 W Grand Ave , Artesia, NM 88210
District III
1000 Rio Brazos Rd , Aztec, NM 87410
District IV
1220 S St Francis Dr , Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

MAR 25 2009

Form C-103
June 19, 2008

RM

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS)		WELL API NO 30-015-31770
1 Type of Well: Oil Well ☐ Gas Well ☒ Other		5. Indicate Type of Lease STATE ☒ FEE ☐
2. Name of Operator Devon Energy Production Co., LP		6. State Oil & Gas Lease No.
3. Address of Operator 20 North Broadway, OKC OK 73102-8260		7. Lease Name or Unit Agreement Name Rifleman 6P State Com
4 Well Location Unit Letter <u>P</u> : <u>720</u> feet from the <u>South</u> line and <u>800</u> feet from the <u>East</u> line Section <u>6</u> Township <u>22S</u> Range <u>26E</u> NMPM Eddy County, NM		8. Well Number 1
11. Elevation (Show whether DR, RKB, RT, GR, etc) 3608' GL		9. OGRID Number 6137
		10. Pool name or Wildcat Happy Valley; Morrow

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐

OTHER: ☐

OTHER: REMOVE PACKER; ISOLATE WET INTERVAL ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

12/02/08:

MIRU W/L trk. Pmp 45 bbls 2% KCL dwn tbg, TIH W/L, perf tbg 1 shot @ 10,930' - 10,932'. RDWL. Swab. Well put to sales.

02/03/09 - 02/12/09:

MIRU. Shot well head w/primer cord & separate tree. NU/BOP. Rls on/off tl & equalize tbg - lch up to pkr. Rls pkr & TOH w/347 jts 2 3/8" tbg. PU 3 7/8" bit w/bailer & hydrotest 347 jts of 2 3/8" tbg in hole to 7000#, all tbg tstd good - tag fill @ 11,135'. RU swivel & D/O fill to 11,376'. Bled well dwn - TOH w/bit - TIH w/4.5" pkr & RBP. Set RBP @ 11,313'. TOH w/tbg - TIH & set 4 5" HD pkr @ 11,213'. Swab & swab tst perfs @ 11,259' - 11,266'. Swab. PUH & set pkr @ 11,145', swab perfs @ 11,176'. Swab. Rls pkr, mv dwn to recover RBP @ 11,313' - had 14' of fill on top of RBP - TOH w/pkr. TIH w/4.5" pkr w/on/off tool & 8' sub w/1.78" R nipple below pkr & 349 just - set pkr @ 11,130' - NU tree & acidize w/3500 gals of 7.5% HCL carrying 80 ball slrs. Swab. Bld well dwn, swab RD/MO/WSU. RBP set @ 11,313'. Turn well over to production.

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE [Signature] TITLE Sr. Staff Engineering Technician DATE 03/24/2009

Type or print name Stephanie A. Ysasaga E-mail address: Stephanie.Ysasaga@dmn.com PHONE: (405)-552-7802

For State Use Only

APPROVED BY: [Signature] TITLE Geologist DATE 3/24/09
Conditions of Approval (if any): MAR 31 2009

DEVON ENERGY PRODUCTION COMPANY LP

Well Name RIFLEMAN 6P STATE COM 1		Field HAPPY VALLEY	
Location 720' FSL & 800' FEL; SEC 6-T22S-R26E		County EDDY	State NM
Elevation 3608' GL, 3624' DF, 3625' KB		Spud Date 10/8/01	Compl Date 12/21/01
API# 30-015-31770	Prepared by Ronnie Slack	Date 2/24/09	Rev

17-1/2" Hole
13-3/8", 48#, H40, @ 508'
 Cmt'd w/600 sx to surface

12-1/4" Hole
9-5/8", 40#, J55, @ 2,416'
 Cmt'd w/975 sx to surface

Top of 4-1/2" Liner @ 9,643'

8-5/8" Hole
7", 26#, P110, @ 9,951'
 Cmt'd w/650 sx TOC @ 6490'-CBL

349 Jts--2-3/8" Production tubing

MORROW
 10976' - 10995'

On/Off tool
Packer @ 11,130' (2/14/09)
 8' sub, 1.78 R nipple

MORROW
 11174' - 11198' 2/13/09 swab 11174-266, avg 400' FE/Hr
 2/14/08 acidized 11174-11266 w/3500 gals 7.5%

MORROW
 11259' - 11266' 2/12/09 swab 11259-266, avg 300' FE/Hr

14' fill, on RBP + 80 ball sealers (2/17/09)
 RBP @ 11313' (2/11/09)

6-1/4" hole
4-1/2", 11.6#, L80, @ 11,548'
 Cmt'd w/250 sx

11502' pbtd

