


Submit To Appropriate District Office District I 1625 N French Dr., Hobbs, NM 88240 District II 1301 W Grand Avenue, Artesia, NM 88210 District III 1000 Rio Brazos Rd., Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505	State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505	Form C-105 July 17, 2008 APR - 2 2009 1. WELL API NO. 30 015 36774 2. Type of Lease ☒ STATE ☐ FEE ☐ FED/INDIAN 3. State Oil & Gas Lease No.								
WELL COMPLETION OR RECOMPLETION REPORT AND LOG										
4. Reason for filing: ☒ COMPLETION REPORT (Fill in boxes #1 through #31 for State and Fee wells only) ☐ C-144 CLOSURE ATTACHMENT (Fill in boxes #1 through #9, #15 Date Rig Released and #32 and/or #33; attach this and the plat to the C-144 closure report in accordance with 19.15.17.13.K NMAC)		5. Lease Name or Unit Agreement Name Reposada 2 State 6. Well Number: 1								
7. Type of Completion: ☒ NEW WELL ☐ WORKOVER ☐ DEEPENING ☐ PLUGBACK ☐ DIFFERENT RESERVOIR ☐ OTHER										
8. Name of Operator OGX Resources, LLC		9. OGRID 217955								
10. Address of Operator P.O. Box 2064, Midland, TX 79702		11. Pool name or Wildcat Brushy Draw Delaware, North Corral Canyon Bone Spring, S(13354)								
12. Location	Unit Ltr	Section	Township	Range	Lot	Feet from the	N/S Line	Feet from the	E/W Line	County
Surface:	B	2	26S	29E		330	North	1980	East	Eddy
BH:	O	2	26S	29E		650 350	South	1980	East	Eddy
13. Date Spudded 12-4-08	14. Date T.D. Reached 1-13-09	15. Date Rig Released 1-14-09		16. Date Completed (Ready to Produce) 1-24-09		17. Elevations (DF and RKB, RT, GR, etc) 3012' GR				
18. Total Measured Depth of Well 9450'		19. Plug Back Measured Depth 9348'		20. Was Directional Survey Made? yes		21. Type Electric and Other Logs Run GR/CCL/CFL				
22. Producing Interval(s), of this completion - Top, Bottom, Name Bone Springs: 8180-9320'										
23. CASING RECORD (Report all strings set in well)										
CASING SIZE	WEIGHT LB./FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED					
13 3/8"	48#	546'	17 1/2"	500 sx CI C	None					
9 5/8"	36#	3075'	12 1/4"	1400 sx CI C	None					
5 1/2"	17#	9450'	7 7/8"	1400 sx CI poz/C	None					
24. LINER RECORD										
SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN						
25. TUBING RECORD										
SIZE	DEPTH SET	PACKER SET								
2 7/8"	8150'									
26. Perforation record (interval, size, and number) 8180' - 7 holes; 8400' - 8 holes; 8640', 8880', 9120', 9320' - 9 holes each										
27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.										
DEPTH INTERVAL			AMOUNT AND KIND MATERIAL USED							
8180-9320'			4162 gals 15% acid							
			Frac w/362,412# sand							
28. PRODUCTION										
Date First Production		Production Method (Flowing, gas lift, pumping - Size and type pump)			Well Status (Prod. or Shut-in)					
2-1-09		pumping			producing					
Date of Test	Hours Tested	Choke Size	Prod'n For Test Period	Oil - Bbl	Gas - MCF					
3-12-09	24			56	216					
Water - Bbl	Gas - Oil Ratio									
253	3857									
Flow Tubing Press.	Casing Pressure	Calculated 24-Hour Rate	Oil - Bbl.	Gas - MCF	Water - Bbl					
					Oil Gravity - API - (Corr.)					
					40					
29. Disposition of Gas (Sold, used for fuel, vented, etc.)					30. Test Witnessed By					
Sales										
31. List Attachments										
Directional Survey, C-104, logs										
32. If a temporary pit was used at the well, attach a plat with the location of the temporary pit. All steel above ground pits										
33. If an on-site burial was used at the well, report the exact location of the on-site burial.										
Latitude		Longitude		NAD 1927 1983						
I hereby certify that the information shown on both sides of this form is true and complete to the best of my knowledge and belief										
Signature		Printed Ann E. Ritchie		Title: Regulatory Agent Date: 3-19-09						
										
E-mail Address: ann.wtor@gmail.com										



DRILLING INC. Oil Well Drilling Contractor

Post Office Box 160 • Artesia, NM 88211-0160 • Office (505) 748-8704 • Fax (505) 748-8719

January 6, 2009

OGX Resources, LLC
P.O. Box 2064
Midland, Texas 79702-2064

Re: Reposado "2" State # 2H
Sec. 2, T-26-S, R-29-E
Eddy County, New Mexico

Attn: Jeff Birkelbach

The following is a Deviation Survey on the referenced well in Eddy County, New Mexico:

186' - 0.75°	3225' - 0.5°
391' - 1.25°	3702' - 1°
530' - 1.5°	4179' - 1.25°
771' - 2.5°	4623' - 0.75°
953' - 2.5°	4998' - 1°
1354' - 2.5°	5478' - 1.25°
1509' - 2.5°	5953' - 1°
1655' - 2°	6460' - 1.75°
1757' - 2°	6950' - 1.5°
1945' - 1.25°	7457' - 2°
2191' - 1°	7921' - 2.75°
2632' - 2.25°	
2791' - 2.25°	
2981' - 0.5°	



OFFICIAL SEAL
Barbara L. Carey
NOTARY PUBLIC-STATE OF NEW MEXICO
My commission expires: Sept. 1, 2009

Sincerely,

Gary W. Chappell
Contracts Manager

STATE OF NEW MEXIC())
COUNTY OF EDDY)

The foregoing was acknowledged before me this 6th day of January, 2009 by Gary W. Chappell.

MY COMMISSION EXPIRES

Sept. 1, 2009

Barbara L. Carey
NOTARY PUBLIC



DIRECTIONAL SURVEY REPORT

OGX RESOURCES, LLC.

REPOSADO 2 STATE #1H

EDDY COUNTY, NEW MEXICO

PREPARED BY: MIKE EVANS


Pathfinder Energy Services, Inc.
6213 W. County Road 112 • Midland, TX • 79706
(432)681-6000

DIRECTIONAL SURVEY COMPANY REPORT:

1. NAME OF SURVEYING COMPANY: PATHFINDER ENERGY SERVICES
2. NAME OF PERSON(S) PERFORMING SURVEY:
A) JUSTIN FALLIN
3. POSITION OF SAID PERSON(S): (A-F) SURVEYORS (FIELD ENGINEERS)
4. DATE(S) ON WHICH SURVEY WAS PERFORMED: 12/30/08 TO 01/12/09
5. STATE IN WHICH SURVEY WAS PERFORMED: NEW MEXICO
6. LOCATION OF WELL: EDDY COUNTY
7. TYPE OF SURVEY(S) PERFORMED: MWD
8. COMPLETE IDENTIFICATION OF WELL:

OGX RESOURCES, LLC.
REPOSADO 2 STATE #1H
EDDY COUNTY, NM
RIG: JW #1
9. SURVEY CERTIFIED FROM: 7,551 TO 9,383 FEET MEASURED DEPTH.

THIS IS TO VERIFY THAT ATTACHED DOCUMENTS SHOWING THE WELL TO BE DISPLACED AT 1,697.19 FEET ON A BEARING OF 173.15 DEGREES FROM THE CENTER OF THE ROTARY TABLE AT A PROJECTED BIT DEPTH OF 9,454 FEET, ARE TRUE AND CORRECT TO THE BEST OF MY KNOWLEDGE.



MIKE EVANS
MWD ENGINEER

PathFinder Energy Services, Inc.

BHL Report

Page 01/01
Tie-in Date: 01/12/2009
Date Completed: 01/07/2009

OGX RESOURCES, INC.
REPOSADO 2 STATE #1H
EDDY COUNTY, NEW MEXICO
Rig:JW #1
PathFinder Office Supervisor: FRANCISCO SINISTERRA
PathFinder Field Engineers:J.FALLIN
M.VLOSICH

Survey Horiz. Reference:WELLHEAD
Ref Coordinates: LAT:32.4.40.5789 N LON:103.57.8.3098 W
GRID Reference:NAD27 new mexico east Transverse Mercator
Ref GRID Coord: X: 618016.1000 Y: 392286.6000
North Aligned To:GRID NORTH
Total Magnetic Correction: 7.83° EAST TO GRID
Vertical Section Plane: 176.59
Survey Vert. Reference: 17.00' Rotary Table To Ground
Altitude:3024.00' Ground To MSL

Measured Depth	9454.00	(feet)
Inclination	86.97	(deg)
Azimuth	172.13	(deg)
True Vertical Depth	8067.69	(feet)
Vertical Section	1694.13	(feet)
Survey X cord	618218.52	(feet)
Survey Y cord	390601.53	(feet)
Survey Lat	32.07330436 N	(deg)
Survey Lon	103.95167403 W	(deg)
Rectangular Corr. N/S	1685.07 S	(feet)
Rectangular Corr. E/W	202.42 E	(feet)
Closure Distance	1697.19	(feet)
Direction of Closure	173.15	(deg)
Dogleg Severity	0.00	(deg/100ft)

PathFinder Energy Services, Inc.

Survey Report

OGX RESOURCES, INC.
REPOSADO 2 STATE #1H
EDDY COUNTY, NEW MEXICO
Rig:JW #1

PathFinder Office Supervisor: FRANCISCO SINISTERRA
PathFinder Field Engineers: J.FALLIN
M.VLOSICH

Survey Horiz. Reference:WELLHEAD
Ref Coordinates: LAT:32.4.40.5789 N LON:103.57.8.3098 W
Reference:NAD27 new mexico east Transverse Mercator
Ref GRID Coord: X: 618016.1000 Y: 392286.6000
North Aligned To:TRUE NORTH
Total Magnetic Correction: 7.83° EAST TO TRUE
Vertical Section Plane: 176.59
Survey Vert. Reference: 17.00' Rotary Table To Ground
Altitude:3024.00' Ground To MSL

Survey Calculations by RX5 V5.11i using Minimum Curvature

Measured Depth (ft)	Incl (deg)	Drift Dir. (deg)	TVD (ft)	Course Length (ft)	Vertical Section (ft)	TOTAL Rectangular Offsets (ft) (ft)	Closure Dist Dir (ft) (deg)	DLS (dg/100ft)
TIE-IN PROVIDED BY SCIENTIFIC DRILLING CONTROLS @ 7500' MD.								
7500.00	2.86	210.59	7497.55	0.00	96.86	92.67 S 73.15 E	118.06@ 141.71	0.00
THE FOLLOWING ARE PATHFINDER MWD SURVEYS.								
7551.00	2.90	227.09	7548.49	51.00	98.73	94.64 S 71.56 E	118.65@ 142.91	1.62
7582.00	3.34	222.04	7579.44	31.00	99.86	95.85 S 70.38 E	118.91@ 143.71	1.67
7613.00	5.36	199.99	7610.35	31.00	101.83	97.88 S 69.28 E	119.92@ 144.71	8.35
7644.00	9.41	183.23	7641.09	31.00	105.68	101.77 S 68.64 E	122.76@ 146.00	14.66
7675.00	12.40	178.79	7671.53	31.00	111.52	107.63 S 68.57 E	127.62@ 147.50	10.01
7706.00	15.30	177.35	7701.62	31.00	118.94	115.05 S 68.83 E	134.06@ 149.11	9.42
7737.00	16.71	177.19	7731.42	31.00	127.48	123.58 S 69.24 E	141.66@ 150.74	4.55
7768.00	18.38	175.79	7760.98	31.00	136.83	132.91 S 69.81 E	150.13@ 152.29	5.56
7799.00	20.84	176.46	7790.18	31.00	147.23	143.29 S 70.51 E	159.70@ 153.80	7.97
7830.00	24.53	177.26	7818.78	31.00	159.18	155.23 S 71.16 E	170.76@ 155.37	11.95
7861.00	27.79	179.85	7846.60	31.00	172.84	168.88 S 71.49 E	183.39@ 157.06	11.14
7891.00	31.74	180.20	7872.63	30.00	187.70	183.77 S 71.48 E	197.19@ 158.75	13.18
7922.00	37.37	178.39	7898.16	31.00	205.26	201.35 S 71.71 E	213.74@ 160.40	18.46
7953.00	43.09	178.52	7921.81	31.00	225.26	221.35 S 72.25 E	232.85@ 161.92	18.45
7984.00	48.98	177.43	7943.32	31.00	247.56	243.64 S 73.05 E	254.36@ 163.31	19.17
8015.00	53.64	178.16	7962.70	31.00	271.74	267.81 S 73.98 E	277.84@ 164.56	15.14
8045.00	59.09	181.09	7979.31	30.00	296.87	292.78 S 74.12 E	302.01@ 165.79	19.90
8075.00	64.19	180.68	7993.56	30.00	322.98	319.16 S 73.71 E	327.57@ 167.00	17.04
8106.00	68.85	178.33	8005.91	31.00	351.37	347.59 S 73.97 E	355.37@ 167.99	16.56
8137.00	75.71	177.06	8015.34	31.00	380.88	377.07 S 75.16 E	384.49@ 168.73	22.47
8168.00	82.04	176.95	8021.31	31.00	411.28	407.43 S 76.75 E	414.60@ 169.33	20.42
8198.00	86.88	177.06	8024.21	30.00	441.13	437.24 S 78.31 E	444.20@ 169.85	16.14
8230.00	89.34	177.11	8025.27	32.00	473.11	469.18 S 79.94 E	475.94@ 170.33	7.69

PathFinder Energy Services, Inc.

Survey Report

OGX RESOURCES, INC.
REPOSADO 2 STATE #1H
EDDY COUNTY, NEW MEXICO
RIG:JW #1

Page 02/03

Measured Depth (ft)	Incl (deg)	Drift Dir. (deg)	TVD (ft)	Course Length (ft)	Vertical Section (ft)	TOTAL Rectangular Offsets (ft) (ft)		Closure Dist (ft)	Dir (deg)	DLS (dg/100ft)
8261.00	88.81	177.09	8025.77	31.00	504.10	500.14 S	81.51 E	506.74@	170.74	1.71
8292.00	87.14	176.86	8026.86	31.00	535.08	531.07 S	83.14 E	537.54@	171.10	5.44
8323.00	85.38	177.08	8028.88	31.00	566.01	561.96 S	84.78 E	568.32@	171.42	5.72
8354.00	83.89	177.09	8031.78	31.00	596.87	592.79 S	86.35 E	599.04@	171.71	4.81
8384.00	83.54	176.68	8035.07	30.00	626.69	622.56 S	87.97 E	628.75@	171.96	1.79
8415.00	84.86	176.44	8038.20	31.00	657.53	653.35 S	89.82 E	659.49@	172.17	4.33
8446.00	84.86	175.75	8040.98	31.00	688.41	684.15 S	91.92 E	690.30@	172.35	2.22
8477.00	86.35	176.00	8043.35	31.00	719.31	714.98 S	94.14 E	721.15@	172.50	4.87
8507.00	88.11	176.20	8044.80	30.00	749.28	744.87 S	96.18 E	751.06@	172.64	5.90
8538.00	90.04	175.61	8045.30	31.00	780.27	775.79 S	98.39 E	782.00@	172.77	6.51
8569.00	90.84	174.70	8045.06	31.00	811.26	806.68 S	101.01 E	812.98@	172.86	3.91
8600.00	91.80	174.29	8044.35	31.00	842.23	837.53 S	103.98 E	843.96@	172.92	3.37
8630.00	91.01	174.48	8043.61	30.00	872.20	867.37 S	106.92 E	873.94@	172.97	2.71
8661.00	90.04	174.07	8043.33	31.00	903.17	898.22 S	110.01 E	904.93@	173.02	3.40
8691.00	88.99	173.56	8043.58	30.00	933.13	928.04 S	113.24 E	934.92@	173.04	3.89
8722.00	89.08	173.40	8044.11	31.00	964.08	958.83 S	116.76 E	965.92@	173.06	0.59
8753.00	90.04	173.23	8044.34	31.00	995.03	989.62 S	120.37 E	996.92@	173.06	3.15
8785.00	89.52	173.17	8044.47	32.00	1026.97	1021.40 S	124.16 E	1028.92@	173.07	1.64
8816.00	89.52	173.89	8044.73	31.00	1057.93	1052.20 S	127.65 E	1059.91@	173.08	2.32
8847.00	88.81	173.94	8045.18	31.00	1088.89	1083.02 S	130.94 E	1090.91@	173.11	2.30
8879.00	89.16	174.22	8045.75	32.00	1120.85	1114.84 S	134.24 E	1122.90@	173.13	1.40
8910.00	91.36	174.68	8045.60	31.00	1151.83	1145.70 S	137.24 E	1153.89@	173.17	7.25
8942.00	91.63	175.28	8044.77	32.00	1183.81	1177.56 S	140.04 E	1185.86@	173.22	2.06
8973.00	87.23	174.13	8045.08	31.00	1214.78	1208.42 S	142.90 E	1216.84@	173.26	14.67
9005.00	87.76	173.58	8046.48	32.00	1246.71	1240.21 S	146.32 E	1248.81@	173.27	2.39
9036.00	87.67	173.89	8047.71	31.00	1277.65	1271.00 S	149.70 E	1279.78@	173.28	1.04

PathFinder Energy Services, Inc.

Survey Report

OGX RESOURCES, INC.
 REPOSADO 2 STATE #1H
 EDDY COUNTY, NEW MEXICO
 RIG:JW #1

Page 03/03

Measured Depth (ft)	Incl (deg)	Drift Dir. (deg)	TVD (ft)	Course Length (ft)	Vertical Section (ft)	TOTAL Rectangular Offsets (ft) (ft)		Closure Dist Dir (ft) (deg)		DLS (dg/100ft)
9068.00	87.67	173.63	8049.01	32.00	1309.58	1302.78 S	153.17 E	1311.75@	173.29	0.81
9099.00	88.11	173.54	8050.15	31.00	1340.52	1333.57 S	156.63 E	1342.73@	173.30	1.45
9131.00	88.46	173.46	8051.11	32.00	1372.46	1365.35 S	160.26 E	1374.72@	173.31	1.12
9162.00	88.20	173.13	8052.02	31.00	1403.40	1396.12 S	163.87 E	1405.71@	173.31	1.36
9194.00	88.81	173.36	8052.85	32.00	1435.33	1427.89 S	167.64 E	1437.69@	173.30	2.04
9225.00	88.55	173.30	8053.56	31.00	1466.27	1458.67 S	171.24 E	1468.69@	173.30	0.86
9257.00	86.44	172.58	8054.96	32.00	1498.18	1490.40 S	175.16 E	1500.65@	173.30	6.97
9288.00	85.56	171.70	8057.13	31.00	1529.01	1521.03 S	179.39 E	1531.57@	173.27	4.01
9320.00	85.74	171.91	8059.55	32.00	1560.80	1552.61 S	183.94 E	1563.47@	173.24	0.86
9351.00	85.65	171.94	8061.88	31.00	1591.61	1583.22 S	188.28 E	1594.37@	173.22	0.31
9383.00	86.97	172.13	8063.94	32.00	1623.44	1614.84 S	192.71 E	1626.30@	173.19	4.17
STRAIGHT LINE PROJECTION TO BIT @ 9454' MD.										
9454.00	86.97	172.13	8067.69	71.00	1694.13	1685.07 S	202.42 E	1697.19@	173.15	0.00

TIE-IN SURVEY INFORMATION SHEET

CLIENT INFORMATION

CLIENT:	OGX RESOURCES LLC		
LEASE / WELL No.:	RESPOSADO 2 STATE	#1H	
WELL LOCATION:	EDDY COUNTY		
COUNTY / STATE / COUNTRY:	EDDY	NEW MEXICO	U.S.A.
RIG:	JW #1		
API WELL No:	30-015-36774		
JOB No:	101008146-WT-WT		
P.O. / AFE No.	0106-0001245-000		
DIRECTIONAL COMPANY:	PATHFINDER ENERGY SERVICES		

WELL SITE INFORMATION

MAGNETIC DECLINATION:			
On Wall Plat:	7.83	LWD Calculated:	7.831847
		Agreed Upon:	7.831847
X =	618016.100000	Feet	Y = 392286.600000
			Feet
SITE LATITUDE:	32.077939 N	SITE LONGITUDE:	103.952308 W
GRID SYSTEM:	☐ UTM ☐ LAMBERT ☒ ZONE: NEW MEXICO EAST		
PROPOSED DRIFT DIRECTION:	176.59		
KELLY BUSHING ELEVATION:	17 FEET		
ALTITUDE:	3012	Feet	WATER DEPTH: 0
			Feet

TIE-IN SURVEY

MEASURED DEPTH:	7500
DRIFT ANGLE:	2.86
DRIFT DIRECTION:	210.59
TRUE VERTICAL DEPTH:	7497.55
VERTICAL SECTION:	-92.67
RECTANGULAR COORDINATE (N / S) :	-92.67
RECTANGULAR COORDINATE (E / W) :	73.15
CLOSURE DISTANCE / DIRECTION:	
SURVEY CALCULATION METHOD:	AA ☐ MC ☒ RC ☐ BT ☐
SOURCE OF TIE-IN DATA (COMPANY):	SCIENTIFIC DRILLING CONTROLS
COPY OF TIE-IN SURVEY REPORT	☐ YES ☒ NO

WELL PLAN

KICKOFF DEPTH:	7472.5'	TOTAL DEPTH:	12460.29'
KICKOFF ANGLE:	0	MAX ANGLE:	90

PES Engineers:

J.C. Fall

**Signature of both field engineers required if applicable

Directional Driller:

Mike Rul

DATE: 12/30/08

PathFinder Energy Services, Inc.

Magnetic & Grid Calculations

OGX RESOURCES, LLC.
REPOSADO 2 STATE #1H
EDDY COUNTY, NEW MEXICO
Rig:JW 1

Tue Dec 16 16:25:38 2008

Coordinates

Latitude: 32.077939 N (32 deg. 4 min. 40.5789 sec.)
Longitude: 103.952308 W (-103 deg. 57 min. 8.3098 sec.)
Elevation: 3024.00 feet.
Calculation Date: Dec/16/2008

Magnetic Calculations

Model: IGRF2005
Dip Angle: 60.0584 degrees
Total Magnetic Field: 0.48764 gauss
Magnetic Declination: 8.034201 degrees
Horizontal Intensity: 0.243390 gauss
To Convert a Magnetic Dir. to a TRUE North Dir. Add 8.034201 Degs

Transverse Mercator Grid Calculations NAD27

Grid System: Transverse Mercator: new mexico east
Ellipsoid: Clarke 1866
X: 618016.1000 feet
Y: 392286.6000 feet
True to Grid: (convergence) -0.202354 degrees
Magnetic to Grid: 7.831847 degrees
To Convert a Magnetic Dir. to a GRID dir. Add 7.831847 Degs.

PathFinder Energy Services, Inc.

Magnetic & Grid Calculations

OGX RESOURCES, INC.
REPOSADO 2 STATE #1H
BRUSHY DRAW DELAWARE-NORTH

Tue Dec 30 15:19:27 2008

Coordinates

Latitude: 32.077939 N (32 deg. 4 min. 40.5789 sec.)
Longitude: 103.952308 W (-103 deg. 57 min. 8.3098 sec.)
Elevation: 3024.00 feet.
Calculation Date: Dec/30/2008

Magnetic Calculations

Model: IGRF2005
Dip Angle: 60.0576 degrees
Total Magnetic Field: 0.48760 gauss
Magnetic Declination: 8.029667 degrees
Horizontal Intensity: 0.243377 gauss
To Convert a Magnetic Dir. to a TRUE North Dir. Add 8.029667 Degr

Transverse Mercator Grid Calculations NAD27

Grid System: Transverse Mercator: new mexico east
Ellipsoid: Clarke 1866
X: 618016.1000 feet
Y: 392286.6000 feet
True to Grid: (convergence) -0.202354 degrees
Magnetic to Grid: 7.827313 degrees
To Convert a Magnetic Dir. to a GRID dir. Add 7.827313 Degr.

DISTRICT I
1625 N. FRENCH DR., HOBBBS, NM 86240

DISTRICT II
1301 W. GRAND AVENUE, ARTESIA, NM 86210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

DISTRICT IV
1220 S. ST. FRANCIS DR., SANTA FE, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources Department

OIL CONSERVATION DIVISION
1220 SOUTH ST. FRANCIS DR.
Santa Fe, New Mexico 87505

Form C-102
Revised October 12, 2005
Submit to Appropriate District Office
State Lease - 4 Copies
Fee Lease - 3 Copies

WELL LOCATION AND ACREAGE DEDICATION PLAT

☐ AMENDED REPORT

API Number 30.015.36774	Pool Code 8085-13354	Pool Name BRUSHY-DRAW DELAWARE-NORTH	Carrai Canyon; Bone Spring, South
Property Code 37487	Property Name REPOSADO "2" STATE		Well Number 1H
OGRID No. 217955	Operator Name OGX RESOURCES		Elevation 3012'

Surface Location

UL or lot No.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
B	2	26-S	29-E		330	NORTH	1980	EAST	EDDY

Bottom Hole Location If Different From Surface

UL or lot No.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
0	2	26-S	29-E		350	SOUTH	1980	EAST	EDDY

Dedicated Acres	Joint or Infill	Consolidation Code	Order No.
160			

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED
OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION

PROJECT AREA → V-6825- PRODUCING AREA → V-6825 GRID AZ. = 176°35'27" HORZ. DIST. = 4716.3' GEODETIC COORDINATES NAD 27 NME Y=392286.6 N X=618016.1 E LAT.=32.077939° N LONG.=103.952308° W BOTTOM HOLE LOCATION Y=387579.7 N X=618296.3 E	POINT OF ENTRY 543' FNL & 1980' FEL S.L. B.H. 1980' 330' 350'	OPERATOR CERTIFICATION I hereby certify that the information herein is true and complete to the best of my knowledge and belief, and that this unitization either owns a working interest unleased mineral interest in the land including the proposed bottom hole location or has a right to drill this well at this location pursuant to a contract with an owner of such mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division. <i>Joe T. Janica</i> Signature Date Joe T. Janica 11/14/08 Printed Name SURVEYOR CERTIFICATION I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief. <i>Ronald J. Eidson</i> Date Surveyed Signature & Seal of Professional Surveyor RONALD J. EIDSON 11/11/08 SURVEYOR Certificate No. GARY EIDSON 12641 RONALD J. EIDSON 3239
--	---	---