

Submit 3 Copies To Appropriate District
Office
District I
1625 N French Dr, Hobbs, NM 88240
District II
1301 W. Grand Ave, Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S St Francis Dr, Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

MAY 13 2009

Form C-103
May 27, 2004

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS)		WELL API NO. 30-005-62771
1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/>		5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
2. Name of Operator Jalapeno Corporation		6. State Oil & Gas Lease No. LG 7996
3. Address of Operator P.O. Box 1608, Albuquerque, NM 87103		7. Lease Name or Unit Agreement Name EMMONS STATE
4. Well Location Unit Letter <u>N : 990</u> feet from the <u>North</u> line and <u>330</u> feet from the <u>West</u> line Section <u>18</u> Township <u>9-S</u> Range <u>28E</u> NMPM County <u>Chaves</u>		8. Well Number 1
11. Elevation (Show whether DR, RKB, RT, GR, etc.)		9. OGRID Number 26307
		10. Pool name or Wildcat Wolf Lake South

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☒ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☒

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

4/7/09-4/17/09

Replaced tubing head. Ran casing scraper & set bridge plug. Ran packer to test casing. Discovered two small leaks in casing, one between 1274 to 1300ft and a second between 245 and 420ft.

Squeezed 250 sacks of Class C Cement with 2%-3% Calcium Chloride, behind casing.

Drilled out cement.

Pressure tested casing to 500 psi. Held pressure.

Cleaned out well to 2295ft. Ran tubing and rods. Placed well back on production on 4/17/09.

Spud Date: **FEBRUARY 28, 1990**

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE: [Signature] TITLE: PRESIDENT DATE 5/11/09

Type or print name HARVEY E. YATES, JR. E-mail address: _____ PHONE: 505-242-2050

For State Use Only

APPROVED BY: [Signature] TITLE Geologist DATE 5/15/2009
Conditions of Approval (if any): _____