Approved By

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Date

|  | UNITED STATE EPARTMENT OF THE  | INTERIOR  | MAY   | 18 2009  | · · · OMB NO  | APPROVED<br>D-1004-0135<br>July 31, 2010                                     |  |
|--|--|---|---|--|---|--|--|
| SUNDRY NOTICES AND REPORTS ON WELLS  Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.   |  |   |   | 5 Lease Senal No<br>NMNM67985                          |   |  |  |
| abandoned we   | IS form for proposals to<br>II. Use form 3160-3 (AF  | PD) for such  | oroposals.  | -  | 6. If Indian, Allottee or   | r Tribe Name   |  |
| SUBMIT IN TRIPLICATE - Other instructions on reverse side.   |  |   |   |  | 7 If Unit or CA/Agreement, Name and/or No<br>NMNM119887                                 |  |  |
| Type of Well  ☑ Oil Well ☐ Gas Well ☐ Other  |  |   |   |  | 8 Well Name and No<br>BENSON 3 FEDERÁL 6  |  |  |
| 2 Name of Operator Contact: LINDA GOOD CHESAPEAKE OPERATING, INC. E-Mail: linda.good@chk.com   |  |   |   |  | 9 API Well No.<br>30-015-26565 /  |  |  |
| 3a. Address<br>P.O. BOX 18496<br>OKLAHOMA CITY, OK 7315  | 3b. Phone No (include area code) Ph: 405-935-4275 Fx: 405-849-4275   |   |   | 10. Field and Pool, or Exploratory SHUGART             |   |  |  |
| 4. Location of Well (Footage, Sec., T., R., M., or Survey Description)   |  |   |   |  | 11 County or Parish, and State  |  |  |
| Sec 3 T19S R30E SENE 2310FSL 480FEL  |  |   |   |  | EDDY COUNTY, NM   |  |  |
|  | •  |   | ,   |  | ,   |  |  |
| 12. CHECK APP  | ROPRIATE BOX(ES) T   | O INDICATE  | NATURE OF N   | NOTICE, RE   | PORT, OR OTHER  | DATA   |  |
| TYPE OF SUBMISSION   | ,  |   | TYPE OF   | F ACTION   | ,   |  |  |
| Notice of Intent   | □ Acidize  | □ Dee   |   | _  | ion (Start/Resume)  | □ Water Shut-Off   |  |
|  | ☐ Alter Casing   | _   | cture Treat   | □ Reclama  |   | □ Well Integrity   |  |
| ☐ Subsequent Report  | ☐ Casing Repair  |   | v Construction  | Recomp   |   | Other .  |  |
| Final Abandonment Notice   | Change Plans   |   | g and Abandon   |  | arily Abandon . , , ,   | • ' •  |  |
|  | Convert to Injection   | _   | g Back  | □ Water D  | •   |  |  |
| 13. Describe Proposed or Completed O If the proposal is to deepen directio Attach the Bond under which the w following completion of the involve testing has been completed. Final A determined that the site is ready for | nally or recomplete horizontall<br>ork will be performed or provi<br>ed operations. If the operation<br>Abandonment Notices shall be | ly, give subsurfac<br>de the Bond No.<br>results in a multi | e locations and meas<br>on file with BLM/Bl<br>ple completion or re | sured and true v<br>IA. Required si<br>completion in a | vertical depths of all perti<br>ubsequent reports shall be<br>a new interval, a Form 31 | inent markers and zone<br>e filed within 30 days<br>60-4 shall be filed once |  |
| CHESAPEAKE, RESPECTF<br>PROCEDURE:   | JLLY, REQUESTS PERI  | MISSION TO I  | PLUG & ABANDO   | ON THIS WE   | ELL PER THE FOLL  | OWING P&A  |  |
| 1. NOTIFY THE BLM 24 HO  | JRS IN ADVANCE PRIO  | R TO COMME  | ENCING PLUG A   | ND ABAND   | ONMENT OPERATION  | ONS.   |  |
| 2. HOLD TAILGATE SAFETY OPERATIONS.  | / MEETING PRIOR TO B   | BEGINNING W   | •   |  |   | R SPECIFIC   |  |
| 3. RACK AND TALLY 116 JC   | )INTS OF 2-7/8" N-80 W   | ORKSTRING.  | \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \                               | SEE ATT  | ACHED FOR   |  |  |
| 4. PREPARE LOCATION. T   | EST ANCHORS. $(\  ot\! R$  | -111-   | P )   | CONDIT   | IONS OF APPI  | ROVAL  |  |
| X See Attacher   | d Reclama  | tion  | Procedu   | re c"  |   |  |  |
| 14. I hereby certify that the foregoing  | is true and correct. Electronic Submission   | #69863 verifie  | by the BLM Well   | I Information  | System  |  |  |
| ,  | For CHESAPE  | AKE OPERATII  | IG, INC., sent to   | the Carlsbad   |   |  |  |
| Name (Printed/Typed) LINDA G   | OOD  |   | Title SR. RE  | GULATORY   | COMPLIANCE SPE  | EC   |  |
| Signature (Electronic  | Submission)  |   | Date 05/08/2  | 009  |   |  |  |
| ,  | THIS SPACE F   | OR FEDERA   | AL OR STATE   | OFFICE U   | <b>SPPROVE</b>  | D  |  |

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and will fully to make it by any departments of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

Title

Office

### Additional data for EC transaction #69863 that would not fit on the form

- 32. Additional remarks, continued
- 5. MIRU PU. NDWH. NU AND TEST BOP.
- 6. RIH W/GAUGE RING AND JUNK BASKET TO PBTD @ 3453'.
- 7. RIH W/CIBP AND SET @ 2,900'. DUMP BAIL 35' OF CEMENT ON THE CIBP @ 2,900'. WAIT ON CEMENT AND TAG PLUG.
- 8. LOAD WELL WITH PLUGGING MUD AND PRESSURE UP TO 500# AND TEST FOR LEAK-OFF.
- RIH W/CIBP AND SET @ 1,740. DUMP BAIL 35' OF CEMENT ON THE CIBP @ 1,740. WAIT ON CEMENT AND TAG PLUG. (BASE OF SALT @ 1,740')
- M. RIH W/CIBP AND SET @ 545' AND SET A 110' CEMENT PLUG. PULL UP HOLE, WAIT 4 HOURS AND TAG PLUG. POH. (8 5/8" CASING SHOE @ 495' AND TOP OF SALT # 545')
- .11. PERFORATE CASING @ 60' W/4 SQUEEZE HOLES AND SQUEEZE A CEMENT PLUG INSIDE AND OUT. CIRCULATE TO SURFACE. TOP OFF CASING. POH.
- 12. RDMO. INSTALL DRY HOLE MARKER AND CUT OFF DEAD MAN. RESTORE LOCATION.

(CHK PN 890933)

9. Either Set CIBP @ 1790 and Spot solid ent plug from 1790' - 625' (RIIIP Potash) Tag or. Spot a plug from 1790 - 625' woc Tag 10. Combine plugs, woc and Tag @ 435. R-111-P

| William William   | a circ-Suit JALT SECTIONS JOP  |
|---|--|
| HOLE SIZE 12/4"   | Perfo 60 RAGE 1745   |
|   | Toc. @ 60' CBL RILLE /es   |
|   |  |
| Cicc.   | CAVE/KARST   |
|   | SFEC WATER   |
|   |  |
| K-SS  | 435 WOC Tag  |
| CASING SIZE 85/8 24   |  |
| TD 485'   |  |
|   | 525  |
| HOLESIZE 7/8"   |  |
|   | FORMATIONS Yetus 2245  |
|   | 7R 2470  |
|   | 01/1/ Qu 2920  |
|   | Solid Plug   |
|   | Then Potash  |
|   | R-111-A  |
|   |  |
|   |  |
|   | The state of the s |
|   | To be a second of the second o |
|   | CIBA   |
|   |  |
|   |  |
|   |  |
|   |  |
|   |  |
| Market | CIBA@ 2900 + AB 35'emt   |
|   |  |
|   |  |
| K-53 (#   |  |
| 1/11/14/  | DVT  |
| CASING SIZE 5/2 15/4  | PERFORATIONS 3018-3063   |
| TD 3500   | 2938-2982  |
| PBTD 3453   |  |
|   |  |

# BUREAU OF LAND MANAGEMENT Carlsbad Field Office 620 East Greene Street Carlsbad, New Mexico 88220 575-234-5972

#### Permanent Abandonment of Federal Wells Conditions of Approval

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

1. Plugging operations shall commence within <u>ninety (90)</u> days from the approval date of this Notice of Intent to Abandon.

If you are unable to plug the well by the 90<sup>th</sup> day provide this office, prior to the 90<sup>th</sup> day, with the reason for not meeting the deadline and a date when we can expect the well to be plugged. Failure to do so will result in enforcement action.

- 2 <u>Notification:</u> Contact the appropriate BLM office at least 24 hours prior to the commencing of any plugging operations. For wells in Chaves and Roosevelt County, call 575-627-0272; Eddy County, call 575-361-2822; Lea County, call 575-393-3612.
- 3. <u>Blowout Preventers</u>: A blowout preventer (BOP), as appropriate, shall be installed prior to commencing any plugging operation. The minimum BOP requirement is a 2M system for a well not deeper than 9,090 feet; a 3M system for a well not deeper than 13,636 feet; and a 5M system for a well not deeper than 22,727 feet
- 4. <u>Mud Requirement:</u> Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at the rate of 25 sacks (50 pounds each) of gel per 100 barrels of water. Minimum nine (9) pounds per gallon.
- 5. <u>Cement Requirement</u>: Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. In lieu of a cement plug in a cased hole, a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 25 sacks of cement. If a bailer is used to cap this plug, 35 feet of cement shall be sufficient.

Unless otherwise specified in the approved procedure, the cement plug shall consist of either Neat Class "C" for up to 7,500 feet of depth or Neat Class "H", for deeper than 7,500 feet plugs.

- 6. <u>Dry Hole Marker</u>: All casing shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). The well bore shall then be capped with a 4-inch pipe, 10-feet in length, 4 feet above ground and embedded in cement. The following information shall be permanently inscribed on the dry hole marker: well name and number, name of the operator, lease serial number, surveyed location (quarter-quarter section, section, township and range or other authorized survey designation acceptable to the authorized officer such as metes and bounds).
- 7. <u>Subsequent Plugging Reporting:</u> Within 30 days after plugging work is completed, file one original and five copies of the Subsequent Report of Abandonment, Form 3160-5 to BLM. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. **Show date well was plugged.**
- 8. <u>Trash:</u> All trash, junk and other waste material shall be contained in trash cages or bins to prevent scattering and will be removed and deposited in an approved sanitary landfill. Burial on site is not permitted.

Following the submission and approval of the Subsequent Report of Abandonment, surface restoration conditions of approval will be developed and furnished to you.



# United States Department of the Interior

## BUREAU OF LAND MANAGEMENT

Carlsbad Field Office 620 E Greene St Carlsbad, New Mexico 88220-6292 www.blm.gov/nm



In Reply Refer To 1310

### Reclamation (Interim/Final) Procedures

Reclamation Objective: Oil and gas development is one of many uses of the public lands and resources. While development may have a short- or long-term effect on the land, successful reclamation can ensure the effect is not permanent. During the life of the development, all disturbed areas not needed for active support of production operations should undergo "interim" reclamation in order to minimize the environmental impacts of development on other resources and uses. At final abandonment, well locations, production facilities, and access roads must undergo "final" reclamation so that the character and productivity of the land and water are restored.

The long-term objective of final reclamation is to set the course for eventual ecosystem restoration, including the restoration of the natural vegetation community, hydrology, and wildlife habitats. In most cases this means returning the land to a condition approximating or equal to that which existed prior to the disturbance. The final goal of reclamation is to restore the character of the land and water to its predisturbance condition. The operator is generally not responsible for achieving full ecological restoration of the site. Instead, the operator must achieve the short-term stability, visual, hydrological, and productivity objectives of the surface management agency and take steps necessary to ensure that long-term objectives will be reached through natural processes.

To achieve these objectives, remove any and all contaminants, scrap/trash, equipment, pipelines and powerlines. Strip and remove caliche, contour the location to blend with the surrounding landscape, redistribute the native soils, provide erosion control as needed, rip and seed as specified in the original APD COA. This will apply to well pads, facilities, and access roads. Barricade access road at the starting point. If reserve pits have not reclaimed due to salts or other contaminants, submit a plan for approval, as to how you propose to provide adequate restoration of the pit area.

- 1. The Application for Permit to Drill or Reenter (APD, Form 3160-3), Surface Use Plan of Operations must include adequate measures for stabilization and reclamation of disturbed lands. Oil and Gas operators must plan for reclamation, both interim and final, up front in the APD process as per Onshore Oil and Gas Order No. 1.
- 2. For wells and/or access roads not having an approved plan, or an inadequate plan for surface reclamation (either interim or final reclamation), the operator must submit a proposal describing the procedures for reclamation. For interim reclamation, the appropriate time for submittal would be when filing the Well Completion or Recompletion Report and Log (Form 3160-4). For final reclamation, the appropriate time for submittal would be when filing the Notice of Intent, or the Subsequent Report of Abandonment, Sundry Notices and Reports on Wells (Form 3160-5). Interim reclamation is to be completed within 6 months of well completion, and final reclamation is to be completed within 6 months of well abandonment.
- 3. The operator must file a Subsequent Report Plug and Abandonment (Form 3160-5) following the plugging of a well.
- 4. Previous instruction had you waiting for a BLM specialist to inspect the location and provide you with reclamation requirements. If you have an approved Surface Use Plan of Operation and/or an approved Sundry Notice, you are free to proceed with reclamation as per approved APD. If you have issues or concerns, contact a BLM specialist to assist you. It would be in your interest to have a BLM specialist look at the location and access road prior to the removal of reclamation

equipment to ensure that it meets BLM objectives. Upon conclusion submit a Form 3160-5, Subsequent Report of Reclamation. This will prompt a specialist to inspect the location to verify work was completed as per approved plans.

- 5. The approved Subsequent Report of Reclamation will be your notice that the native soils, contour and seedbed have been reestablished. If the BLM objectives have not been met the operator will be notified and corrective actions may be required.
- 6. It is the responsibility of the operator to monitor these locations and/or access roads until such time as the operator feels that the BLM objective has been met. If after two growing seasons the location and/or access roads are not showing the potential for successful revegetation, additional actions may be needed. When you feel the BLM objectives have been met submit a Final Abandonment Notice (FAN), Form 3160-5, stating that all reclamation requirements have been achieved and the location and/or access road is ready for a final abandonment inspection.
- 7. At this time the BLM specialist will inspect the location and/or access road. If the native soils and contour have been restored, and the revegetation is successful, the FAN will be approved, releasing the operator of any further liability of the location and/or access road. If the location and/or access road have not achieved the objective, you will be notified as to additional work needed or additional time being needed to achieve the objective.

If there are any questions, please feel free to contact any of the following specialists:

Jim Amos Supervisory Environmental Protection Specialist 575-234-5909, 575-361-2648 (Cell)

Terry Gregston Environmental Protection Specialist 575-234-5958

Bobby Ballard Environmental Protection Specialist 575-234-2230

Randy Rust Environmental Protection Specialist 575-234-5943

Linda Denniston Environmental Protection Specialist 575-234-5974

Jennifer Van Curen Environmental Protection Specialist 575-234-5905

Justin Frye Environmental Protection Specialist 575-234-5922 Cody Layton Natural Resource Specialist 575-234-5959

Trishia Bad Bear Natural Resource Specialist 575-393-3612

Todd Suter Surface Protection Specialist 575-234-5987

Doug Hoag Civil Engineering Technician 575-234-5979