

AUG 18 2009

Form C-103

May 27, 2004

Submit 3 Copies To Appropriate District  
Office  
District I  
1625 N French Dr, Hobbs, NM 87240  
District II  
1301 W Grand Ave, Artesia, NM 88210  
District III  
1000 Rio Brazos Rd, Aztec, NM 87410  
District IV  
1220 S St Francis Dr, Santa Fe, NM 87505

State of New Mexico  
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

WELL API NO. 30-015-22895
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. 647-371
7. Lease Name or Unit Agreement Name. Empire Abo Unit 'F'
8. Well Number 343
9. OGRID Number 00778
10. Pool name or Wildcat Empire Abo

**SUNDRY NOTICES AND REPORTS ON WELLS**  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS)

1. Type of Well. Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other	2. Name of Operator BP America Production Company
3. Address of Operator P.O. Box 1089 Eunice NM 88231	4. Well Location Unit Letter <u>F</u> <u>2300</u> feet from the <u>N</u> line and <u>1675</u> feet from the <u>W</u> line Section <u>34</u> Township <u>17S</u> Range <u>28E</u> NMPM County <u>EDDY</u>
11 Elevation (Show whether DR, RKB, RT, GR, etc) 3662' GR	
Pit or Below-grade Tank Application <input type="checkbox"/> or Closure <input type="checkbox"/> Pit type _____ Depth to Groundwater _____ Distance from nearest fresh water well _____ Distance from nearest surface water _____ Pit Liner Thickness: _____ mil Below-Grade Tank: Volume _____ bbls; Construction Material _____	

12. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	MULTIPLE COMPLETION <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	
OTHER <input type="checkbox"/>		OTHER <input type="checkbox"/>	

13 Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions. Attach wellbore diagram of proposed completion or recompletion.

8/7/09: MIRU. PUMP 30 BBL KILL WELL ND WH NU BOP.

8/8/09: POH LD 193 JOINTS, RIH TO 5800' W BIT AND SCRAPER POH TO 1500'

8/11/09: POH W/ KILL STRING LD BIT & SCRAPER PU CIBP RIH SET @ 5721 LOAD AND TEST TO 500 PSI. SPOT 25 SKS OF CLASS C NEAT FROM 5721-5471. WITNESSED BY PHIL HAWKINS, NMOCD. POH LD 10 JOINTS CIRCULATE HOLE W 9.5 PLUG MUD SALT WATER CLAY 40 VIS 140BBL. CMT 25 SKS OF CLASS C NEAT FROM 5400' POH TO 3700'.

Continued on page 2.

I hereby certify that the information above is true and complete to the best of my knowledge and belief I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines ☐ , a general permit ☐ or an (attached) alternative OCD-approved plan ☐

SIGNATURE Barry C. Price TITLE Area Operations Team Lead DATE 8/17/09

Type or print name Barry C. Price

E-mail address

barry.price@bp.com

Telephone No. 575-394-1648

For State Use Only

APPROVED BY Phil Hawkins TITLE

Conditions of Approval, if any.

Approved for plugging of well bore only.  
Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms. [www.cmnrd.state.nm.us/oed](http://www.cmnrd.state.nm.us/oed).

DATE 8/18/09

Form C-103  
Empire Abo Unit F-343  
30-015-22895  
Continued from page 1

8/12/09: M&P 25 SKS. CLASS (C) 15. PPG F- 3700'. POOH L/D 10 JTS. POOH  
L/D CIBP SETTING TOOL P/U SLOTTED SUB TIH WHILE WOC. RIH TAG  
CMT @ 3443' CMT. F- 3700'T- 3443'. L/D TBG. TO 1450' M&P 160 SKS. 14.9  
PPG CLASS (C) CMT. FROM 1450' TO SURFACE . L/D TBG. R/D FLOOR.

8/17/09: DIG OUT AROUND WELLHEAD. CUT OFF ALL ANCHORS AND  
WELL HEAD, WELD IN PLATE, 1" NIPPLE & VALVE, DRY HOLE MARKER,  
BACKFILL AND LEVEL LOCATION.