E Sundry	UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter an bandoned well. Use form 3160-3 (APD) for such proposals.			S		PPROVED 1004-0135 ember 30, 2000
SUBMIT IN TR	IPLICATE - Other instruc	ctions on rev	erse side. RECEIV	ED	7. If Unit or CA/Agreer	nent, Name and/or No.
Type of Well Oil Well	JAN 0 1 7	ŀ	8. Well Name and No. KITTY HAWK FED	ERAL 1		
2. Name of Operator LYNX PETROLEUM CONSULTANTS INC Contact: MARC WI E-Mail: lynx			e e e e e e e e e e e e e e e e e e e		9. API Well No. 30-015-32746-00-X1	
3a. Address P O BOX 1708 HOBBS, NM 88241		3b. Phone No. (include area code) Ph: 505.392.6950 Fx: 505.392.7886)	10. Field and Pool, or Exploratory SHUGART-MORROW SHUGART-STRAWN	
4. Location of Well (Footage, Sec., 7	11. County or Par		11. County or Parish, ar	d State		
Sec 1 T19S R31E NWSE 198			EDDY COUNTY,	NM		
12. CHECK APP	ROPRIATE BOX(ES) TO	O INDICATE	NATURE OF	NOTICE, RE	PORT, OR OTHER	DATA
TYPE OF SUBMISSION	TYPE OF ACTION					
☐ Notice of Intent	☐ Acidize	☐ Deep	pen	☐ Producti	on (Start/Resume)	☐ Water Shut-Off
_	☐ Alter Casing		☐ Fracture Treat		tion	☐ Well Integrity
Subsequent Report	☐ Casing Repair	_	Construction Recomp			☑ Other Drilling Operations
☐ Final Abandonment Notice	☐ Change Plans	-	and Abandon	☐ Temporarily Abandon		Dinning Operations
	Convert to Injection	☐ Plug		☐ Water D		
13. Describe Proposed or Completed Op If the proposal is to deepen direction Attach the Bond under which the work following completion of the involve testing has been completed. Final Adetermined that the site is ready for Drilled 11" hole to 4500'. Ran 100 jts 8 5/8", 32#, K-55. Cemented with 875 sxs 35:65 1% CaCl2 mixed at 14.8 ppg job. Cement did not circulate pipe and tagged cement top a had cement returns at surface bit.	ally or recomplete horizontally, or will be performed or provide d operations. If the operation re bandonment Notices shall be fil final inspection.) ST&C to 4500'. 5:6 Class C mixed at 12.5 (1.34 cf/sx). Plug down at to surface. Ran temperatuat 340'. Pumped 111 sxs 0	give subsurface the Bond No. or sults in a multiple ed only after all a ppg (2.00 cf/s 8:45 pm 12/2 ure survey. To Class C neat r	locations and meast file with BLM/BI/e e completion or rec requirements, includes ax), followed by 1 4/03. Had full m p of cement at 1 nixed at 14.8 pp	ared and true ver A. Required sub completion in a n- ling reclamation 250 sxs Class and returns du 350'. Ran 1" g (1.34 cf/sx)	tical depths of all pertines sequent reports shall be fi ew interval, a Form 3160, have been completed, ar	nt markers and zones. led within 30 days 4 shall be filed once
	Electronic Submission a For LYNX PETROLI ommitted to AFMSS for pro	EUM CONSULI	rants INC, sent NDA ASKWIG on	t to the Carlsb 12/31/2003 (0	ad 4LA0062SE)	
Name (Printed/Typed) MARC W	Title REPOR	RT AUTHORI	ZER			
Signature (Electronic	Submission)	<u> </u>	Date 12/30/2	2003		
	THIS SPACE FO	OR ENDERA	L OR STATE	OFFICE US	SE	
Approved By ACCEPT	ED	<i>b</i>	ALEXIS C TitlePETROLE	SWOBODA UM ENGINE	ER OCA	Date 12/31/2003

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those which would entitle the applicant to conduct operations the subject lease which would entitle the applicant to conduct operations the subject lease which would entitle the applicant of conduct operations the subject lease which would entitle the applicant of conduct operations the subject lease which would entitle the applicant of conduct operations the subject lease which would entitle the applicant of conductions and the subject lease which would entitle the applicant of conductions are subject lease. Office Carlsbad Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.