

## State of New Mexico

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88241-1980

Energy, Minerals and Natural Resources Department

Form C-102

Revised February 10, 1994

Submit to Appropriate District Office

State Lease - 4 Copies

Fee Lease - 3 Copies

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88211-0719

## OIL CONSERVATION DIVISION

P.O. Box 2088

Santa Fe, New Mexico 87504-2088

DISTRICT III  
1000 Rio Brazos Rd., Artec, NM 87410

DISTRICT IV  
P.O. BOX 2088, SANTA FE, N.M. 87504-2088

## WELL LOCATION AND ACREAGE DEDICATION PLAT

☐ AMENDED REPORT

API Number 30-015-32804	Pool Code	Pool Name
Property Code 32388	Property Name SOUTHWEST TT "11" STATE	Well Number 1
OGRID No. 194930	Operator Name EDGE PETROLEUM OPERATING COMPANY, INC.	Elevation 3388'

## Surface Location

UL or lot No. L	Section 11	Township 19-S	Range 29-E	Lot Idn	Feet from the 1830'	North/South line SOUTH	Feet from the 660'	East/West line WEST	County EDDY
--------------------	---------------	------------------	---------------	---------	------------------------	---------------------------	-----------------------	------------------------	----------------

## Bottom Hole Location If Different From Surface

UL or lot No.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
---------------	---------	----------	-------	---------	---------------	------------------	---------------	----------------	--------

Dedicated Acres 320	Joint or Infill	Consolidation Code	Order No.
------------------------	-----------------	--------------------	-----------

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED  
OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION

	<p>RECEIVED DEC 2:6 2003 OCD-ARTESIA</p>	<p>GEODETIC COORDINATE NAD "1927" NME Y = 608611.8 N X = 586740.9 E LAT. 32°40'22.28"N LONG. 104°03'05.19"W</p>	<p>OPERATOR CERTIFICATION</p> <p>I hereby certify the the information contained herein is true and complete to the best of my knowledge and belief.</p> <p><i>Jim Keisling</i> Signature</p> <p>Jim Keisling Printed Name</p> <p>Chief Engineer Title</p> <p>December 10, 2003 Date</p>
			<p>SURVEYOR CERTIFICATION</p> <p>I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.</p> <p>September 18, 2003</p> <p>Date Surveyed _____ AWB</p> <p>Signature &amp; Seal of Professional Surveyor</p> <p><i>Gary E. Eason</i> 9/19/03 03.11.1048</p> <p>Certificate No. ROMAN L. EIDSON 3238 CARY EIDSON 12641</p>

# **HYDROGEN SULFIDE DRILLING OPERATIONS PLAN**

## **EDGE PETROLEUM OPERATING CO., INC.** **Southwest TT "11" State #1**

### **I. HYDROGEN SULFIDE TRAINING**

- A. All regularly assigned personnel, contracted or employed by Edge Petroleum Operating Co., Inc., will receive training from a qualified instructor in the following areas prior to commencing drilling potential hydrogen sulfide bearing formations in this well:**
  - 1. The hazards and characteristics of hydrogen sulfide (H<sub>2</sub>S).**
  - 2. The proper use and maintenance of personal protective equipment and life support systems.**
  - 3. The proper use of H<sub>2</sub>S detectors, alarms, warning systems, briefing areas, evacuation procedures and prevailing winds.**
  - 4. The proper techniques for first aid and rescue procedures.**
- B. In addition, supervisory personnel will be trained in the following areas:**
  - 1. The effects of H<sub>2</sub>S on metal components. If high tensile tubulars are to be used, personnel will be trained in their special maintenance requirements.**
  - 2. Corrective action and shut-in procedures when drilling or reworking a well and blowout prevention and well control procedures.**
  - 3. The contents and requirements of the H<sub>2</sub>S Drilling Operations Plan.**
- C. There will be an initial training session just prior to encountering a known or probable H<sub>2</sub>S zone (within 3 days or 500 feet) and weekly H<sub>2</sub>S and well control drills for all**

personnel in each crew. The initial training session shall include a review of the site specific H<sub>2</sub>S Drilling Operations Plan. This plan shall be available at the well site. All personnel will be required to carry documentation that they have received the proper training.

## **II. H<sub>2</sub>S SAFETY EQUIPMENT AND SYSTEMS**

**Note:** All H<sub>2</sub>S safety equipment and systems will be installed, tested and operational when drilling reaches a depth of 500 feet above, or three days prior to penetrating the first zone containing or reasonably expected to contain H<sub>2</sub>S.

### **A. Well Control Equipment.**

- 1. Flare line with continuous pilot.**
- 2. Choke manifold with a minimum of one remote choke.**
- 3. Blind rams and pipe rams to accommodate all pipe sizes with properly sized closing unit.**
- 4. Auxiliary equipment to include: annular preventer, mud-gas separator, rotating head and flare.**

### **B. Protective Equipment for Essential Personnel:**

**Mark II Surviveair 30-minute units located in the dog house and at briefing areas, as indicated on well site diagram.**

### **C. H<sub>2</sub>S Detection and Monitoring Equipment:**

- 1. Two portable H<sub>2</sub>S monitors positioned on location for best coverage and response. These units have warning lights and audible sirens when H<sub>2</sub>S levels of 20 ppm are reached.**
- 2. One portable SO<sub>2</sub> monitor positioned near flare line.**

### **D. Visual Warning Systems**

- 1. Wind direction indicators are shown on well site diagram.**
- 2. Caution/Danger signs shall be posted on roads providing direct access to location. Signs will be**

**painted a high visibility yellow with black lettering of sufficient size to be readable at a reasonable distance from the immediate location. Bilingual signs will be used when appropriate. See example attached.**

**E. Mud Program**

- 1. The Mud Program has been designed to minimize the volume of H<sub>2</sub>S circulated to the surface. Proper mud weights, safe drilling practices and the use of H<sub>2</sub>S scavengers will minimize hazards when penetrating H<sub>2</sub>S bearing zones.**
- 2. A mud-gas separator will be utilized as needed.**

**F. Metallurgy:**

**All drill strings, casing, tubing, wellhead, blowout preventers, drilling spool, kill lines, choke manifold and line and valves shall be suitable for H<sub>2</sub>S service.**

**G. Communication:**

**Cellular telephone communications in company vehicles, rig floor and mud logging trailer.**

**H. Well Testing:**

**Drill stem testing will be performed with a minimum number of personnel in the immediate vicinity, which are necessary to safely and adequately conduct the test. The drill stem testing and an H<sub>2</sub>S environment will be conducted during the daylight hours.**