Form 3160-5 (September 2001)

Oil Cons. N.M. DIV-Dist. 2

FORM APPROVED OMB NO. 1004-0135

UNITED STATES 1301 W. Grand Avehue DEPARTMENT OF THE INTERIOR Artesia, NM 8821 Expires January 31, 2004 **BUREAU OF LAND MANAGEMENT** Lease Serial No. SUNDRY NOTICES AND REPORTS ON WELLS NM 04686

| Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals. | | | | | 6. If Indian, Allottee or Tribe Name | |
|--|--|---|--|--|--------------------------------------|--|
| SUBMIT IN TRIPLICATE - Other instructions on reverse side | | | | 7. If Unit or CA/Agreement, Name and/or No. SW 158 | | |
| 1. Type of Well X Oil Well Gas Well Other 2. Name of Operator | | RECE | 7803 | 8. Well Name and BRIGHT FEDER | | |
| KERR MOSEE OIL & GAS ONSHORE, ILC 3a. Address 16666 NORTHCHASE, HOUSTON, TEXAS 77060 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) | OCD-ARTESIA 3b. Phone No. (include area code) 281-673-6590 | | 9. API Well No. 30-015-28899 10. Field and Pool, or Exploratory Area INDIAN BASIN UPPER PENN | | | |
| 1900' FSL & 2200' FWL SE/4 NE/4 SW/4 SEC.21, TWP. 21S, RGE. 23E 12. CHECK APPROPRIATE BOX | (ES) TO IND | DICATE NATURE OF N | NOTICE, REP | 11. County or P. EDDY ORT, OR OTHE | NM | |
| TYPE OF SUBMISSION | TYPE OF ACTION | | | | | |
| Notice of Intent Subsequent Report X Final Abandonment Notice | Acidize Alter Casing Casing Repair Change Plans Convert to Injecti | Deepen Fracture Treat New Construction Plug and Abandon Plug Back | Reclamation Recomple | te [| Water Shut-Off Well Integrity Other | |

Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the final cities reach for final increation. determined that the final site is ready for final inspection.)

KERR MOGEE OIL & GAS ONSHORE, ILC REQUESTS APPROVAL TO PLUG AND ABANDON THE SUJECT WELL PER BLM SPECIFICATIONS AS THE ATTACHED PLUGGING PROCEDURE. IF YOU SHOULD HAVE ANY QUESTIONS OR CONCERNS PLEASE CONTACT DAVID EYLER @ 432.687.3033.

APPROVAL SUBJECT TO GENERAL REQUIREMENTS AND SPECIAL STIPULATIONS ATTACHED



| 14. I hereby certify that the foregoing is true and correct Name (Printed/Typed) | itle | | | | | |
|---|---------------------|------------------|--|--|--|--|
| DAVID A. EYLER | AGENT | | | | | |
| - Court V. C. S. | Date 12/11/03 | | | | | |
| THIS SPACE FOR FEDERALOSE STATE OFFICE USE | | | | | | |
| Approved by (ORIG. SGD.) ALEXIS C. SMCROBA (************************************ | TPETROLEUN ENGINEER | Data DEC 17 2003 | | | | |
| Conditions of approval, if any, are attached. Approval of this assiste does not warrant of certify that the applicant holds legal or equitable title toptobe rights in the subject least which would entitle the applicant to conduct operations thereon. | Office | | | | | |

Kerr McGee Oil & Gas Onshore, LLC

Bright Federal Gas Com #3 A.P.I. #: 30-015-28899

Lease Serial #: NM 04686

Field: Indian Basin Upper Penn

Location: 1900' FSL & 2200' FWL, SE/4 NE/4 SW/4, Sec. 21, Twp. 21S, Rge. 23E

Eddy County, New Mexico

Completion Date: 1996

Total Depth: 7,590' P.B.T.D.: 7507' (Fill)

Casing Data: 9-5/8" 36# K-55 @ 1285' w/ 960 sxs. - TOC = Surface

7" 23# K-55 @ 7272' w/ 365 sxs. – TOC = 5000' (Calc)

5-1/2" 15.5# J-55 FJ Liner @ 7162'-7462'

Tubing Data: 3-1/2" @ 7054' (Note: (11) jts. 2-7/8" below TAC

Rod Data: (88) 3/4", (108) 7/8", (86) 1"

Open Perfs: 7162'-7312' (1/2" holes @ 6 spf)

Remarks: None

PXA PROCEDURE

1) MIRU workover rig & PXA equipment.

- 2) ND wellhead & POOH laying down rods; NU BOP's; Release TAC & POOH w/3-1/2" tubing & TAC; Remove TAC & PU 7" CICR; RIH w/ CICR & tubing to 7150'; Set CICR & mix & sqz. a 100 sx. cmt. plug below CICR; Sting out of CICR & mix & pump a 15 sx. cmt. plug on top of CICR @ 7150'; Circ. well w/ pxa mud & POOH laying down tbg. to 6525'; Mix & pump a 25 sx. cmt. plug @ 6425'-6525'; POOH w/ tbg. standing back 4050' & laying down the balance.
- 3) ND BOP's & NDWH & NU csg. equip.; Work stretch on 7" csg.; RUWL & RIH & cut 7" csg. (estimated recovery = 4000'); POOH & RDWL; POOH laying down 7" casing.
- 4) ND csg. equip. & NUWH & NU BOP's; RIH w/ tubing OE to 4050'; Mix & pump a 75 sx. cmt. plug @ 4050'; POOH w/ tbg. & WOC; RIH w/ tbg. & tag top of cmt. plug; POOH laying down tbg. to 1340'; Mix & pump a 60 sx. cmt. plug @ 1340'; POOH w/ tbg. & WOC; RIH w/ tbg. & tag top of cmt. plug; POOH laying down tbg. to 400'; Mix & pump a 60 sx. cmt. plug @ 400'.
- 5) POOH laying down tubing to 63' & mix & pump a 30 sx. cmt. surf. plug @ 3'-63'. FOOH w/ tubing.
- 4) Dig out and cut off well head 3' B.G.L.; Weld steel plate on top of casings & set dry hole marker.
- 5) RDMO rig and PXA equipment. Clean location.

