

Submit 3 Copies To Appropriate District Office  
District I  
1625 N French Dr, Hobbs, NM 88240  
District II  
1301 W. Grand Ave, Artesia, NM 88210  
District III  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV  
1220 S. St Francis Dr, Santa Fe, NM 87505

State of New Mexico  
Energy, Minerals and Natural Resources

Form C-103  
June 19, 2008

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

WELL API NO. 30-015-37301

5. Indicate Type of Lease

STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name  
Limousine 15 M

8. Well Number 1

9. OGRID Number  
14744

10. Pool name or Wildcat  
Cemetery Yeso

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐

RECEIVED

2. Name of Operator  
Mewbourne Oil Company

OCT 26 2009

3. Address of Operator PO Box 5270  
Hobbs, NM 88241

NMOCD ARTESIA

4. Well Location

Unit Letter M : 990 feet from the South line and 660 feet from the West line  
Section 15 Township 20S Range 25E NMPM Eddy County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)  
3438'

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐  
DOWNHOLE COMMINGLE ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ P AND A ☐  
CASING/CEMENT JOB ☒

OTHER: ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

10/07/09...MI & spud 11" hole. Ran 815' 8 5/8" 24# J55 ST&C csg. Cemented with 100 sks Thixad Class H with additives. Mixed @ 14.6 #/g w/1.52 yd. Tail with 400 sks Class C with additives. Mixed @ 14.8 /g w/1.34 yd. Plug down @ 7:00 pm 10/08/09. Did not circ cmt. Slow rate lift pressure @ 210# @ 2 BPM. WOC. Ran temp survey indication TOC @ 260'. RIH with 1" pipe. Tag at 248'. Ran 1" pipe in 8 stages with 205 sks Thixad Class H with additives. Mixed @ 14.6 #/g w/ 1.52 yd. Circ 12 sks to pit. WOC 18 hrs. At 1:00 am 10/10/09 tested BOPE and casing to 1500# for 30 minutes, held OK. Drilled out with 7 7/8" bit.

10/13/09 TD'ed 7 7/8" hole @ 3212'. Ran 3212' 4 1/2" 11.6# J55 LT&C csg. Cemented w/300 sks BJ Lite Class C (50:50:10) with additives. Mixed @ 11.5 /g w/2.71 yd. Tail with 350 sks Class C with additives. Mixed @ 14.8/g w/1.33 yd. Plug down @ 2:45 am 10/13/09. Circ 122 sks cement to pit. At 2:45 am on 10/13/09, tested csg to 1725# for 30 mins, held OK. Set wellhead slips w/30k.

10/13/09...Released rig at 12:00 pm.

Spud Date: 10/07/09

Rig Release Date: 10/13/09

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Jackie Lathan TITLE Hobbs Regulatory DATE 10/22/09

Type or print name Jackie Lathan E-mail address: jlathan@mewbourne.com PHONE: 575-393-5905

For State Use Only

APPROVED BY: Jacqui Reyes TITLE Geologist DATE 10/28/2009

Conditions of Approval (if any):