Office District I  1625 N. French Dr., Hobbs, NM 88240 District II	New Mexico and Natural Resources	Form C-103 June 19, 2008 WELL API NO. 30-015-37044
District III 1000 Rio Brazos Rd , Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505  OIL CONSERVATION DIVISION 1220 South St. Francis Dr. Santa Fe, NM 87505		5. Indicate Type of Lease  STATE ☑ FEE ☐  6. State Oil & Gas Lease No.
SUNDRY NOTICES AND REPORTS ON (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEP DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM PROPOSALS.)  1. Type of Well: Oil Well Gas Well Other  2. Name of Operator	ı	7. Lease Name or Unit Agreement Name STALEY STATE  8. Well Number #5  9. OGRID Number 255333
LIME ROCK RESOURCES A, L.P.  3. Address of Operator	NMOCD ARTESIA	10. Pool name or Wildcat: (96836)
c/o Mike Pippin LLC, 3104 N. Sullivan, Farmington, NM 874		Red Lake, Glorieta-Yeso NE
4. Well Location		
Unit Letter H : 1650 feet from the NORTH line and 330 feet from the EAST line		
Section 30 Township 17-S Range 28-E NMPM Eddy County		
11. Elevation (Show whether DR, RKB, RT, GR, etc.)		
3595' GL		
NOTICE OF INTENTION TO:  PERFORM REMEDIAL WORK   PLUG AND ABANDON TEMPORARILY ABANDON   CHANGE PLANS PULL OR ALTER CASING   MULTIPLE COMPL DOWNHOLE COMMINGLE	REMEDIAL WORK COMMENCE DRIL CASING/CEMENT	LING OPNS. P AND A
OTHER: Spud & Surface & Production Casings		
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.		
Spud well on 10/27/09. Drilled 12-1/4" hole to 445'. Landed 8-5/8" 24# J-55 csg @ 434'. Cmted lead w/175 sx (236 cf) C cmt w/2% Cacl2 & 1/8# p-e-flake. Tailed w/200 sx (270 cf) C cmt w/2% Cacl2. Circ 133 sx cmt to surface. On 10/29/09, PT 8-5/8" csg to 1000 psi for 30 min – OK.		
Drilled 7-7/8" hole to TD4790' on 11/9/09. Ran open hole logs. Landed 5-1/2" 17# J-55 csg @ 4771'. Cmted lead w/500 sx (945 cf) 35/65 poz C cmt w/0.125# p-e-flake, 3# salt, & 3# gilsonite & tailed w/550 sx (732 cf) C cmt w/0.125# p-e-flake, 0.4% Lap-1, 0.5% CFR-3, & ½# D-air. Circ 142 sx cmt to pit. Released drilling rig on 11/9/09. On 11/18/09, PT 5-1/2" csg to 1000 psi for 30 min - OK.		
Spud Date: 10/27/09	Orilling Rig Release Date:	11/9/09
I hereby certify that the information above is true and complete to the best of my knowledge and belief.		
SIGNATURE Miles Tippin TITLE Petroleum Engineer - Agent DATE 11/23/09		
Type or print name Mike Pippin E-mail address: mike@pippinllc.com PHONE: 505-327-4573		
For State Use Only		
APPROVED BY: Acquired TITLE Conditions of Approval (if any):	E Geologist	DATE 119569
<i>'</i>		