

Submit 1 Copy To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
October 13, 2009

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO.

30-015-34606

5. Indicate Type of Lease

STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH
PROPOSALS)

1. Type of Well: Oil Well ☐ Gas Well ☒ Other ☐

2. Name of Operator

Mewbourne Oil Company

3. Address of Operator

PO Box 5270, Hobbs, NM 88241

4. Well Location

Unit Letter L : 1980' feet from the South line and 660' feet from the West line

Section 10 Township 20S Range 25E NMPM Eddy County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3440' GL

7. Lease Name or Unit Agreement Name

Long Draw 10 Fee Com

8. Well Number

1

9. OGRID Number

14744

10. Pool name or Wildcat

Cemetery Yeso 11795

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐

OTHER: Completion Sundry ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

08/28/09 POOH w/tbg. Set Isolation plug @ 9350' w/35' cmt. PBTD @ 9315'. Set Isolation plug @ 7600' w/35' cmt. PBTD @ 7565'. Perforate squeeze holes @ 4950' - 4951' (4 SPF, 8 holes).

08/29/09 Set cmt retainer @ 4860' cmt 4 1/2" x 8 5/8" annulus w/220 sks BJ Lite Class "C" (50:50:10) w/additives (Mixed @ 11.5#/g w/2.71 yd). Followed by 675 sks Class "C" w/additives. (Mixed @ 14.8#/g w/1.33 yd). Circ 5 sks to pit. POOH w/tbg. New PBTD @ 4840'. SD operations for cmt & evaluation of frac seismic study.

11/03/09 Perforate Yeso @ 2518' - 2853' selectively. 50', 1 SPF 50 holes, 0.40" EHD 120° phasing, 19 GC. Frac Yeso w/1000 gals 10% HCl & 400,000 gal 20# slickwater carrying 200,000# 20/40 sand. Flowback for cleanup.

11/06/09 RIH with tbg & pump. PWOL.

Spud Date: 06/01/06

Rig Release Date: 06/21/06

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Jackie Lathan TITLE Hobbs Regulatory DATE 02/15/10

Type or print name Jackie Lathan E-mail address: jlathan@mewbourne.com PHONE: 575-393-5905

For State Use Only

APPROVED BY: David Day TITLE Field Supervisor DATE 2-18-2010
Conditions of Approval (if any): submit a sundry with tubing detail