		٠ ")	
Submit 3 Copies To Appropriate District	State of New Mexico		Form C-103 7
Office District I	Energy, Minerals and Natural Resources		June 19, 2008
1625 N. French Dr., Hobbs, NM 88240			WELL API NO.
District II 1301 W. Grand Ave., Artesia, NM 88210	OIL CONSERVATION DIVISION		30-015-36249
District III	1220 South St. Francis Dr.		5. Indicate Type of Lease STATE FEE
1000 Rio Brazos Rd., Aztec, NM 87410 District IV	Santa Fe, NM 87505		6. State Oil & Gas Lease No.
1220 S. St Francis Dr., Santa Fe, NM 87505			o. State on te das Boase No.
SUNDRY NOTICES AND REPORTS ON WELLS 7. Lease Name or Unit Agreement Name			
(DO NOT USE THIS FORM FOR PROPODIFFERENT RESERVOIR. USE "APPL PROPOSALS.)	OSALS TO DRILL OR TO DEEPER	N OR PLUG BACK TO A	AID 24 STATE
PROPOSALS.)	ICATION FOR PERMIT" (FORM C	PEREIVED	
1. Type of Well: Oil Well	Gas Well Other	OLIVLD	8. Well Number #4
2. Name of Operator		MAR 09 2010	9. OGRID Number 255333
LIME ROCK RESOURCES A, L.P.		1	
3. Address of Operator		NMOCD ARTESIA	10. Pool name or Wildcat
Co white rippin BBC, 5104 N. Sumvan, raminigton, NW 67401			
4. Well Location			
Unit Letter I :		SOUTH_ line and 430	feet from the <u>EAST</u> line
Section 24		7-S Range 28-E	NMPM Eddy County
	11. Elevation (Show when 3678' GL	ther DR, RKB, RT, GR, etc.)	
	CHANGE PLANS MULTIPLE COMPL	SUBS REMEDIAL WORK COMMENCE DRIL CASING/CEMENT	SEQUENT REPORT OF: C
- · · · · · · · · · · · · · · · · · · ·	pleted operations. (Clearly s		give pertinent dates, including estimated date
of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.			
Spud well on 2/11/10. Drilled 12-1/4" hole to 365'. Landed 8-5/8" 24# J-55 csg @ 350'. Cmted lead w/175 sx (236 cf) C cmt w/2% Cacl2 & 1/8# p-e-flake. Tailed w/200 sx (270 cf) C cmt w/2% Cacl2. Circ 129 sx cmt to surface. On 2/11/10, PT 8-5/8" csg to 500 psi for 30 min – OK.			
Drilled 7-7/8" hole to TD5355' on 2/26/10. Ran open hole logs. Landed 5-1/2" 17# J-55 csg @ 5341'. Cmted lead w/550 sx (1029 cf) 35/65 poz C cmt w/0.125# p-e-flake, 3# salt, & 3# gilsonite & tailed w/650 sx (864 cf) C cmt w/0.125# p-e-flake, 0.4% Lap-1, 0.5% CFR-3, & ½# D-air. Circ 166 sx cmt to pit. Released drilling rig on 2/27/10. We plan to PT 5-1/2" csg during completion operations.			
Spud Date: 2/11/10	Dril	lling Rig Release Date:	2/27/10
I hereby certify that the information above is true and complete to the best of my knowledge and belief.			
SIGNATURE Mile	tippin TITLE	Petroleum Engineer - Ager	nt DATE <u>3/8/10</u>
Type or print name Mike Pippin E-mail address: mike@pippinllc.com PHONE: 505-327-4573			
For State Use Only			
APPROVED BY: Duald lies TITLE Field Supervisor DATE 3-15-10 Conditions of Approval (if any):			