



NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD

AREA 400 ACRES
LOCATE WELL CORRECTLY

Mail to Oil Conservation Commission, Santa Fe, New Mexico or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate approximate date by following it with (T). SUBMIT IN TRIPlicate FORM C-110 WILL NOT BE APPROVED UNTIL FORM C-105 IS PROPERLY FILLED OUT.

Artesia, New Mexico
Company or Operator
Russell
Well No. 7-1 In SE 1/4 35 of Sec. 35, T. 17-S
Lease
R. 27-E, N. M. P. M., Artesia, Field, Artesia, Eddy County
Well is 4950 feet south of the North line and 1650 feet west of the East line of Sec. 35
If State land the oil and gas lease is No. Assignment No.
If patented land the owner is Address
If Government land the permittee is Russell Address
The Lessee is aton Bros Address Artesia, New Mex.
Drilling commenced Dec. 14 1942 Drilling was completed Dec. 30th 1942
Name of drilling contractor aton Bros Address Artesia, New Mex.
Elevation above sea level at top of casing feet
The information given is to be kept confidential until 19

OIL SANDS OR ZONES

No. 1, from 450 to 455 No. 4, from to
No. 2, from 470 to 475 No. 5, from to
No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from None to feet
No. 2, from to feet
No. 3, from to feet
No. 4, from to feet

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED FROM TO	PURPOSE
8 1/2"	38	8	Lucas 138					

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
10"	8 1/2"	432	25	Halliburton		50 sacks

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set
Adapters—Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
		acidized with 1000 gallons, 12% acid from 450' to 475'				

Results of shooting or chemical treatment

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from feet to feet, and from feet to feet
Cable tools were used from 0 feet to 477 feet, and from feet to feet

PRODUCTION

Put to producing Dec. 30th, 1942
The production of the first 24 hours was 12 Bbls. per hour of fluid of which 100% was oil; % emulsion; % water; and % sediment Gravity, Be 36
If gas well, cu. ft. per 24 hours eight Gallons gasoline per 1,000 cu. ft. of gas
Rock pressure, lbs. per sq. in.

EMPLOYEES

W. E. Fleming, Driller
L. Davis, Driller
H. M. Willey, Driller
Ralph Yoder, Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Artesia, New Mex.
Subscribed and sworn to before me this 29 day of Jan 1943
Notary Public
My Commission expires Aug 19, 1944
Name: Eaton Bros
Position: President
Representing: Eaton Bros
Company or Operator
Address: Artesia, New Mex.

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	70	70	Anhydrite Red Rock
70	125	55	Anhydrite
125	145	20	Anhydrite
145	210	65	Red Rock
210	250	40	Red Rock
250	265	15	Broken Anhydrite
265	295	30	Red Rock
295	310	15	Red Rock
310	345	35	Anhydrite
345	365	20	Red Rock
365	380	15	Anhydrite
380	385	05	Red Rock
385	427	42	Anhydrite
427	432	05	Anhydrite
432	437	05	Anhydrite
437	460	23	Anhydrite
460	455	05	Oil
455	470	15	Anhydrite
470	475	05	Oil
475	477	02	Anhydrite.