

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Oil Cons.
N.M. DIV-Dist. 2
1301 W. Grand Avenue
Artesia, NM 88210

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

RECEIVED

JAN 27 2004

OCD-ARTESIA

1 Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Mack Energy Corporation

3. Address and Telephone No.

P.O. Box 960, Artesia, NM 88211-0960

(505)748-1288

4. Location of Well (Footage, Sec., T. R., M. or Survey Description)

1980 FNL & 660 FWL, Sec. 21-T17S-R28E, E

5. Lease Designation and Serial No.

LC-046250A

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Red Lake Sand Unit #32

9. API Well No.

30-015-01492

10. Field and Pool, or Exploratory Area

Red Lake; Queen-Grayburg-SA

11. County or Parish, State

Eddy, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☒ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☒ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other _____
- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13 Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work)*

Mack Energy Corporation proposes to plug and abandon well as follows:

1. Notify BLM 24 hours prior to starting plugging operations.
2. Set 100' plug from 1679-1579'. WOC and tag.
3. Circulate hole w/mud gel.
4. Perforate @ 500' squeeze 100' plug.
5. Perforate @ 60' circulate cement to surface.
6. Install dry hole marker.

APPROVED

JAN 23 2004

LES BABYAK
PETROLEUM ENGINEER

Accepted for record - NMOCED

14. I hereby certify that the foregoing is true and correct

Signed

Geny W. Shervell

Title

Production Clerk

Date

1/14/04

(This space for Federal or State office use)

Approved by

Conditions of approval, if any:


Title

Date

MACK ENERGY CORPORATION
RED LAKE SAND UNIT #32
Sec 21 T17S R28E 1980 FNL 660 FWL

BLM


BEFORE



7" csc @ 1529' C/w 50sks

Open Hole 1529'-1962'

AFTER



1. Notify BLM 24 hrs. prior to any work done.
2. Set 100' cmt plug 1679'-1579' and tag.
3. Circ hole with mud gel.
4. Perf @ 500 squeeze cmt 100' plug
5. Perf @ 60' circ cmt to surface
6. Install Dry Hole Marker