Form 3160-5 -(August 2007)

## UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

## SUNDRY NOTICES AND REPORTS ON WELLS

	FORM APPROVED
Artesia	OMB No 1004-0137
	Expues July 31, 2010
CEIVE	

	<b>—</b> !	V	5 Lea	e Serial	Ν
4 D D	_		NM-	53219	

OCD

Do not use this form for proposals to drill or to	re-enter an AP	P - C 0010	NM-53219		
abandoned well. Use Form 3160-3 (APD) for suc	· · · · · · · · · · · · · · · · · · ·	R -6 2010	NIA	e or Tribe Name	
SUBMIT IN TRIPLICATE - Other instru	NMOC ctions on page 2.	D ARTES	Af Unit or CA/Agre	reement, Name and/or No	
1 Type of Well			NM-112743		
Oil Well X Gas Well Other			8 Well Name and N	No	
2 Name of Operator			Whitbread BF	G Federal Com #1	
Yates Petroleum Corporation			9 API Well No		
3a Address 3b Phone No (include area code)			30-015-33932		
105 S. 4th Str., Artesia, NM 88210	575-748-1471		10 Field and Pool or Exploratory Area		
4 Location of Well (Footage, Sec ,T.,R ,M , OR Survey Description)			McKittrick Hill	ls; Morrow	
			11 County or Paris	h, State	
1980'FNL & 660'FWL of Section 1-T22S-R24E (Unit E,	SWNW)		Eddy County,	, New Mexico	
12 CHECK APPROPRIATE BOX(ES) TO IND:	ICATE NATURE OF I	NOTICE, REI	PORT, OR OT	HER DATA	
TYPE OF SUBMISSION	TYPE C	F ACTION			
Acidize	Deepen	X Production (S	tart/Resume)	Water Shut-Off	
Notice of Intent Alter Casing	Fracture Treat	Reclamation		Well Integray	
Casing Repair	New Construction	X Recomplete		Other	
Subsequent Report		-		Other	
Change Plans	Plug and Abandon	Temporarily /	\bandon		
Final Abandonment Notice Convert to Injection	Plug Back	Water Dispos	al		
13 Describe Proposed of Completed Operation Clearly state all pertinent details, including	g estimated starting date of any pro-	oposed work and app	proximate duration ther	reof If	
the proposal is to deepen directionally or recomplete honzontally, give subsurface local Attach the Bond under which the work will be performed or provide the Bond No on					
following completion of the involved operations of the operation results in a multiple of	2				
testing has been completed. Final Abandonment Notices must be filed only after all re- determined that the site is ready for final inspection.	quirements, including reclamation,	, have been complete	ed and the operator has	s	
1/24/10 Began recompletion, NU BOP.					
1/25/10 Wireline set a cement retainer at 7800'. Sting into	o retainer				
/26/10 Squeezed Penn 7922'-8006' with 160 sx Class "H" cement and 150 sx Class "H" cement. Good squeeze to 2000 psi.					
Stung out of retainer. Reverse circulate 21 bbls of			,,,,	, o 2 0 1 0 1 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	
1/28/10 Tagged retainer at 7800'. Drilled out retainer. Cit		_	8010'-		
1/10 Wireline set 7" cement retainer at 7798'. Sting into retainer.					
/4/10 Re-squeezed Penn with 50 sx Thixtropic Class "H" and 50 sx Class "H". Did not squeeze.					
2/5/10 Re-squeezed Penn with 50 sx Class "H", 150 sx Thixtropic Class "H" and 100 sx Class "H" cement. Did not squeeze.					
Pumped 100 sx Thixtropic Class "H" and 200 sx C					
2/9/10 Re-squeezed with 400 sx Class "H" cement. Stin					
		CONTIN	ווובט טא אובי	VT DACE:	
		CONTIN	IUED ON NEX	AT FAGE.	
14 I hereby certify that the foregoing is true and correct					
Name (Printed/Typed)					
Tina Huerta	Title Regulati	tory Complia	hee/Subervise	מת תחת תחת חול	

14 I hereby certify that the foregoing is true and correct				
Name (Printed/Typed)	1	•		
Tına Huerta	Title	Regulatory Comp	liance Supervisor	LUD DLUUDD
11			LUOUTI ITA	HOR RECORD
Signature (Jana) Leura	Date	March 10, 2010		
THIS SPACE FOR FE	EDERAL OR	STATE OFFICE USE	ADD	4 2010
Approved by		Title	Date	2010
Conditions of approval, if any, are attached. Approval of this notice does not we certify that the applicant holds legal or equitable title to those rights in the subjective which would entitle the applicant to conduct operations thereon.		Office	BUREAU OF L	AND MANAGEMENT
Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for	or any person k	nowingly and willfully to mal	ke to any department or/a	gendy of the Ψηιίed States
any false, fictitious or fraudulent statements or representations as to any matter w	rithin its jurisdic	chon		0.00
(Instructions on page 2)				038 4-8-10

Yates Petroleum Corporation Whitbread BFG Federal Com #1 Section 1-T22S-R24E Eddy County, New Mexico Page 2

## Form 3160-5 continued:

2/10/10 2/11/10	Sting into retainer at 7798'. Pressured casing to 1200 psi, good.  Drilled out retainer. Retainer fell to 7945'. Drilled on soft cement. Cement fell out at 8051'. Circulated clean. Pressure tested to 500 psi in 45 min, pressure dropped to 345 psi.
2/14/10	Cleaned well to 8468', top of 4-1/2" liner. Circulated clean.
2/15/10	Cleaned out 4-1/2" liner to 9268'. Circulated clean.
2/16/10	Cleaned well out down to 10,510'. Circulated clean.
2/18/10	Perforated Morrow 10,110'-10,116' (37), 10,128'-10,134' (37), 10,232'-10,246' (85) and
	10,282'-10,290' (49). Acidized 10,232'-10,290' with 1500g Clay Safe "H" acid.
2/21/10	Acidized Morrow 10,110'-10,134' with 1000g Clay Safe "H" acid. 2-7/8" tubing and
	packer at 10,174'.
3/6/10	Date of 1st production for recompletion - Morrow

Regulatory Compliance Supervisor

March 10, 2010