

Submit 1 Copy To Appropriate District
Office
District I
1625 N French Dr., Hobbs, NM 88240
District II
1301 W Grand Ave, Artesia, NM 88210
District III
1000 Rio Brazos Rd, Aztec, NM 87410
District IV
1220 S St Francis Dr, Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
October 13, 2009

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO.
30-015-21720

5. Indicate Type of Lease

STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH
PROPOSALS)

1. Type of Well: Oil Well ☐ Gas Well ☐ Other

2. Name of Operator
Yates Petroleum Corporation

3. Address of Operator
105 South Fourth Street, Artesia, NM 88210

4. Well Location
Unit Letter N : 330 feet from the South line and 2310 feet from the West line
Section 12 Township 17S Range 25E NMPM Eddy County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3454'GR

7. Lease Name or Unit Agreement Name
Norris FK

8. Well Number
1

9. OGRID Number
025575

10. Pool name or Wildcat
Undes. Eagle Creek; San Andres

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Yates Petroleum Corporation plans to plug and abandon this well as follows:

NOTE: This well has previously been plugged and a CIBP is located at 1350' inside 4-1/2" casing and has been capped with 35' cement

1. MIRU WSC. Rig up any safety equipment as needed. Weld a bell nipple on the 5-1/2" casing and NU BOP.
2. Spot a 105 sx cement plug at 1262' across the intermediate casing and surface casing shoe. This will leave a surface plug from 0-1262'. WOC and tag plug, reset if necessary.
3. Cut casing off below ground and install a below ground dry hole marker as per Director Fesmire's letter date May 13, 2010. Rig down and allow the construction crew to continue to build and pave the parking lot.

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Tina Huerta TITLE Regulatory Compliance Supervisor DATE June 15, 2010

Type or print name Tina Huerta E-mail address: tinah@yatespetroleum.com PHONE: 575-748-4168

For State Use Only

APPROVED BY: Miguel Hernandez TITLE DIST II DATE 6/15/10

Conditions of Approval (if any):

WELL NAME: Norris FK #1 FIELD: _____
 LOCATION: 330' FSL & 2310' FWL of Section 12-17S-25E Eddy Co., NM
 GL: 3,454' ZERO: _____ KB: _____
 SPUD DATE: 1/19/76 COMPLETION DATE: 2/1/76
 COMMENTS: API No.: 30-015-21720

CASING PROGRAM

10-3/4" 32#	330'
7"	1,212'
4-1/2 10.5# 40 596'	
5-1/2 14# J-55 968'	1,566'

15" Hole

9-1/2" Hole

6-1/4" Hole

10-3/4" @ 330' w/200 sx

Before

TOPS

SA 786'

7" @ 1,212' w/500 sx (Circ) Cmt
dropped. Filled hole w/2-1/2 yds Ready-
mix

CIBP @ 1,350' w/ 35'

SA Perfs: 1,367-1,509' (32)

TD: 1,566"

4-1/2" @ 1,566' w/150 sx
(Circ)

Not to Scale

6/15/10
DC/Hill

WELL NAME: Norris FK #1 FIELD: _____
 LOCATION: 330' FSL & 2310' FWL of Section 12-17S-25E Eddy Co., NM
 GL: 3,454' ZERO: _____ KB: _____
 SPUD DATE: 1/19/76 COMPLETION DATE: 2/1/76
 COMMENTS: API No.: 30-015-21720

CASING PROGRAM

10-3/4" 32#	330'
7"	1,212'
4-1/2 10.5# 40 596'	
5-1/2 14# J-55 968'	1,566'

15" Hole

9-1/2" Hole

6-1/4" Hole

10-3/4" @ 330' w/200 sx

Cmt Plug 0-1,262'

7" @ 1,212' w/500 sx (Circ) Cmt
dropped. Filled hole w/2-1/2 yds Ready-
mix

After

TOPS

SA 786'

CIBP @ 1,350' w/ 35'

SA Perfs: 1,367-1,509' (32)

TD. 1,566"

4-1/2" @ 1,566' w/150 sx
(Circ)

Not to Scale
6/15/10
DC/Hill