

Submit 3 Copies To Appropriate District Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
June 19, 2008

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-015-37672
5. Indicate Type of Lease STATE ☒ FEE ☐
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name NO BLUFF 36 STATE COM
8. Well Number #10
9. OGRID Number 255333
10. Pool name or Wildcat: (96836) Red Lake, Glorieta-Yeso NE
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3595' GL

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-104 FOR SUCH PROPOSALS.)	
1. Type of Well: Oil Well ☒ Gas Well ☐ Other	RECEIVED
2. Name of Operator LIME ROCK RESOURCES A, L.P.	JUN 22 2010
3. Address of Operator c/o Mike Pippin LLC, 3104 N. Sullivan, Farmington, NM 87401	NMOCD ARTESIA
4. Well Location Unit Letter D : 330 feet from the NORTH line and 890 feet from the WEST line Section 36 Township 17-S Range 27-E NMPM Eddy County	
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3595' GL	

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐

OTHER: ☐

OTHER: Completion ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

On 6/4/10, PT 5-1/2" csg to 5000 psi for 30 min-OK. Perfed lower Yeso @ 4094'-96', 4109'-11', 4149'-51', 4176'-78', 4211'-13', 4229'-31', 4248'-50', 4290'-92', 4352'-53', 4366'-68', 4396'-98', 4429'-31', 4468'-70', 4493'-95', 4509'-11' w/2-0.42" spf. Total 60 holes. Treated w/3616 gal 15% NEFE acid & 120 perf balls. On 6/8/10, fraced lower Yeso w/132,652# 16/30 & 33,131# 16/30 super LC sand in 20# X-linked gel. Spotted 1000 gal 15% NEFE acid on flush across 2nd stage perfs.
Set 5-1/2" CBP @ 4014'. PT csg to 4000 psi for 30 min-OK. Perfed middle Yeso @ 3577'-79', 3618'-20', 3656'-58', 3668'-70', 3681'-83', 3701'-03', 3718'-20', 3782'-84', 3792'-94', 3849'-51', 3880'-82', 3899'-3901', 3915'-17', 3938'-40', 3963'-65' w/2-0.42" spf. Total 60 holes. Treated perfs w/3545 gal 15% NEFE acid & 120 perf balls. Fraced w/114,336# 16/30 & 33,458# super LC 16/30 sand in 20# X-linked gel. Spotted 1000 gal 15% NEFE acid on flush across 3rd stage perfs.
Set 5-1/2" CBP @ 3550'. PT csg to 4000 psi for 30 min-OK. Perfed upper Yeso @ 3159'-61', 3195'-97', 3219'-21', 3242'-44', 3270'-72', 3311'-13', 3327'-29', 3347'-49', 3379'-81', 3401'-03', 3424'-26', 3451'-53', 3476'-78', 3489'-91', 3503'-04', 3517'-18' w/2-0.42" spf. Total 60 holes. Treated perfs w/6237 gal 15% NEFE acid & 120 perf balls. Fraced w/155,400# 16/30 & 48,575# super LC 16/30 sand in 20# X-linked gel.
On 6/9/10, MIRUSU. Drilled CBPs @ 3550' & 4014' & CO to PBTD4598'. On 6/10/10, landed 2-7/8" 6.5# J-55 tbg @ 4485. Ran pump & rods. Released completion rig on 6/14/10.

Spud Date: 5/8/10 Drilling Rig Release Date: 5/20/10

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Mike Pippin TITLE Petroleum Engineer - Agent DATE 6/19/10

Type or print name Mike Pippin E-mail address: mike@pippinllc.com PHONE: 505-327-4573

For State Use Only

APPROVED BY: Donald Gray TITLE Field Supervisor DATE 7/6/10

Conditions of Approval (if any):