Office	Appropriate District State of New Mexico Energy, Minerals and Natural Resources	
1625 N. French Dr., Hobbs, NM 88240		WELL API NO. 30-015-37850
1301 W. Grand Ave., Artesia, NM 88210 OIL CONS		
District III 1000 Rio Brazos Rd, Aztec, NM 87410 District IV  1220 South St. Francis Dr. Santa Fe, NM 87505		STATE X FEE  6. State Oil & Gas Lease No.
1220 S St Francis Dr., Santa Fe, NM 87505		L-3355
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A		7. Lease Name or Unit Agreement Name
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS)		Parkway 26 State Com  8. Well Number
1. Type of Well: Oil Well X Gas Well  Other	RECEIVED	4H
2. Name of Operator Mewbourne Oil Company	JUN <b>2 2</b> 2010	9. OGRID Number 14744
3. Address of Operator		10. Pool name or Wildcat
PO Box 5270, Hobbs, NM 88241	NMOCD ARTESIA	Turkey Track Bone Spring 60660
4. Well Location  Unit Letter_M: 380' feet from the South line and 330' feet from the West line		
Section 26 Township 19S Range 29E NMPM Eddy County		
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3319' GL		
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data		
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:		
PERFORM REMEDIAL WORK  PLUG AND ABANDON  REMEDIAL WORK  ALTERING CASING  TEMPORARILY ABANDON  CHANGE PLANS  COMMENCE DRILLING OPNS. PAND A		
TEMPORARILY ABANDON		
DOWNHOLE COMMINGLE	_	
OTHER:	☐ OTHER:	
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date		
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.		
r · r · · · · · · · · · · · · · · · · ·		
06/03/10MI & spud 26" hole. TD'd hole @ 243'. Ran 243' 20" 94# K55 BT&C csg. Cemented with 300 sks BJ Lite Class "C"		
(35:65:6) with additives. Mixed @ 12.5 #/g w/ 2.05 yd. Tail with 200 sks Class "C" additives. Mixed @ 14.8 #/g w/ 1.34 yd. Plug down @ 8:30 pm 06/04/10. Circ 107 sks to pit. WOC 18 hrs. Drilled out with 17 ½" bit.		
06/11/10TD'ed 17 ½" hole @ 1502'. Ran 1502' 13 ¾" 48/54.5# J55 ST&C Csg. Cemented with 850 sks BJ Lite "C" (35:65:6) with		
additives. Mixed @ 12.5 /g w/ 2.05 yd. Tail with 200 sks Class "C" w/2% CaCl2. Mixed @ 14.8 #/g w/ 1.34 yd. Plug down		
@ 5:00 pm 06/10/10. Circ 95 sks to pit. WOC 18 hrs. Drilled out with 12 1/4" bit.		
Spud Date: 06/03/2010	Rig Release Date:	
I hereby certify that the information above is true and complete to the best of my knowledge and belief.		
SIGNATURE Lathan	TITLE_ Hobbs Regulatory	DATE_06/21/10
Type or print name <u>Jackie Lathan</u> E-mail address: jlathan@mewbourne.com PHONE: 575-393-5905 For State Use Only		
APPROVED BY: Conditions of Approval (if any):	ntle Field Supervi	SOT DATE 7-6-10