

Submit 1 Copy To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
October 13, 2009

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-015-37850
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. L-3355
7. Lease Name or Unit Agreement Name Parkway 26 State Com
8. Well Number 4H
9. OGRID Number 14744
10. Pool name or Wildcat Turkey Track Bone Spring 60660

RECEIVED

JUN 23 2010

NMOCD ARTESIA

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/>	
2. Name of Operator Mewbourne Oil Company	
3. Address of Operator PO Box 5270, Hobbs, NM 88241	
4. Well Location Unit Letter M : 380' feet from the South line and 330' feet from the West line Section 26 Township 19S Range 29E NMPM Eddy County	
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3319' GL	

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☒

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

06/17/10...TD 12 1/4" hole at 3523'. Ran 3523' 9 5/8" 36# J55 ST & C & LT&C csg. Cemented with 180 sks Thixad Class H /additives. Mixed @ 14.6 #/g w/ 1.52 yd. Followed w/700 sks BJ Lite Class C (50:50:10) w/additives. Mixed @ 11.7#/g w/2.53 yd. Tail w/200 sks Class C w/2% CaCl2. Mixed @ 14.8 #/g w/ 1.34 yd. Plug down @ 4:30 pm 06/16/10. Did not circ cmt. Slow rate lift pressure @ 830# @ 3 BPM. WOC. Ran temp survey indication TOC @ 1210'. RIH with 1" pipe. Tag at 1627'. Ran 1" pipe in 2 stages with 150 sks Class C w/4% CaCl2. Mixed @ 14.8 #/g w/1.34 yd, and 100 sks Thixad H 12/2. Mixed @ 14.6 #/g w/1.52 yd. Tag 1" pipe @ 344'. Circulated 18 sks to pit. Tested BOPE to 2500# and Annular to 1500#. 06/18/10 tested casing to 1500# for 30 minutes, held OK. Drilled out with 8 3/4" bit.

Spud Date: 06/03/2010

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Jackie Lathan TITLE Hobbs Regulatory DATE 06/21/10

Type or print name Jackie Lathan E-mail address: jlathan@mewbourne.com PHONE: 575-393-5905

For State Use Only

APPROVED BY: David Gray TITLE Field Supervisor DATE 7-6-10
Conditions of Approval (if any):