

Submit 1 Copy To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
October 13, 2009

OIL CONSERVATION DIVISION

1220 South St. Francis Dr.
Santa Fe, NM 87505

RECEIVED

AUG - 2 2010

INMOOD ARTESIA

WELL API NO.

30-015-28181

5. Indicate Type of Lease

STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

West Red Lake Unit

8. Well Number

42

9. OGRID Number

6137

10. Pool name or Wildcat

San Andres

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN A WELL IN A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Devon Energy Production Company, LP

3. Address of Operator

20 North Broadway, Oklahoma City, OK 73102

405.552.4615

4. Well Location

Unit Letter O 330 feet from the South line and 1650 feet from the East line

Section 7 Township 18S Range 27E NMPM County Eddy

11. Elevation (Show whether DR, RKB, RT, GR, etc.)

3290' KB; 3282' GL

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

SUBSEQUENT REPORT OF

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS ☐ P AND ☐
CASING/CEMENT JOB ☐

OTHER: RE-ENTER /SIDETRACK ☐

OTHER:

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7 14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Proposed Plug & Abandonment

1. MIRU TIH and tag CIBP @ 1047' Circulate hole w/10 ppg mud.
2. Spot 25 sx cement on CIBP @ 1047'. WOC & Tag. (Calc TOC @ 800' 8-5/8" csg shoe @ 900')
3. Circulate 25 sx cement from 240' to surface. (13-3/8" csg shoe @ 174')
4. Cut casings off 3' below ground level
5. Set dry hole marker

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Ronnie Slack TITLE Operations Technician DATE 7/30/10

Type or print name Ronnie Slack E-mail address: Ronnie.Slack@dmn.com PHONE: 405.552.4615

For State Use Only

APPROVED BY [Signature] TITLE DATE 8/3/2010

Conditions of Approval (if any):

Approval Granted providing work
is complete by 11/3/2010

DEVON ENERGY PRODUCTION COMPANY LP

Well Name: WEST RED LAKE UNIT #42		Field: RED LAKE	
Location: 330' FSL & 1650' FEL; SEC 7-T18S-R27E		County: EDDY	State: NM
Elevation: 3290' KB; 3282' GL, 8' KB-GL		Spud Date: 1/28/95	Compl Date: 3/6/95
API#: 30-015-28181	Prepared by: Ronnie Slack	Date: 7/30/10	Rev:

PROPOSED P&A

17-1/2" hole

13-3/8", 48#, H40, STC, @ 174'

Cmt'd w/300 sx + topped out w/ready mix to surface

12-1/4" Hole

8-5/8", 24#, J55, @ 900'

Cmt'd w/450 sx to surface

10 ppg mud

Proposed:

1. Clrc 25 sx cmt from 240' to surface.
2. Cut casings off and set dry hole marker

Proposed:

1. Tag CIBP @ 1047
2. Spot 25 sx cmt on CIBP
3. WOC & Tag. (Calc TOC @ 800')

CIBP @ 1047' (7/27/06)

SAN ANDRES PERFED INTERVAL

1072' - 1086' (5/95) Sqzd w/75 sx (3/99) →

1477' - 1596' (5/95)

1645' - 1696' (3/95)

1713' - 1794' (3/95)

1836' - 1846' (3/95)

1852' - 1890' (3/95)

7-7/8" Hole

5-1/2", 15.5#, J55, @ 2008'

Cmt'd w/350 sx to surface

1920' PBDT

2,010' TD

DEVON ENERGY PRODUCTION COMPANY LP

Well Name: WEST RED LAKE UNIT #42		Field: RED LAKE	
Location: 330' FSL & 1650' FEL, SEC 7-T18S-R27E		County: EDDY	State: NM
Elevation: 3290' KB; 3282' GL; 8' KB-GL		Spud Date: 1/28/95	Compl Date: 3/6/95
API#: 30-015-28181	Prepared by: Ronnie Slack	Date: 7/30/10	Rev

CURRENT SCHEMAT

17-1/2" hole
13-3/8", 48#, H40, STC, @ 174'
 Cmt'd w/300 sx + topped out w/ready mix to surface

12-1/4" Hole
8-5/8", 24#, J55, @ 900'
 Cmt'd w/450 sx to surface

2-7/8" Tubing (not sure of tubing depth)

CIBP @ 1047' (7/27/06)

SAN ANDRES PERFED INTERVAL

1072' - 1086' (5/95) Sqzd w/75 sx (3/99) →

1477' - 1596' (5/95)

1645' - 1696' (3/95)

1713' - 1794' (3/95)

1836' - 1846' (3/95)

1852' - 1890' (3/95)

7-7/8" Hole
5-1/2", 15.5#, J55, @ 2008'
 Cmt'd w/350 sx to surface

1920' PBDT

2,010' TD